

#23 30-039-07104

#96 30-039-07108

4803

#112 30-039-07099

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 9 Twp 27 Rng 6

Name of Well/Wells or Pipeline Serviced SAN JUAN 28-6 UNIT #23, #96, #112
cps 681w

Elevation 6478' Completion Date 12/29/65 Total Depth 420' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

Type & amount of coke breeze used: 4400 lbs.

OIL CON. DIV
DIST. 3

Depths anodes placed: 362', 356', 350', 344', 338', 332', 326', 320', 314', 308'

Depths vent pipes placed: 362' OF 3/4" HOSE

Vent pipe perforations: BOTTOM 100' , 1' INTERVALS

Remarks: qgb #1

qgb #1 & qgb #2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

Date 12-29-65

cm# 4 3/4 Drag = 100' #3

Well Name SUJ 28-6 #96, #23 & #112		CPS No. 681W	
Location SW 9-27-6		Work Order No. 53914 184 - 52627-50-20	
Anode Hole Depth 420	Total Drilling Rig Time 42 1/2 Hrs.	Type & Size Bit Used 7 7/8 10035-340	No. Sacks Mud Used 4
No. Sacks Lost Circulation Mat'l Used 1	Anode Depth #1 326 #2 356 #3 350 #4 344 #5 338 #6 332		
Total Lbs. Coke Used 4400	Anode Output (Volts) #1 4.0 #2 4.3 #3 4.3 #4 5.0 #5 4.9 #6 4.5		
Total Circuit Resistance Volts 12.2 Amps 11.0 Ohms 1.1	No. Ft. Surface Cable Conduit		

Drilling Log (Attach Hereto) ☐

Remarks: R/S 600' SW 28-6 #112 = .76 4 Notch

600' S #23 = .78 1 Notch

600' S #96 = .78 3 Notch

3/4" Plastic Hose to Bottom Anode - Hose Perforated

Approx 1' intervals Bottom 100'

4 lbs Chemical to G.B

Install Good All Rectifier 45V 30A (4 NEG) Set # 65C 6640

ANODES - 3550 #8 WIRE

Plowed Wire - 2417' #8 WIRE

5967'

All Construction Completed

(Signature)

GROUND BED LAYOUT SKETCH



