This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

## **NEW MEXICO OIL CONSERVATION DIVISION**

Page 1 Revised June 10, 2003

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Operator: Williams Production			WellLease Name: <u>Inidan I</u> No#001								
Location Of W	ell: Unit Letter:_	<u>D</u> Sec <u>28</u>	Twp3 Rg	e <u>27</u> API	# <u>30-30</u> 039072460	<u>o</u>					
	Name of Rese	Type of Prod. (Oil or Gas)		Method of Pro (Flow or Art. L							
Upper Completion	PICURED CLIES		GA5		71000	TUBING					
Lower Completion	MESA VAROE		GA5		FLOW	TUBING					
Pre-Flow Shut-In Pressure Data											
Upper Completion	Hour, Date, Shut	Length of Time Shut-In 72 HAS		SI Press. Psig 225	Stabilized? (Yes or No)						
Lower Completion	Hour, Date, Shut-In 10 9/14- 4-20-07		Length of Time 72 /		SI Press. Psig	Stabilized? (Yes or No)					
Flow Test No. 1											
Commenced at (hour, date)*9% 4-24-07 Zone producing (Upper or Lower): Lowel.											
Time (Hour, Date)	Lapsed Time Since*	Pre Upper Compl.	ssure Lower Compl.	Prod. Zo Temp							
99/1-2407	72 MS	225	625	30	STATICAL	STATES LOWER ZONE FLOW					
4-25-07	24	225	210	35	· LOWER Z	LOWER ZONE FLOWING.					
4-26-07	24	225	180	42	· lower	STATES UPPER ZONE HOW TEST COMPLETED					
4-26-07	24	225	180	42	STATRE	STATES UPPER ZONE ZON					
	,				TEST	Conflet tel					
Production rate during test											
Oil:BOPD based onBbls. InHrsGravGOR											
Gas: 140 MCFPD; Test thru (Orifice or Meter): MYTEL											
Mid-Test Shut-In Pressure Data											
		Length of Time Shut-In		SI Press. Psig	Stabilized? (Yes or No)						
Lower Completion	· · · · · · ·		Length of Time Shut-In		SI Press. Psig	Stabilized? (Yes or No)					
(Continue on reverse side)											

RCVD APR27'07 OIL CONS. DIV. DIST. 3

## Flow Test No. 2

	<u> </u>		Flow Test 1	10. 2				
Commenced a	t (hour, date)**		Zo	Zone producing (Upper or Lower):				
Time	Lapsed Time	Pressure		Prod. Zone	Remarks			
(Hour, Date)			Lower Compl.	Temp.				
			<u> </u>					
			_					
	_		_					
						<u> </u>		
Production rate								
Oil:BOPD based onBbls. In Gas:MCFPD; Test thru (Orifice or Meter): _			_Bbls. In	Hrs	Grav	GOR		
Gas:	MCFP	D; Test thru (Ori	fice or Meter):					
Remarks:								
I hereby certify	that the informa	tion herein contai	ned is true and cor	nplete to the best	of my knowleds	ge.		
		APR 2 7 ZU	الا 20	17	Millian	Wade not on		
Approved			Operator	VICCINAS	THOOCETION			
New Mexico C	il Conservation I	Division		-70	Ole	dame in the		
. 1	1 0 -1.1	•	By	Operator Williams Pladueties  By Tomy Chemins  Title FIRLD TROLL				
_ //	illanver	7. <del>-</del>	7	DICID TENI				
				Title	nus tat	<u> </u>		
DEP!	JTY OIL & GAS INS	PECTOR, DIST.						
Title		· · · · · · · · · · · · · · · · · · ·	E-mail Address					
				1	26-07			
				Date	20-07			

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).