UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RCVD APR18'07 OIL CONS. DIV. DIST. 3

Sundry Notices and Reports on Wells	2007 APR 16 FN	3: 21	
	RECEIVED	5.	Lease Number SF-078960
Type of Well GAS	210 FARMURET	્ 6 ⊵્	If Indian, All. or Tribe Name
Name of Operator		7.	Unit Agreement Name
ConocoPhillips		0	San Juan 29-6 Unit Well Name & Number
Address & Phone No. of Operator		8.	
PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	SJ 29-6 Unit #71C API Well No.
Location of Well, Footage, Sec., T, R, M		=	30-039-29867
erf Unit L (NWSW), 2070' FSL & 220' FWL, Sec. 16, T29N, I	DAW NMPM	10.	Field and Pool
ott Unit I (NESE), 1900' FSL & 10' FEL, Sec. 17, T29N, R6W			Dlanga Masa Vayda
,		11.	Blanco MesaVerde County and State
_			Rio Arriba Co., NM
Describe Proposed or Completed Operations 7/07 MIRU AWS 711. NU. PT casing 600# 30/min - good test. RIH w/8 ¾" bit. //07 While drilling 8 ¾" hole, lost bit & part of directional motor @ 1935'. A	tempted to fish & lost overshot, ex		
th @ 1935. Want to set plug @ 1600' & TOC @ 1400', & then kickoff from the Monanted to have them try & put cement @ 50' above fish, but if unsuccess wato (BLM) & Henry Villanueva (OCD).	here with side track. Nocimento @ ful, the cement plug from 1400' – 1	1147', (600' is (Djo Alamo @ 2447'. DK. Approval received from Jim
/07 RU to cement Pumped 200 sx(214cf-38bbls) Class G Cement w/3% KCL. K 27'. WOC.			•
1/07 PU directional BHA, timed drilling, time drill to sidetrack. Drilled ahead to 3 of to cement. 4/11/07 pumped pre-flush of 10 bbls FW/10 bbls MC/10 bbls FW. Pu 6 FL-52, 5 #/sx LCM-1, & .4% SMS. Lead-pumped 400 sx(852cf-151bbls) Prend 4% SMS. Tail- pumped 66 sx(91cf-16bbls) Type 3 Cement w/1% CaCl2, .25 #/sug. Plug down @ 12:00 hrs. Circ 48 bbls cement to surface. WOC.	amped Scavenger 19sx(57cf-10bbls) nium Lite Cement w/3% CaCl2, .25 s x Cello-flakes, & .2% FL-52. Dropp	Cement #/sx Cell ed plug &	w/3% CaCl2, .25 #/sx Cello-Flake, o-Flakes, .4% FL-52, .5 #/sx LCM-1 & displaced w/119 bbls FW. Bumped
1/07 RIH w/6 ½" bit. PT casing to 1500# 30/min - good test. D/O shoe track, tag H w/138 jts 4 ½" 11.6# L-80 LT & C casing set @ 5762'. 10' mandrel pum & mabbs FW. Pumped Scavenger 9 sx(27cf-5bbls) Cement w/.3% CD-32, .25 #/sx Celemium Lite Cement w/.3% CD-32, .25 #/sx Cello-flake, 1% FL-52, 6.25 #/sx LCf 77 bbls. ND BOPE. RD RR @ 2100 hrs. e casing TOC & PT will be conducted by the completion rig and results shown or	ndrel landed @ 12:30 hrs. RU to cer lo-flake, 1% FL-52, & 6.25 #/sx LC! M-1. Dropped plug & displaced w/7	nent, 4/1 M-1. Tai	4/07 Pumped pre-flush of 10 bbls MC I- pumped 189 sx(374cf-67bbls)
4. I hereby certify that the foregoing is true and correct.			
gned They W. Wlomes Tracey N. Monroe	Title Regulatory Tec	hniciar	Date 4/16/07 . ACCEPTED FOR RECO
his space for Federal or State Office use) PPROVED BY Title			Date APR 1 7 2007
ONDITION OF APPROVAL, if any: 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any starting of foundations of founda	or agency of		FARMINGTON FIELD OFFI