

DIST. 3

submitted in lieu of Form 3160-5  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2007 MAY -1 PM 4:09

1. Type of Well  
GAS2. Name of Operator  
ConocoPhillips

3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit A (NENE) 330' FSL &amp; 1225' FEL, Sec. 5, T30N, R6W, NMPM

5. Lease Number  
NMPM - 03404  
210 FARMINGTON, NM  
Tribe Name

7. Unit Agreement Name

8. San Juan 31-6 Unit  
Well Name & Number9. SJ 31-6 Unit #49F  
API Well No.

30-039-29903

10. Field and Pool

Blanco Mesa Verde/Basin Dakota

11. County and State  
Rio Arriba Co., NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment

## Type of Action

☐ Abandonment☐ Recompletion☐ Plugging☐ Casing Repair☐ Altering Casing☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection☒ Other - Casing Report

## 13. Describe Proposed or Completed Operations

4/16/07 MIRU Aztec 301. NU BOPE. PT casing 600# 30/min - good test. RIH w/8 1/4" bit. D/O cement, tagged @ 200'. Drilled ahead to 3820' Intermediate. Circ hole. RIH w/92 jts 7" 20# J-55 ST & C casing set @ 3810', Stage Collar @ 2697'. RU to cement. 4/24/07 1<sup>st</sup> Stage - Pumped pre-flush 10 bbls mud clean II w/2 bbls H2O. pumped Scavenger 19 sx(57cf- 10 bbls) Premium Lite Cement w/3% CaCl2, .25 #/sx Cello-Flake, 5 #/sx LCM-1, .4% FL-52, 8% Bentonite and .4% SMS. Lead-Pumped 99 sx(211cf- 37 bbls) Premium Lite Cement w/3% CaCl2, .25 #/sx Cello-Flake, 5 #/sx LMC -1. Tail- Pumped 90 sx(124cf-22 bbls) Type III Cement w/1% CaCl2, .2% FL-52A. Dropped plug & displaced w/60 bbls H2O. Bumped Plug. Open Stage Collar @ 2400#. Circ 20 bbls cement. Circ between Stages. 2<sup>nd</sup> Stage- pumped pre-flush 10 bbls Mud clean II w/2 bbls H2O. Pumped Scavenger 19sx(57cf-10bbls) Premium Lite FM Cement w/3% CaCl2, .25 #/sx Cello-Flake, 5# LCM-1, 8% Bentonite, .4% SMS, .4% FL-52A. Tail- pumped 380 sx(809cf-144 bbls)Premium Lite FM Cement w/3% CaCl2, .25 #/sx Cello-Flake, 5 #/sx LCM-1, 8% Bentonite, .4% SMS, .4% FL-52. Dropped plug & displaced w/109 bbls H2O. Bumped plug & closed Stage Collar @ 2640#. Plug down @ 04:45 hrs 4/25/07. Circ 35 bbls cement to surface. RD cement.

4/25/07 PT casing to 1500 # 30/min - good test. RIH w/6 1/4" bit. D/O cement & ahead to 8026' (TD). TD reached on 4/28/07. Circ hole. RIH w/194 jts 4 1/2" 11.6# L-80 LT & C casing set @ 8025', Float Collar set @ 8023'. RU to cement. 4/29/07 Pumped pre-flush of 10 bbls gel H2O/2 Bbls FW. Pumped Scavenger 9 sx(28cf- 5 bbl)Premium Lite HS FM Cement w/.25 #/sx Cello-Flake, .3% Cd-32, 6.25 #/sx LCM-1, 1% FL-52A. Tail- pumped 301 sx(596cf-106 bbls) Premium Lite HS FM Cement w/.25 #/sx Cello-Flake, .3% CD-32, 6.25 #/sx LCM-1, & 1% FL-52A. Dropped plug & displaced w/124 bbls FW. Bumped plug. Plug down @ 18:04 hrs. ND BOPE & RD. RR @ 00:00 Hrs on 4/30/07. RD. The casing PT & TOC will be conducted by the completion rig and results shown on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 4/30/07

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

Date MAY 02 2007

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON FIELD OFFICE

NMOCN