

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2007 MAY -4 PM 3:34

1. Type of Well
GAS

2. Name of Operator
ConocoPhillips

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
Unit B (NWNE), 1220' FNL & 2615' FWL, Sec. 19, T29N, R6W, NMPM

5. Lease Number
SF-078426
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
San Juan 29-6 Unit
8. Well Name & Number
SJ 29-6 Unit #65C
9. API Well No.
30-039-29808
10. Field and Pool
Blanco Mesa Verde
11. County and State
Rio Arriba Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

4/12/07 MIRU HP 282.NU BOP. PT casing to 6003' 30/min - good test. RIH w/8 3/4" bit. D/O cement & ahead to 3425' intermediate. RIH w/65 jts 7" 23# J-55 LT & C casing set @ 3418', DV tool @ 3414. Dropped bomb to open tool. RU to cement. 4/17/07 Pumped pre-flush of 10 bbls H2O/10 bbls Calseal/10 bbls H2O spacer/20 bbls superflush/10 bbls H2O spacer. Lead-pumped 410 sx(582cf-103bbls) 50/50 V POZ Cement w/2% Gel, .2% Verset, .1% Halad 766. Tail- pumped 180 sx(232cf-41bbls) 50/50 V POZ Cement w/2% Gel, .2% Verset, .1% Halad. Dropped plug & displaced w/134 bbls H2O. Bumped plug to 2800# to close DV tool. Circ 50 bbls foam cement to surface.

4/17/07 PT casing to 1500# 30/min - good test. RIH w/6 1/4" bit. D/O cement and ahead to 5545' (TD) TD reached on 4/20/07. Circ hole. RIH w/133 jts 10.5# J-55 ST & C casing set @ 5541'. RU to cement. 4/21/07 Pumped pre-flush of 10 bbls Gel H2O/2 bbls H2O. Pumped 166 sx(329cf-58bbls) Premium Lite HS FM Cement w/.25 #/sx Cello-flake, .3% CD-32, 6.25 #/sx LCM-1, 1% FL-52. Dropped plug & displaced w/78 bbls H2O. Bump plug to 1500#. RD equipment. ND BOP. RR @ 16:30 on 4/21/07.

PT and TOC will be shown on next report. PT will be conducted by completion rig.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 5/3/07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

MAY 09 2007

FARMINGTON FIELD OFFICE

NMOCD