

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-039-27478
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator ConocoPhillips Company 217817		6. State Oil & Gas Lease No. E-347-39
3. Address of Operator 5525 Highway 64, NBU 3004, Farmington, NM 87401		7. Lease Name or Unit Agreement Name: San Juan 31-6 Unit 31328
4. Well Location Unit Letter <u>D</u> : <u>1010</u> feet from the <u>North</u> line and <u>1300</u> feet from the <u>West</u> line Section <u>2</u> Township <u>30N</u> Range <u>6W</u> NMPM County <u>Rio Arriba</u>		8. Well No. SJ 31-6 Unit #211A
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6445' GL		9. Pool name or Wildcat Basin Fruitland Coal 71629

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒

OTHER: ☐ 7" casing report ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/31/03 RIH w/8-3/4" bit & tagged cement @ 182'. Drilled cement and then formation to 2925'. Circ. hole. RIH w/7", 20#, J-55 casing and set @ 2920'. RU Schlumberger to cement. Pumped a preflush of 30 bbls FW w/dye in last 10 bbls. Pumped Lead - 420 sx (1096.2 cf - 195.2 bbl slurry) Class G cement w/3% extender, 0.25#/sx Cellophane & 0.2% Antifoam. Tail - 100 sx (127 cf - 22.5 bbl slurry) 50/50 Class G POZ w/2% Gel, 5#/sx Gilsonite, 2% CaCl₂, 0.25#/sx Cellophane & 0.25% Antifoam. Released wiper plug and displaced plug w/20 bbls FW & 96 bbl drill water. Bumped plug w/1290 psi @ 0600 hrs 9/2/03. Circ. 40 bbls good cement to surface. RD Schlumberger. ND BOP, set slips and cut off casing. Installed trash cap. RD & released rig 9/2/03 @ 1300 hrs. Will show casing PT on next report.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Patsy Clugston TITLE SHEAR Administrative Assistant DATE 9/3/03

Type or print name Patsy Clugston Telephone No. 505-599-3454

(This space for State use)

APPROVED BY Charles R. DEPUTY OIL & GAS INSPECTOR, DIST. SEP - 8 2003

Conditions of approval, if any: