Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED	
OM B No 1004-0137	
OM B No. 1004-0117	2

OM B No. 1004-0137 Expires: March 1, 2017	4
Loon Coriol Ma	_

SUNDRY NOTICES AND REPORTS ON 1	WELLS

_			an an Taiba l	James
U	SF-07850	8	10	
, I	Case Serial	INU.	_	

SUBMIT IN TR	IPLICATE- Other ins	tructions on reve	rse side.	7. If Unit o	CA/Agreement, Name and/or No.
I. Type of Well Oil Well	Gas Well Other		- 210 r	NA 8. Well Na	<u> </u>
2. Name of Operator Koch Explor	ration Company, LLC			9. API We	aus 716S ell No.
3a Address PO Box 489, Aztec, NM 87410		3b. Phone No. (include 505-334-9111	e area code)	30-045 10. Field an	-32655 d Pool, or Exploratory Area
4. Location of Well (Footage, Sec., 445' FSL & 2350' FEL, S13, 7 Lat 36.53.5162, Long 107.43.8	131N, R9W "O"		DE OF NOTICE	11. County San Ju	or Parish, State an, New Mexico
TYPE OF SUBMISSION	TROPAGE BOX(ES) T		PE OF ACTION	ACTORT, OF	COTILE DATA
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (S Reclamation Recomplete Temporarily A Water Disposa	bandon	Water Shut-Off Well Integrity Other Spud Well and Surface Casing and Cement


Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

05/08/07 Spud Well.

5/8-5/9/07 Drilled 12 1/4" hole to 185', ran 9 5/8", 36# J-55 STC Casing, landed @ 175' KB (KB=13.0) 5/09/07 Cemented with 171 sks, 15.2#, Type III Cement plus 3% CaCL, plus 0.25 lb/sk Celloflake, yield 1.28 (15.2 ppg) 218.88 cu. ft. We used 3 centralizers on the bottom 3 joints. Circulated 20 bbls cement to surface. Wait on cement 8 hours.

Tested BOPs 250# low for 5 minutes, and 2000# high for 10 minutes. Tested 9 5/8" casing to 600# for 30 minutes, held O.K.

Tagged cement @ 125' in 9 5/8" casing.



e District Superi	ntendent	
e	05/11/2007	
R STATE OF	FICE USE	
Title	Date	
Office		
	e R STATE OF	e District Superintendent e 05/11/2007 R STATE OFFICE USE Title Date

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

