UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

5.	Lease Serial No.						
	SF 079010.		L EIS	i I		20	
5.	If Indian, Alfottee or	T	ibe Name	П	٠	70	•

abandoned We		RECEIVED						
SUBMIT IN TR	7. If Unit or CA/Agreement, Name and/or No. Northeast Blanco Unit 10 10 11 11 11 11 11 11 11 11 11 11 11							
1. Type of Well Oil Well								
2. Name of Operator Devon Energ								
3a Address 3b. Phone No. (include area code) 20 N. Broadway, Oklahoma City, OK 73102 405-552-7917					30-045-34138 10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec.,	Basin Fruitland Coal							
SL - 1,840' FNL & 775' FWL, BHL - 1,025' FNL & 1,900' FV	11. County or Parish, State San Juan, NM							
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA								
TYPE OF SUBMISSION								
Notice of Intent ✓ Subsequent Report ☐ Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Sta Reclamation Recomplete Temporarily Ab	ŕ	Water Shut-Off Well Integrity Other Casing and Cement			
					ork and approximate duration thereof. hs of all pertinent markers and zones.			

Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Drilled 8 3/4" hole to 3,450' on 5/4/07, set 77 jts of 7", J-55 LT&C, 23# casing at 3,440'. Cemented lead w/550 sx (144 bbls) 50/50 POZ cement w/3% Gel, 5# Gilsonite, 1/4# Flocele, 0.1% CFR 3, 0.4% Halad 344 and tail w/75 sx (16 bbls) STD "B" cement w/0.4% Halad 344. Circulated 20 bbls of cement to surface. Tested casing to 1,500 psi.

> RCVD MAY16'07 OIL CONS. DIV. DIST. 3

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)		
	itle Senior Staff Operations Techni	cian
Signature C	Date 5-7-07	
THIS SPACE FOR FEDERAL C	OR STATE OFFICE USE	AVEYHERMANA
Approved by	Title	Date MAY 1 4 2007
Conditions of approval, if any, are attached. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		FARMINGTON FIZED OFFICE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)