

## NEW MICAICO ENEKGI, MINEKALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 (505) 334-8178 FAX: (505) 334-817

nnrd.state.nm.us/ocd/District lil/3dh

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page Revised 11/16/5

	bp America	Production	n Company		ER-LEAKAGE TES			
•					( W_API # 30-0145-			
	NAME OF RES		OF PROD. lor Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)			
Upper Completion	BLANCO	$\sim m_{\chi}$	G/	4S	FLOW	TBG		
Lower Completion	BASIN	`G#	IS	FLOW	TBG			
		PRE	-FLOW SHUT-	IN DRESSI	PE DATA			
Upper	Hour, date shut-in			shut-in	Si press. Psig	Stabilized? (Yes or No)		
Completion	08/25	08/25/03			Logo	YES		
Lower	Hour, date shut-in	Length of time		SI press. Psig	Stabilized? (Yes or No)			
Completion	08/26	/03	72 HO		1 420	YES		
	Chaus datalt	······································	FLOW II	EST NO. 1				
Commenced at					g (Upper or Lower):			
TiME (hour,date)	LAPSED TIME SINCE*	<del></del>	SSURE DK	PROD. ZOI TEMP.	NE REMARKS			
		Upper Completion	Lower Completion		<u>_</u>			
8/26	DAY 1	69	175		BOTH ZONES S	SHUT IN		
8 127	DAY 2	93	315	<u> </u>	BOTH ZONES S	SHUT IN		
8/28	DAY 3	103	420	<u> </u>	BOTH ZONES S	SHUT IN		
8:129	DAY 4	108	206		FLOW Lower	ZONE		
8 130	DAY 5	119	129		FLOW "	ZONE		
8/31	DAY 6	120	123		FLOW "	ZONE		
roduction ra	te during test	DID N	ot class o	NER - C	ONTINUED TEST			
il:BOPD based on_			on	Bbls. in	avGOR			
as:		MCFF	PD; Tested thru	(Orifice or M	leter):			
•		MID-	TEST SHUT-IN	PRESSUR	E DATA			
Upper Completion	Hour, date shut-in		Length of time s		SI press psig	Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in		Length of time s	hut-ìn	SI press. psig	Stabilized? (Yes or No.)		

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lowr):		
TIME (hour,date)	LAPSED TIME Since**	YY\ V PRESS Upper Completion	URE DIC Lower Completion	PROD. ZONE	REMARKS	
V1		,123	183	\$	BOTH ZONES SI	
9/2		127	315		fr st ts	
9/3		129	385		67 14 21	
9/4		101	444	,	FLOW UPPER ZONG	
9/5		69	494		11 11 11	
9/6		<u> 103</u>	534		ty ty a	

Produ	uction	rate	durina	test

Oil: Gas:	_BOPD based onMCFP	Bbls. ii D:Tested thru (Orf	nHours ice or Meter):	Grav	GOR	
Remarks:			<u> </u>	····		_
	e information herein con	tained is true and o	complete to the bes	of my knowledge.	,	
ApprovedSEP	- 9 2003	_ Operator	bp America	Production	Company	New
Mexico Oil Conservation	Division	Ву	Sheri Bradsh	aw 33		,
By Charle To		Title	Field Tech		— <del>——</del>	
DEPUTY OIL & GAS IN	Sheciar nouse	Date	9/8/03			

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the weilhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which wa previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereo and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested a wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the entire of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gain dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 day: after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)