

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED

OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NM-03567

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

Gage 3G

9. API WELL NO.

30-045-34106

10. FIELD AND POOL, OR WILDCAT

Basin Dakota/Blanco Mesa Verde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 20 T30N R10W, NMPM
RCUD MAY 25 '07
OIL CONS. DIV.

DIST. 3

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

2/13/07

16. DATE T.D. REACHED

2/26/07

17. DATE COMPL. (Ready to prod.)

5/11/07

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)

GL 6408'

KB 6423'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

7556'

21. PLUG, BACK T.D., MD & TVD

7552'

22. IF MULTIPLE COMPL., HOW MANY*

2

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Basin Dakota 7316' - 7504'

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Cement bond Log w/Gamma Ray Casing Collars

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8" H-40	32.3#	237'	12 1/4"	surface; 172ax (232 cf)	15 bbls
7" J-55	20# & 23#	4942'	8 3/4"	surface; 785ax (1637 cf)	58 bbls
4 1/2" J-55	11.6#	7555'	6 1/4"	TOC 4770'; 194ax (383 cf)	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	7412'	

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

@2SPF
7400' - 7504' = 40 holes
@1SPF
7316' - 7380' = 15 holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

7316' - 7504' Pumped 630 gal 15% HCL Acid, Frac w/Slickwater w/35062# 20/40 TLC Sand.

33. PRODUCTION

7316' - 7380' = 15 holes

</

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This is a MV/DK well being DHC per order #2509 AZ.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED *Shirley N. Monahan*

TITLE Regulatory Technician

DATE 5/22/07

(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

MAY 23 2007

FARMINGTON FIELD OFFICE

NMOCD

Ojo Alamo	1578'	1738'	White, cr-gr ss.	Ojo Alamo	2522'
Kirtland	1738'	2617'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2654'
Fruitland	2617'	2936'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	2937'
Pictured Cliffs	2936'	3075'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3150'
Lewis	3075'	3734'	Shale w/siltstone stringers	Lewis	3309'
Huerfanito Bentonite	3734'	3924'	White, waxy chalky bentonite	Huerfanito Bent.	3604'
Chacra	3924'	4543'	Gry fn grn silty, glauconitic sd stone w/drck gry shale	Chacra	4070'
Mesa Verde	4543'	4733'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	4704'
Menefee	4733'	5245'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	4928'
Point Lookout	5245'	5578'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5350'
Mancos	5578'	6488'	Dark gry carb sh.	Mancos	5742'
Gallup	6488'	7212'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh	Gallup	6467'
La Ventana	XXXX	XXXX	Wt to lt buff to med grn sl carb bent	Greenhorn	7252'
Greenhorn	7212'	7263'	Highly calc gry sh w/thin lmst.	Graneros	7313'
Graneros	7263'	7314'	Dk gry shale, fossil & carb w/pyrite incl.	Dakota	7346'
Dakota	7314'		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks		