RECEIVED

FORM APPROVED OMB No. 1004-0136 Expires November 30, 2000

UNITED STATES	<u> </u>	Expires November 30, 2000			
DEPARTMENT OF THE INTERIO BUREAU OF LAND MANGEMEN	5. Leas	5. Lease Serial No. SF - 0781326. If Indian, Allottee or tribe Name			
APPLICATION OFOR PERMIT TO DRILL O	6. If In				
	070 Farmington, NM			 	
1a. Type of Work: X DRILL REENTI	ER	7. If U	nit or CA Agreement,	, Name and No	
1b. Type of Well: Oil Well Sas Well Gas Other	Single Zone Multiple Zon	8. Leas	se Name and Well No Elliott Gas (
2. Name of Operator		9. API	Well No.		
•	n: Mary Corley		3004.	531841	
3a. Address 3b. Phone No. (include area code)			10. Field and Pool, or Exploratory		
P.O. Box 3092 Houston, Texas 77253 281-366-4491			Blanco Mesaverde		
4. Loction of Well (Report location clearly and in accordance with an	ny State requirements.*)) (4.6178)	11. Sec.	., T., R., M., or Blk, as	nd survey or Area	
At surface 2185' FNL & 880' FEL	AUD 200	L	∫ Sec. 14, T29N	, R09W	
At proposed prod. Zone 1200' FNL & 660' FEL	4/03	10/10	<i>!</i> 		
 Distance in miles and direction from nearest town or post office* 20 miles from Bloomfield, N 	IM	Day	anty or Parish San Juan	13. State New Mexico	
15. Distance from proposed*	16. No. of Acres in lease	17. Spacing U	Init dedicated to this w	vell	
Location to nearest Property or lease line, ft.		a 📝 💎 💮		A . /	
(Also to nearest drig. Ujnit line, if any) 660' BHL	320		320 /	N2	
18. Distance from proposed location*			BLM/BIA Bond No. on file		
to nearest well, drilling, completed, applied for, on this lease, ft. 1000'	1000 FQEA'		WY2924		
. Elevations (show whether DF, KDB., RT, GL, etc. 22. Approximate date work will sta		11 start* 23	rt* 23. Estimated duration		
6408' GL September 15, 2003			7 Days		
	24. Attachments				
The following, completed in accordance with the requirements of Onshore	e Oil and Gas Order No. 1, shall be a	tached to this for	m:		
 Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National forest System SUPO shall be filed with the appropriate Forest Service Office). 	4. Bond to cover 20 above). 5. Operator certif. 6. Such other sit	the operations un ecation.	nless covered by an ex	as may be required by the	
	suthorized officerinted/typed)	er. Date			
25. Signatury (Asylon Name (Printed/typed) Mary Corley			08/1	1/2003	
Title	Senior Regulatory Analyst				
Approve David J. Mankiewicz Name (Printed)		Date	AUG 2 6 2	003	
	* · · · · · · · · · · · · · · · · · · ·				

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct Operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on reverse)

Title

DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHED "GENERAL REQUIREMENTS".

Office

Fris action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4

District I PO Box 1980, Hobbs NM 88241-1980 District II PO Drawer KK, Artesia, NM 87211-0719 District III

State of New Mexico Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION PO Box 2088 Santa Fe, NM 87504-2088

Form C-102 Revised February 21, 1994 Instructions on back Submit to Appropriate District Office State Lease - 4 Copies

Fee Lease - 3 Copies

AMENDED REPORT

1000 Rio Brazos Rd., Aztec, NM 87410 District IV PO Box 2088, Santa Fe, NM 87504-2088 WELL LOCATION AND ACREAGE DEDICATION PLAT API Numbe 72319 Well Number ELLIOTT GASCOM 13 000 441 BP AMERICA PRODUCTION COMPANY 6408 **Surface Location** Range North/South line East/West line County Township Feet from the Lot Idn UL or Lot No. SAN JUAN 29 N 9 W 2185 NORTH 880 EAST 14 H ¹¹ Bottom Hole Location If Different From Surface UL or lot no. Section Township Lot Idn Feet from the Past/West line County SAN JUAN 29 N EAST 1200 NORTH 660 A 14 9 W Consolidation Code Joint or Infill Dedicated Acres 320 NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION 223(8) "OPERATOR CERTIFICATION hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. Bottom Hole Location 1200 F/NL 660 F/EL 2185 Azimuth -9°43' 1551

880' Dat "SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. June 6, 2003 Lot 3 Lot 2 Lot 1 Date of Survey Signature and S Lot 6 Lot 7 Lot 8 5127(R)

BP AMERICA PRODUCTION COMPANY DRILLING AND COMPLETION PROGRAM

Prospect Name: Elliott GC A

HGJ/MNP/JMP

Form 46 12-00 MNP

Lease: Elliott GC A

County: San Juan

Well No: 1 B

Surface Location: 14-29N-9W, 2185 FNL, 880 FEL

BHL: 14-29N-9W, 1200 FNL, 660 FEL

							FEL	
±	w Mexico		Field:	Blanco M	lesaverde	!		
	gust 7, 2003							
OBJECTIVE: Drill 400' be		ookout Sandstone, se						
MET	HOD OF DRILLING		APPROXIMA					
TYPE OF TOOLS	OOLS DEPTH OF DRILLING			Estimated GL: 6294' Estimated KB: 6308'				
Rotary	0 - TD	MARKER		T	VD	MD		
LOG PROGRAM			Ojo Alamo		19	974	2070	
TYPE DEPTH INVERAL			Kirtland		20	057	2161	
OPEN HOLE			Fruitland	1	25	553	2706	
None			Fruitland Coal	*	28	317	2986	
			Pictured Cliffs	*		010	3186	
			Lewis	*	1	217	3397	
CASED HOLE			Cliff House	#		527	4708	
GR-CCL-TDT	TDT – TD to	Menefee	#		789	4970		
CBL	Identify 4 1/2"	cement top	Point Lookout	#		273	5454	
DEMARKS.			Mancos	İ	54	458	5639	
REMARKS:	(magnituda P dunatian)			l l				
- Please report any flares	(magnitude & duration)) .						
				- 1				
			TOTAL DEPTH		56	673	5854	
			# Probable cor			* Possible		
	PECIAL TESTS		DRILL CUT				LING TIME	
TYPE	PECIAL TESTS		FREQUENC			REQUEN		
			None	Producti		Geolograph		
None			Notic	Froducti	off flore	3eologi apri	U-1D	
REMARKS:								
	····					 		
MUD PROGRAM:								
			•					
Approx. Interval	Type Mud	Weight, #/gai	Vis, sec/qt	W/L cc's	s/30 min	Other :	Specification	
Approx. Interval		#/gal	Vis, sec/qt	W/L cc's	s/30 min	Other	Specification	
Approx. Interval 0 - 120	Spud	#/gal 8.6-9.2	Vis, sec/qt		s/30 min	Other	Specification	
Approx. Interval 0 - 120 120 - 2934	Spud (1) Water/LSN	#/gal 8.6-9.2 ND 8.6-9.2		<u> </u> <6		<u> </u>		
Approx. Interval 0 - 120 120 - 2934 2934 - 5854	Spud	#/gal 8.6-9.2 ND 8.6-9.2	Vis, sec/qt	<u> </u> <6		<u> </u>		
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS:	Spud (1) Water/LSN Gas/Air/N2	#/gai 8.6-9.2 ND 8.6-9.2 2/Mist Volume	I sufficient to main	<6 tain a stabl	e and clea	an wellbor	e	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854	Spud (1) Water/LSN Gas/Air/N2	#/gai 8.6-9.2 ND 8.6-9.2 2/Mist Volume	I sufficient to main	<6 tain a stabl	e and clea	an wellbor	e	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require	(1) Spud Water/LSN Gas/Air/N2 sweeps to keep unlo	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume	sufficient to main	<6 tain a stabl t hole cond	e and clea	an wellbore ate freque	e ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (1)	(1) Spud Water/LSN Gas/Air/N2 sweeps to keep unlo	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume paded while fresh	sufficient to main water drilling. Le	<6 tain a stabl t hole cond	e and clea	an wellbore ate freque	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String)	(1) Spud Water/LSN Gas/Air/N2 sweeps to keep unlo	#/gai 8.6-9.2 ND 8.6-9.2 2/Mist Volume standed while fresh llocation letter specific Casing Size	sufficient to main water drilling. Le es casing sizes to be	<6 tain a stabl t hole cond used. Hole s Weight	e and clea litions dict sizes will be Hole Size	an wellbore ate freque governed by e Landi	e ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor	(1) Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : aded while fresh llocation letter specific Casing Size 9 5/8"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C	<6 tain a stabl t hole cond used. Hole s Weight 32#	e and clea litions dict sizes will be Hole Size 12.2	an wellborn ate freque governed by a Landi 5" 1	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production	(1) Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : aded while fresh llocation letter specific Casing Size 9 5/8"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C	<6 tain a stabl t hole cond used. Hole s Weight 32#	e and clea litions dict sizes will be Hole Size 12.2	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS:	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al (4) 100' Overlap	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al (4) 100' Overlap CORING PROGRAM: None	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface Fruitland Coal bove 7" shoe	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al (4) 100' Overlap CORING PROGRAM:	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface Fruitland Coal bove 7" shoe	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume : added while fresh llocation letter specific Casing Size 9 5/8" 7"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al (4) 100' Overlap CORING PROGRAM: None COMPLETION PROGRAM	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface Fruitland Coal bove 7" shoe	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume: Paded while fresh Casing Size 9 5/8" 7" 4 1/2"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al (4) 100' Overlap CORING PROGRAM: None COMPLETION PROGR Rigless, 2-3 Stage Limit	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface Fruitland Coal bove 7" shoe	#/gal 8.6-9.2 ND 8.6-9.2 2/Mist Volume: Paded while fresh Casing Size 9 5/8" 7" 4 1/2"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C	<6 tain a stable t hole condused. Hole s Weight 32# 20#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al (4) 100' Overlap CORING PROGRAM: None COMPLETION PROGR Rigless, 2-3 Stage Limit GENERAL REMARKS:	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface Fruitland Coal bove 7" shoe	#/gal 8.6-9.2 ND 8.6-9.2 Z/Mist Volume Paded while fresh Resing Size 9 5/8" 7" 4 1/2"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C J-55	<6 tain a stabl t hole cond used. Hole s Weight 32# 20# 10.5#	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al (4) 100' Overlap CORING PROGRAM: None COMPLETION PROGR Rigless, 2-3 Stage Limit GENERAL REMARKS: Notify BLM/NMOCD 24	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface Fruitland Coal bove 7" shoe	#/gal 8.6-9.2 ND 8.6-9.2 Z/Mist Volume standed while fresh llocation letter specific Casing Size 9 5/8" 7" 4 1/2"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C J-55 Casing and Cem	<6 tain a stable t hole cond used. Hole s Weight 32# 20# 10.5# enting.	litions dict sizes will be Hole Size 12.2 8.7 6.2	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	
Approx. Interval 0 - 120 120 - 2934 2934 - 5854 REMARKS: (1) The hole will require CASING PROGRAM: (Casing String Surface/Conductor Intermediate Production REMARKS: (1) Circulate Cement to (2) Set casing 50' above (3) Bring cement 100' al (4) 100' Overlap CORING PROGRAM: None COMPLETION PROGR Rigless, 2-3 Stage Limit GENERAL REMARKS:	Spud Water/LSN Gas/Air/N2 sweeps to keep unlo Normally, tubular goods a Estimated Depth 120 2934 5854 Surface Fruitland Coal bove 7" shoe	#/gal 8.6-9.2 ND 8.6-9.2 Z/Mist Volume standed while fresh llocation letter specific Casing Size 9 5/8" 7" 4 1/2"	sufficient to main water drilling. Le es casing sizes to be Grade H-40 ST&C J/K-55 ST&C J-55	<6 tain a stable t hole cond used. Hole s Weight 32# 20# 10.5# enting.	e and clea litions dict sizes will be Hole Size 12.2 8.7	an wellbore ate freque governed by Landi 5" 1 5" 1,2	ency.	

August 7, 2003

Version 1.0

BP America Production Company BOP Pressure Testing Requirements

Well Name: Elliott GC A

County: San Juan

1 B

State: **New Mexico**

Formation	Estimated TVD/MD	Anticipated Bottom Hole Pressure	Maximum Anticipated Surface Pressure ** -
Ojo Alamo	1974		
Fruitland Coal	2553		
PC	3010		
Lewis Shale	3217		
Cliff House	4527	500	0
Menefee Shale	4789		
Point Lookout	5273	600	0
Mancos	5458		
Dakota	-	2600	1374

** Note: Determined using the following formula: ABHP - (.22*TVD) = ASP

Requested BOP Pressure Test Exception: 750 psi

SAN JUAN BASIN Dakota Formation Pressure Control Equipment

Background

The objective Dakota formation maximum surface pressure is anticipated to be less than 1000 psi, based on shut-in surface pressures from adjacent wells. Pressure control equipment working pressure minimum requirements are therefore 2000 psi. Equipment to be used will conform to API RP-53 (Figure 2.C.2) for a 2000 psi system per Federal Onshore Order No. 2. Due to available conventional equipment within the area, 3000 psi rated pressure control equipment will typically be utilized in a double ram type arrangement. Regional drilling rights to be utilized have substructure height limitations which exclude the use of annular preventers; therefore a rotating head will be installed above these rams. This pressure control equipment will be utilized for conventional drilling below conductor to total depth in the Basin Dakota. No abnormal temperature, pressure, or H2S anticipated.

Equipment Specification

Interval

BOP Equipment

Below conductor casing to total depth

11" nominal or 7 1/16",3000 psi double ram preventer with rotating head.

All ram type preventers and related control equipment will be hydraulically tested to 250 psi (low pressure) and 2000 psi (high pressure), upon installation, following any repairs or equipment replacements, or at 30 day intervals. Accessories to BOP equipment will include kelly cock, upper kelly cock with a handle available, floor safety valves and choke manifold which will also be tested to equivalent pressure.

BP American Production Company



Well Control Equipment Schematic

