

187E-30-039-25361

*55-30-039-06741

5057

RECEIVED
JUL 5 1995

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

OIL CON. DIV.
DIST. 3

Operator Unocal Oil and Gas Operation Location: Unit P Sec. 35 Twp 27N Rng 7W

Name of Well/Wells or Pipeline Serviced Rincon Unit 55 Rincon Unit 187E

Elevation 594' Completion Date 02/03/95 Total Depth 320' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. NONE NOTED

Depths gas encountered: NONE

Type & amount of coke breeze used: 3050 lbs. Carbo 40

Depths anodes placed: 91', 97', 102', 107', 115', 151', 160', 165', 181', 186'

Depths vent pipes placed: 0' to 320'

Vent pipe perforations: 80' thru 320'

Remarks: Lease SF 080385

First Ground Bed installed on this location

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

Cathodic Protection Services

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 251-00311	P/L NAME(s), NUMBER(s) Rincon 55					S 2 T 36 N R 7 W	
WO #	TOTAL 10 - Anode	VOLTS 12.36	AMPS 7.3	= OHMS 1.69	DATE 2-3-95	NAME Don L.	

REMARKS (notes for construction log)

3,050 lb of Coke Breeze

Depth
80 - 1.1 85 1.1 90 1.1 95 1.1

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	
100	1.1		295			490			685			
105	1.5		300			495			690			
110	.7		305			500			695			
115	.7		310			505			700			
120	.6		315			510			ANODE	DEPTH	NO	FULLY
125	.4		320			515			#		COKE	COKE'D
130	.4		325			520			1	186	.7	1.5
135	.3		330			525			2	181	.9	1.5
140	.2		335			530			3	165	.7	1.6
145	.3		340			535			4	160	.9	1.6
150	.5		345			540			5	151	.6	1.1
155	.2		350			545			6	115	.7	1.4
160	.6		355			550			7	107	1.0	3.3
165	.9		360			555			8	102	1.5	3.4
170	.2		365			560			9	97	1.2	3.5
175	.2		370			565			10	91	1.1	3.2
180	.3		375			570			11			
185	.9		380			575			12			
190	.2		385			580			13			
195	.3		390			585			14			
200	.2		395			590			15			
205	.3		400			595			16			
210	.2		405			600			17			
215	.2		410			605			18			
220	.2		415			610			19			
225	.2		420			615			20			
230	.1		425			620			21			
235	.2		430			625			22			
240	.2		435			630			23			
245	.3		440			635			24			
250	.1		445			640			25			
255	.2		450			645			26			
260	T-40		455			650			27			
265			460			655			28			
270			465			660			29			
275			470			665			30			
280			475			670						
285			480			675						
290			485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

**P.O. BOX 1359 - PHONE 334-6141
AZTEC, NEW MEXICO 87410**

[illegible]

REMARKS: _____

Wm. F. Burgess

Deletion

Food Overview