

601
30-045-2689
E
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit P Sec. 25 Twp 24 Rng 11

Name of Well/Wells or Pipeline Serviced P.L. Davis #2 E

2222W

Elevation 6438 Completion Date 11-8-91 Total Depth 388 Land Type F

Casing Strings, Sizes, Types & Depths Set 100' of 8" P.O.C.

If Casing Strings are cemented, show amounts & types used Used 23
sacks of neat cement.

If Cement or Bentonite Plugs have been placed, show depths & amounts used
No plugs

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. H₂O is at 150' and is clear

Depths gas encountered: No gas

Ground bed depth with type & amount of coke breeze used: 388' with
55 sacks of Asbury 4518

Depths anodes placed: #1 is at 375' #10 is at 160'

Depths vent pipes placed: 388' to surface.

Vent pipe perforations: vent pipe is perforated up to 150

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State;
If Federal or Indian, add Lease Number.

RECEIVED

FEB 24 1992

OIL CON. DIV.

DIST. 3

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2222-W	P/L NAME(s), NUMBER(s) <i>P.L. Davis #2E</i>					
JO # 3221A	TOTAL	VOLTS 12.54	AMPS 29.6	- OHMS .42	DATE 11-8-91	NAME R. Smith

REMARKS (notes for construction log)

H₂O is at 150, vent
is perked up to 150'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100			295	.9		490			685			
105			300	.5		495			690			
110			305	.5		500			695			
115			310	.7		505			700			
120			315	.6		510			ANODE	DEPTH	NO	FULL
125			320	.8		515			*		COKE	COKE
130			325	1.4	①	520			1	375	2.5	8.1
135			330	2.2		525			2	365	2.4	7.5
140	1.5		335	2.3	⑤	530			3	355	2.3	6.6
145	1.7		340	2.2		535			4	345	2.2	6.5
150	2.1		345	2.1	④	540			5	335	2.3	6.3
155	1.9		350	2.5		545			6	325	2.0	6.4
160	2.2	⑫	355	2.5	③	550			7	230	2.0	7.5
165	2.1		360	2.5		555			8	220	2.0	7.6
170	2.2	⑩	365	2.4	②	560			9	210	2.5	8.4
175	1.8		370	2.4		565			10	200	2.1	7.5
180	1.6		375	2.3	①	570			11	170	2.2	8.6
185	1.2		380	2.7		575			12	160	2.2	8.7
190	.8		385	2.4		580			13			
195	1.6		390	70388		585			14			
200	1.9	⑪	395			590			15			
205	2.3		400			595			16			
210	2.4	⑨	405			600			17			
215	2.0		410			605			18			
220	1.8	⑧	415			610			19			
225	2.2		420			615			20			
230	1.9	⑦	425			620			21			
235	1.5		430			625			22			
240	1.1		435			630			23			
245	1.2		440			635			24			
250	1.0		445			640			25			
255	.8		450			645			26			
260	.8		455			650			27			
265	.6		460			655			28			
270	.6		465			660			29			
275	.5		470			665			30			
280	.9		475			670						
285	.9		480			675						
290	1.0		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist