

501- 30-045-27633

1- 30-045-07005

E

2229

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Location: Unit L Sec. 36 Twp 28 Rng 10

Name of Well/Wells or Pipeline Serviced Order #501 #1

Elevation 5903 Completion Date 12-4-91 Total Depth 361 Land Type F

Casing Strings, Sizes, Types & Depths 8" PVC SURFACE CASING
9.5' DEEP

If Casing Strings are cemented, show amounts & types used Yes with
23 BAGS CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Fresh 120'

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 361' DEEP with
150lbs Loreco Types SW + 4500lbs of Asbury 4518 Flo-Coke

Depths anodes placed: 343, 335, 325, 315, 305, 295, 215, 205, 195, 185, 175,

Depths vent pipes placed: 361'

Vent pipe perforations: bottom 250'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.]

Dist. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2229-W	P/L NAME(S), NUMBER(S) Omler #501 #1					
WO # K265	TOTAL	VOLTS 11.87	AMPS 31.8	= OHMS 37	DATE 12-4-91	NAME MRW

REMARKS (notes for construction log)

95' of 8" PVC CASING; 23 CEMENT

L36-28-10 H₂O AT 120 Drilled 380, LOGGED 361

Perforated bottom 250 3 bags Loresco 90 Asbury (4650

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE	*		ANODE	*		ANODE	*		ANODE	*
100			295	2.0		490			685		
105			300	1.9		495			690		
110			305	1.9		500			695		
115			310	1.9		505			700		
120	1.8		315	1.8		510			ANODE	DEPTH	NO
125	1.9		320	2.0		515			*		FUL
130	1.9		325	1.9		520					COKE
135	1.9		330	1.7		525			1	343	2.0
140	2.0		335	1.8		530			2	335	1.8
145	1.8		340	1.7		535			3	325	1.9
150	1.8		345	1.9		540			4	315	2.0
155	2.0		350	1.9		545			5	305	1.9
160	1.5		355	1.9		550			6	295	1.9
165	1.8		360	TD	361	555			7	215	1.8
170	1.8		365			560			8	205	1.7
175	1.9		370			565			9	195	1.7
180	2.0		375			570			10	185	1.9
185	2.0		380			575			11	175	1.9
190	1.9		385			580			12	155	2.0
195	1.8		390			585			13		
200	1.8		395			590			14		
205	1.8		400			595			15		
210	1.8		405			600			16		
215	1.9		410			605			17		
220	1.5		415			610			18		
225	1.4		420			615			19		
230	1.8		425			620			20		
235	1.6		430			625			21		
240	1.4		435			630			22		
245	.7		440			635			23		
250	.9		445			640			24		
255	1.1		450			645			25		
260	1.5		455			650			26		
265	1.4		460			655			27		
270	1.8		465			660			28		
275	1.6		470			665			29		
280	1.4		475			670			30		
285	.9		480			675					
290	1.4		485			680					

DISTRIBUTION: - original - permanent CPS FILE

copy - Division Corrosion Supervisor
copy - Region Corrosion Specialist