

30-045-28946 HUERTFANITO UNIT #98-M

30-045-06097 HUERTFANITO UNIT #30

3682

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit 0 Sec. 35 Twp 27 Rng 09

Name of Well/Wells or Pipeline Serviced _____

HUERTFANITO UNIT #98M AND HUERTFANITO UNIT #30-35

Elevation _____ Completion Date 9/21/93 Total Depth 355' Land Type F

Casing Strings, Sizes, Types & Depths 9/16 Set 59' of 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 16 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT A SEEP AT 105', AND A FRESH WATER

VEIN AT 160'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 355' DEPTH.

USED 93 SACKS OF ASBURY 218R (H650*)

Depths anodes placed: 322', 310', 300', 283', 275', 265', 255', 220', 213', 203', 195', 185', 175', 165', + 155'

Depths vent pipes placed: SURFACE TO 355'.

Vent pipe perforations: BOTTOM 250'.

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV./

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.