submitted in lieu of Form 3160-5 UNITED STATES		AMENDED TOC 1ST STA	
DEPARTMENT OF THE INTERIOR	pc	UD JUN19'07	
BUREAU OF LAND MANAGEMENT	٠	IL CONS. DIV.	
Sundry Notices and Reports on Wells	75	nici a	
1. Type of Well GAS	P. P. S.	Lease Number NMSF-078999 If Indian, All. or Tribe Name	
2. Name of Operator	7.	Unit Agreement Name	
ConocoPhillips	 8.	San Juan 31-6 Unit Well Name & Number	
3. Address & Phone No. of Operator	•		
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	SJ 31-6 Unit #25M API Well No.	
4 X and an extension of the beautiful and the be		30-039-30013	
4. Location of Well, Footage, Sec., T, R, M		Field and Pool	
Unit H (SENE) 2490' FNL & 660' FEL, Sec. 33, T31N, R6W, NMPM	Bianco	MesaVerde/Basin Dakota	
	11.	County and State Rio Arriba Co., NM	
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT Type of Submission Notice of Intent Abandonment Recompletion X Subsequent Report Plugging Casing Repair Final Abandonment Altering Casing Conversion to Injection	ORT, OTHER I X Other – Casi		
13. Describe Proposed or Completed Operations 5/28/07 MIRU Aztec 301. NU BOP. PT 9 5/8" casing to 600# 30/min – good test. RIH w/8 %" bit, tagged ce depth. Circ hole. RIH w/94 jts 7" 20# J-55 8RD ST & C casing set @ 3791', Stage tool @ 2800'. RU to cem clean/2 bbls H2O. Pumped Scavenger 19 sx(57cf-10bbls) Premium Lite Cement w/8% Bentonite, 3% CaCl2, SMS. Lead-pumped 57 sx(121cf-22bbls) Premium Lite FM Cement w/8% Bentonite, 3% CaCl2, .25 #/sx Ce pumped 88 sx(121cf-22bbls) Type III Cement w/1% CaCl2, & 2% FL-52. Dropped plug & displaced w/50 b 6/1/07. Did not circ cement. Open stage collar @ 2200#. Circ between stages. Waited 4 hrs before attempting Bbls Mud clean/2 bbls H2O. Pumped Scavenger 19 sx(57cf-10bbls) Premium Lite FM Cement w/8% Bentonite, 3% CaCl2, & .4% SMS. Lead-pumped 350 sx(746cf-133bbls) Premium Lite FM Cement w/8% Bentonite, 3% CaCM-1, & .4% SMS. Lead-pumped 350 sx(746cf-133bbls) Premium Lite FM Cement w/8% Bentonite, 3% CaCM-1, & .4% SMS. Dropped plug & displaced w/114 bbls H2O. Bumped plug to 2600# & close stage collar. Plug dow	ent. 6/1/07 1* Stage .25 #/sx Cello-flake, llo-Flake, 4% FL-52 bls H2O. Bumped pli to pump second stage ite, 3% CaCl2, .25 #/sx Cello	e-Pumped pre-flush of 10 bbls mud .4% FL-52, 5 #/sx LCM-1, & .4% .5 #/sx LCM-1, & .4% SMS. Tail- ug to 840#. Plug down @ 23:09 hrs ge. 2 nd Stage- pumped pre-flush of 10 /sx Cello-Flake, .4% FL-52, 5#/sx -Flake, .4% FL-52, 5% LCM-1, &	
6/3/07 Call to Wayne Townsend (BLM). Cement did not circ to surface on 7" casing 1" Stage <u>TOC @ 2</u> TOC @ 320'. Noclemento @ 584', Ojo @ 1750', Kirtland @ 2163', FC @ 3064'. Stage tool set @ 2800'			
6/2/07 RIH w/6 ¼" bit, tagged cement @ 3723'. PT 7" casing to 1500# 30/min – good test. D/O stage collar 6/5/07. Circ hole. RIH w/168 jts 4 ½" 10.5# J-55 8RD ST & C & 25 jts 4 ½" 11.6# L-80 8RD LT & C casing 10 bbls Gel H2O/2 bbls FW. Pumped Scavenger 9sx(27cf-5bbls) Premium Lite HS FM Cement w/.3% CD-3. Tail-pumped 308 sx(610cf-108bbls) Premium Lite HS FM Cement w/.3% CD-32, 1% FL-52, .25 #/sx Cellobbls FW. Bumped plug to 1550#. Plug down @ 12:40. WOC. ND BOP. RD RR @ 06:00 hrs on 6/7/07. The casing PT & TOC will be conducted by the completion rig and results shown on next report.	g set @ 8074'. RU to 2, 1% FL-52A, .25#/	cement. 6/6/07 Pumped pre-flush of /sx Cello-Flake, & 6.25 #/sx LCM-1.	
14. I hereby certify that the foregoing is true and correct.			

Title Regulatory Technician Date (This space for Federal or State Office use) APPROVED BY CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



FARMINGTON FIELD OFFICE