

#5=30-039-06968

3381

DATE:

17
4-17-96DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Location: Unit M Sec. 23 Twp 27 Rng 3Name of Well/Wells or Pipeline Serviced Jicarilla 94 #5Elevation _____ Completion Date 4-17-96 Total Depth 432' Land Type ICasing Strings, Sizes, Types & Depths 60' 8" PVC Casing Set on 4-15-96If Casing Strings are cemented, show amounts & types used CementedCasing with 14 Sacks.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NoneDepths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. Water at 80'Depths gas encountered: NoneGround bed depth with type & amount of coke breeze used: 432'5950 lbs AsburyDepths anodes placed: 0405, 385, 375, 365, 355, 300, 290, 280, 272, 264, 255, 245, 215, 205, 195Depths vent pipes placed: Surface to 432'Vent pipe perforations: 182' to 432'

Remarks: _____

RECEIVED
FEB 19 1997OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME (S), NUMBER (S)					DATE	NAME
2962-w	Jic 94 #5					4/17/96	David Ashworth
WORK	TOTAL	VOLTS	AMPS	- OHMS			
2109		11.9	28.9	.41			
REMARKS (notes for construction log)							
4-15 60' CASING 500' F = -684							
5950 lbs Coke 200							

DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE	
100	1.6		295	2.6		490			685			
105	1.7		300	2.6	6	495			690			
110	1.8		305	2.0		500			695			
115	2.4		310	1.8		505			700			
120	2.8		315	2.0		510						
125	2.0		320	1.3		515						
130	1.2		325	1.1		520						
135	1.1		330	1.6		525						
140	1.1		335	1.0		530						
145	1.1		340	1.0		535						
150	1.7		345	1.0		540						
155	1.7		350	1.7		545						
160	1.6		355	2.3	5	550						
165	1.9		360	2.5		555						
170	1.8		365	2.5	4	560						
175	1.7		370	2.5		565						
180	1.8		375	2.6	3	570						
185	1.7		380	2.3		575						
190	1.7		385	2.2	2	580						
195	2.6	15	390	1.7		585						
200	2.5		395	1.8		590						
205	2.3	14	400	1.6		595						
210	2.9		405	2.5	1	600						
215	2.7	13	410	2.2		605						
220	1.7		415	1.0		610						
225	1.2		420	1.1		615						
230	1.3		425	1.0		620						
235	1.4		430	4.32-7.7		625						
240	2.2	12	435			630						
245	2.6		440			635						
250	2.0	11	445			640						
255	2.5		450			645						
260	2.5	10	455			650						
265	2.8		460			655						
270	2.6	9	465			660						
275	2.7		470			665						
280	2.7	8	475			670						
285	2.7		480			675						
290	2.5	7	485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor
copy - Region Corrosion Specialist