

#63A = 30-039-25479

3422

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit 0 Sec. 10 Twp 29 Rng 7

Name of Well/Wells or Pipeline Serviced SAN JUAN 29-7#63A

Elevation — Completion Date 10/24/95 Total Depth 352' Land Type —

Casing Strings, Sizes, Types & Depths 100' of 8" PVC SURFACE CASING

If Casing Strings are cemented, show amounts & types used Yes 17 BAGS

CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Fresh H₂O 120'

Depths gas encountered: N/A

Ground bed depth with type & amount of coke breeze used: 352' deep

with 4,400 lbs Asbury 218R COKE breeze

Depths anodes placed: 341, 334, 327, 320, 313, 306, 299, 292, 177, 171, 165, 159, 153, 147

140

Depths vent pipes placed: 352'

Vent pipe perforations: bottom 240'

RECEIVED
FEB 19 1997

Remarks: —

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(S), NUMBER(S)				
2864u	S.S. 29-7 #63A				
WO #	TOTAL	VOLTS	AMPS	- OHMS	DATE
4928		11.3	12.7	.884	10-24-95
NAME					
7MRW					
REMARKS (notes for construction log)					
100' CASING 17 BAGS CEMENT					
Drilled 360' Logged 352' WATER 120'					
88 BAGS Asbury 218R bottom 240'					

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100			295	1.0		490			685			
105			300	1.6		495			690			
110	.4		305	1.7		500			695			
115	.5		310	1.6		505			700			
120	.7		315	1.0		510			ANODE	DEPTH	NO	FULLY
125	.7		320	.7		515			*		COKE	COKE'D
130	.7		325	.9		520			1	341	1.2	2.8
135	.8		330	1.0		525	334		2	325	1.0	2.3
140	1.3		335	.9		530	327		3	329	1.0	2.3
145	1.7		340	1.1		535	320		4	323	.9	2.3
150	1.8		345	1.7		540	313		5	317	1.5	3.7
155	1.5		350	1.6	352	545			6	306	1.7	4.1
160	1.7		355			550			7	299	1.3	3.6
165	2.0		360			555			8	292	1.2	2.9
170	2.1		365			560			9	177	1.6	4.9
175	1.8		370			565			10	171	2.2	5.7
180	.9		375			570			11	165	2.1	5.8
185	.4		380			575			12	159	1.9	5.8
190	.3		385			580			13	153	1.6	5.3
195	.3		390			585			14	147	2.0	5.3
200	.4		395			590			15	140	1.4	4.5
205	.5		400			595			16			
210	.6		405			600			17			
215	.7		410			605			18			
220	.8		415			610			19			
225	.7		420			615			20			
230	.7		425			620			21			
235	.7		430			625			22			
240	.7		435			630			23			
245	.6		440			635			24			
250	.6		445			640			25			
255	.6		450			645			26			
260	.7		455			650			27			
265	.6		460			655			28			
270	.6		465			660			29			
275	.6		470			665			30			
280	.7		475			670						
285	.8		480			675						
290	.9		485			680						

DISTRIBUTION - original - permanent CPS FILE

COPY

- Division Corrosion Supervisor

COPY

- Region Corrosion Specialist