

30-045-06613

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator ARCO Oil and Gas Company Location: Unit P Sec. 10 Twp 27N Rng 11W
Name of Well/Wells or Pipeline Serviced Schlosser WN Fed. #7

Elevation 6214' Completion Date 10/26/84 Total Depth 250' Land Type* F-SF078673

Casing, Sizes, Types & Depths Open hole, 7-7/8"

RECEIVED

FEB 25 1991

If Casing is cemented, show amounts & types used

OIL CON. DIV.
DIST. 3

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. Not available.

Depths gas encountered: None

Type & amount of coke breeze used: Hole filled with metallurgical coke breeze from bottom to surface
by slurry method.

Depths anodes placed: Anode tops at 240', 230', 220', 205', 185', 175', 165', 155'

Depths vent pipes placed: 245' to 3' above ground

Vent pipe perforations: 1/8" holes every 6" from 245' to 155'

Remarks: 3" x 60" graphite anodes

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL TYPE GROUND BED DATA

Data Sheet No. 25

COMPANY ARCO OIL AND GAS CO. JOB No. 248 DATE: 10-26-84
 WELL: SCHLOSSER #7 PIPELINE _____
 LOCATION: SEC. 10 TWP. 27-N RGE. 11-W CO. SAN JUAN STATE NEW MEXICO
 ELEV. _____ ft. ROTARY _____ ft. CABLE TOOL _____ ft. CASING _____ ft.
 GROUND BED: DEPTH 250 ft. DIA. 7 7/8 in. GAB ±2000 lbs. ANODES 8-3"X60" UCAR 79

DEPTH. FT.	DRILLER'S LOG	FINAL ANODE TO STRUCTURE			EXPLORING ANODE TO STRUCTURE			DEPTH TOP OF ANODES
		E	I	R	E	I	R	
50	0-20 BROWN SAND	14.5			12.6	2.5		
55	20-130 BLUE SAND					1.8		
60	130-180 BLUE SANDY SHALE - MOIST					1.7		
65	180-250 BLUE SAND					1.3		
70						1.2		
75						1.5		
80						1.5		
85						1.6		
90						1.7		
95						1.7		
100						2.7		
5						3.0		
10						2.6		
15						2.8		
20						2.9		
25						2.9		
30						3.6		
35						3.1		
40						3.3		
45						2.7		
50						3.1		
55			9.9			2.9		#8
60						3.1		
65			9.7			3.1		#7
70						2.6		
75			8.1			2.3		#6
80						1.9		
85			3.7			1.6		#5
90						1.1		
95						1.1		
200			3.3			1.0		
5						1.5		#4
10						1.1		
15						1.6		
20			3.9			1.5		#3
25						1.3		
30			8.0			1.9		#2
35						2.6		
40			8.0			2.4		#1
45						1.3		
50						1.1		

GROUND BED RESISTANCE: (1) VOLTS _____ * AMPS _____ OHMS

Corrosion Specialists, Ltd.

(2) VIBROGROUND _____ OHMS