

DATE:

5/29/96

34207

#28A = 30-045-

22916

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc Location: Unit F Sec. 26 Twp 32 Rng 10

Name of Well/Wells or Pipeline Serviced

S.J. 32-9 #28AElevation _____ Completion Date 5/29/96 Total Depth 485' Land Type FCasing Strings, Sizes, Types & Depths 5/28 Set 59' of 8" PVC CASING.NO GAS or WATER, But 18'(0-18') of Boulders Were Encountered During CASING.If Casing Strings are cemented, show amounts & types used CementedWITH 26 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONEDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. NO WATER.Depths gas encountered: NONEGround bed depth with type & amount of coke breeze used: 485' DEPTH.Used 101 SACKS OF Asbury 218R (5050#)Depths anodes placed: 475', 465', 441', 434', 427', 420', 394', 385', 368', 360', 280', 231', 224', 211', & 210'.Depths vent pipes placed: SURFACE TO 485'.Vent pipe perforations: BOTTOM 300'

RECEIVED

FEB 19 1997

Remarks: _____

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 1433-W DFL NAME(S) NUMBER(S) S.J. 32-9 #28A
 NO 2171 TOTAL VOLTS 11.53 AMPS 18.6 CHMS .620 DATE 5/29/96 NAME JOHN L. MOSS

REMARKS (PLEASE FOR CONSTRUCTION LOG) Drillet Reported DAMP AREAS
 AT 150', 210', AND 360' BUT NO LIVE WATER. INSTALLED 485' OF 1" PE VENT PIPE, WITH THE BOTTOM 300' PERFORATED.
 COKE BREEZE TO 190'.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
100			295	.8		490	T.D	485	685		
105			300	.8		495			690		
110			305	.2		500			695		
115			310	.3		505			700		
120			315	.2		510					
125			320	.2		515					
130			325	.4		520					
135			330	.1		525			1	475'	1.0
140			335	.2		530			2	465'	1.4
145			340	.2		535			3	441'	1.0
150	SANDSTONE		345	.2		540			4	434'	1.4
155			350	.2		545			5	427'	1.4
160			355	.2		550			6	420'	1.4
165			360	1.1	10	555			7	394'	1.1
170			365	1.8		560			8	385'	1.7
175			370	1.0	9	565			9	368'	1.1
180			375	.9		570			10	360'	2.0
185			380	.8		575			11	280'	1.0
190			385	1.7	8	580			12	231'	1.1
195			390	1.7		585			13	224'	1.6
200			395	1.1	7	590			14	217'	1.8
205			400	.5		595			15	210'	1.5
210	1.1	15	405	.3		600			16		
215	1.5	14	410	.4		605			17		
220	1.7		415	.7		610			18		
225	1.5	13	420	1.3	6	615			19		
230	1.2	12	425	1.5	5	620			20		
235	1.1		430	1.5		625			21		
240	.9		435	1.5	4	630			22		
245	.4		440	1.2	3	635			23		
250	.2		445	.7		640			24		
255	.3		450	.5		645			25		
260	.2		455	.5		650			26		
265	.2		460	.4		655			27		
270	.1		465	1.2	2	660			28		
275	1.0		470	1.0		665			29		
280	1.1	11	475	1.1	1	670			30		
285	.9		480	.5		675					
290	1.0		485	.4		680					