

#46A-30-045-29277

3429

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit 0 Sec. 04 Twp 31 Rng 09

Name of Well/Wells or Pipeline Serviced _____

SAN JUAN 32-9 #46A

Elevation — Completion Date 1/9/96 Total Depth 448' Land Type F

Casing Strings, Sizes, Types & Depths 1 1/8 SET 99' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used CEMENTED

WITH 24 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 160'

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 448' DEPTH.

USED 115' SACKS OF ASBURY 218R (5750#)

Depths anodes placed: 397', 390', 383', 376', 369', 362', 355', 337', 330', 323', 316', 285', 260', 250', +195'

Depths vent pipes placed: SURFACE TO 448'

Vent pipe perforations: BOTTOM 320'

Remarks: _____

RECEIVED
FEB 1 9 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPB# 2885-W P/L NAME(S), NUMBER(S) SAN JUAN 32-9 #46A
 NO 1C37 TOTAL VOLTS 11.44 AMPS 18.0 OHMS .636 DATE 11/9/96 NAME JOHN L. MOSS

REMARKS (NOTES FOR CONSTRUCTION LOG)

Driller Reported WATER AT 160'

INSTALLED 448' OF 1" PE VENT PIPES WITH THE BOTTOM 320' PERFORATED. COKE BREEZE TO 115'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	"		ANODE	"		ANODE	"		ANODE	"	
100			295	.4		490			685			
105			300	.8		495			690			
110			305	.8		500			695			
115			310	.9		505			700			
120			315	1.3	11	510			ANODE	DEPTH	NO	FULLY
125			320	1.0		515			"		COKE	COKE
130			325	1.0	10	520			1	397'	1.1	3.7
135			330	1.1	9	525			2	390'	1.3	3.6
140	.3		335	1.1	8	530			3	383'	1.4	4.6
145	.2		340	.8		535			4	376'	1.5	5.7
150	.1		345	.4		540			5	369'	1.3	6.4
155	.4		350	1.0		545			6	362'	1.8	6.4
160	.7		355	1.7	7	550			7	355'	1.3	5.9
165	.2		360	1.8	6	555			8	337'	1.0	4.5
170	.6		365	1.9		560			9	330'	1.1	4.8
175	.6		370	1.6	5	565			10	323'	1.0	5.0
180	.4		375	2.1	4	570			11	316'	1.2	5.2
185	.1		380	1.7		575			12	285'	1.1	4.3
190	.7		385	1.7	3	580			13	260'	1.4	5.2
195	1.1	15	390	1.6	2	585			14	250'	1.9	5.3
200	.8		395	1.1	1	590			15	195'	1.0	3.1
205	.5		400	.6		595			16			
210	.5		405	.3		600			17			
215	.9		410	.3		605			18			
220	.5		415	.3		610			19			
225	.4		420	.3		615			20			
230	.5		425	.4		620			21			
235	.4		430	.4		625			22			
240	.5		435	.3		630			23			
245	.6		440	.3		635			24			
250	1.3	14	445	T.D.	448'	640			25			
255	1.3		450			645			26			
260	1.2	13	455			650			27			
265	1.1		460			655			28			
270	.9		465			660			29			
275	.7		470			665			30			
280	.9		475			670						
285	1.1	12	480			675						
290	.5		485			680						

DISTRIBUTION - ORIGINAL - SEPARATE CPS FILE
 COPY - DIVISION CORROSION SUPERVISOR