

#3 = 30-039-07090

DATE: 6/19/96

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit B Sec. 15 Twp 27 Rng 04

Name of Well/Wells or Pipeline Serviced _____

SAN JUAN 27-4 #3

Elevation 6896 Completion Date 6/19/96 Total Depth 420' Land Type F

Casing Strings, Sizes, Types & Depths 6/18 Set 60' of 8" PVC CASING

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING

If Casing Strings are cemented, show amounts & types used Cemented

WITH 15 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 80'.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 420' DEPTH.

Used 88 SACKS OF ASBURY 218R (4400#)

Depths anodes placed: 394, 386, 355, 335, 305, 295, 285, 275, 265, 235, 215, 205, 195, 185, 175.

Depths vent pipes placed: SURFACE TO 420'.

Vent pipe perforations: BOTTOM 270'.

Remarks: _____

RECEIVED
FEB 19 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

SPB# 2975-W P/L NAME(S), NUMBER(S) S.J. 27-H #3
 NO 2R22 TOTAL VOLTS 11.67 AMPS 23.1 OHMS .505 DATE 6/19/96 NAME JOHN L. MOSS

REMARKS (NOTES FOR CONSTRUCTION LOG) Driller Reported WATER AT 80'.
 Installed 420' of 1" PE Vent Pipe, WITH THE BOTTOM
 270' Perforated. Cpk Breeze To 165'.

DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE	DEPTH	LOG ANODE	ANODE
100			295	2.4	6	490			685		
105			300	2.0		495			690		
110			305	1.4	5	500			695		
115			310	1.1		505			700		
120			315	.8		510					
125			320	.3		515					
130	.4		325	.5		520					
135	.7		330	1.0		525			1	394'	1.2
140	2.5		335	1.5	4	530			2	386'	1.6
145	2.6		340	.6		535			3	355'	1.9
150	2.5		345	.4		540			4	335'	1.6
155	1.1		350	.4		545			5	305'	1.4
160	.6		355	1.9	3	550			6	295'	2.4
165	.9		360	.9		555			7	285'	1.6
170	1.1		365	.9		560			8	275'	1.7
175	1.7	15	370	.6		565			9	265'	1.7
180	2.1		375	.3		570			10	235'	1.6
185	1.7	14	380	.4		575			11	215'	1.2
190	2.0		385	1.2	2	580			12	205'	1.5
195	2.2	13	390	1.6		585			13	195'	2.2
200	2.2		395	1.0	1	590			14	185'	1.6
205	1.5	12	400	.4		595			15	175'	1.9
210	1.2		405	.3		600			16		
215	1.3	11	410	.3		605			17		
220	.6		415	.3		610			18		
225	.5		420	T.O.	420'	615			19		
230	1.1		425			620			20		
235	1.6	10	430			625			21		
240	1.3		435			630			22		
245	.5		440			635			23		
250	.4		445			640			24		
255	.4		450			645			25		
260	.5		455			650			26		
265	1.7	9	460			655			27		
270	1.4		465			660			28		
275	1.6	8	470			665			29		
280	1.6		475			670			30		
285	1.6	7	480			675					
290	1.1		485			680					

DISTRIBUTION - ORIGINAL - DEPARTMENT CPS FILE

COPY

- DIVISION CORRECTION SUPERVISOR