

1 = 30-045-07318
6 = 30-045-21041 4760

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit H Sec. 21 Twp 28 Rng 8

Name of Well/Wells or Pipeline Serviced GRAMBLING A #1, #6

cps 470w

Elevation 5808 Completion Date 8/19/88 Total Depth 340' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 40'

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

OIL CON. DIV
DIST. 3

Type & amount of coke breeze used: N/A

Depths anodes placed: 320', 313', 296', 289', 282', 275', 260', 250', 215', 90'

Depths vent pipes placed: 345' OF 1" PVC VENT PIPE

Vent pipe perforations: BOTTOM 240'

Remarks: qb #3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

Redrill

Drilling Log (Attach Hereto) ☒Completion Date 8-19-88

CPS #	Well Name, Line or Plant: <i>Stambling A #1</i>	Work Order # <i>47916A</i>	Static:	Ins. Union Check ☐ Good ☐ Bad																																																												
<i>470W</i>	<i>3" #6</i>	<i>44378A</i>																																																														
Location: <i>H21-28-8</i>	Anode Size: <i>2" x 60"</i>	Anode Type: <i>Duriron</i>	Size Bit: <i>6 3/4"</i>																																																													
Depth Drilled <i>340'</i>	Depth Logged <i>340'</i>	Drilling Rig Time	Total Lbs. Coke Used	Lost Circulation Mat'l Used																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Anode Depth</td> <td colspan="2">Anode Output (Amps)</td> <td colspan="2">Anode Depth</td> <td colspan="2">Anode Output (Amps)</td> <td colspan="2">Total Circuit Resistance</td> </tr> <tr> <td># 1</td><td><i>320</i></td> <td># 2</td><td><i>313</i></td> <td># 3</td><td><i>296</i></td> <td># 4</td><td><i>289</i></td> <td># 5</td><td><i>282</i></td> </tr> <tr> <td># 6</td><td><i>275</i></td> <td># 7</td><td><i>260</i></td> <td># 8</td><td><i>250</i></td> <td># 9</td><td><i>215</i></td> <td># 10</td><td><i>90</i></td> </tr> <tr> <td># 11</td><td></td> <td># 12</td><td></td> <td># 13</td><td></td> <td># 14</td><td></td> <td># 15</td><td></td> </tr> <tr> <td># 16</td><td></td> <td># 17</td><td></td> <td># 18</td><td></td> <td># 19</td><td></td> <td># 20</td><td></td> </tr> <tr> <td colspan="2">Volts <i>12.46</i></td> <td colspan="2">Amps <i>21.0</i></td> <td colspan="2">Ohms <i>.59</i></td> <td colspan="2">No. 8 C.P. Cable Used</td> <td colspan="2">No. 2 C.P. Cable Used</td> </tr> </table>					Anode Depth		Anode Output (Amps)		Anode Depth		Anode Output (Amps)		Total Circuit Resistance		# 1	<i>320</i>	# 2	<i>313</i>	# 3	<i>296</i>	# 4	<i>289</i>	# 5	<i>282</i>	# 6	<i>275</i>	# 7	<i>260</i>	# 8	<i>250</i>	# 9	<i>215</i>	# 10	<i>90</i>	# 11		# 12		# 13		# 14		# 15		# 16		# 17		# 18		# 19		# 20		Volts <i>12.46</i>		Amps <i>21.0</i>		Ohms <i>.59</i>		No. 8 C.P. Cable Used		No. 2 C.P. Cable Used	
Anode Depth		Anode Output (Amps)		Anode Depth		Anode Output (Amps)		Total Circuit Resistance																																																								
# 1	<i>320</i>	# 2	<i>313</i>	# 3	<i>296</i>	# 4	<i>289</i>	# 5	<i>282</i>																																																							
# 6	<i>275</i>	# 7	<i>260</i>	# 8	<i>250</i>	# 9	<i>215</i>	# 10	<i>90</i>																																																							
# 11		# 12		# 13		# 14		# 15																																																								
# 16		# 17		# 18		# 19		# 20																																																								
Volts <i>12.46</i>		Amps <i>21.0</i>		Ohms <i>.59</i>		No. 8 C.P. Cable Used		No. 2 C.P. Cable Used																																																								

Remarks: *Water at 40'; water sample taken. Installed 345' of 1" PVC vent pipe, bottom 240' perforated. Water sample taken at 50'*

GB 4074.00

Rectifier Size: _____ V _____ A *0*
 Addn'l Depth _____
 Depth Credit: *160' @ 3.50* - *560.00*
 Extra Cable: *10' @ 2.40* - *24.00*
 Ditch & 1 Cable: *20' @ 7.00* - *14.00*
 25' Meter Pole: _____
 20' Meter Pole: _____
 10' Stub Pole: _____

GROUND BED LAYOUT SKETCH

Function Box

225.00
3755.40
187.77
3943.17

new GB
#2 ⊗ *20'* *rect*
present GB
 ⊗ *#1*

All Construction Completed

Calvin Rockman
 (Signature)



O. CRASS DRILLING CO.

Drill No. 3

DRILLER'S WELL LOG

S. P. No. Graveling #1-A Date 8-19-88
Client Meridian Oil Co. Prospect _____
County SAN JUAN State New Mex.

If hole is a redrill or if moved from original staked position show distance
and direction moved: _____

FROM	TO	FORMATION — COLOR — HARDNESS
0	25	SANDSTONE
25	35	SHALE
35	90	SAND —
90	130	SHALE
130	210	SANDSTONE
210	275	SANDY SHALE
275	340	SHALE

Mud _____ Bron _____ Lime _____

Rock Bit Number _____ Make _____

Remarks: Water @ 50'

Driller Rennie Brown