Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR BURGALL OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires: January 31, 2004

BUREAU OF LAND MANAGEMENT

5. Lease Serial No.

INDEV NOTICES AND DEPORTS ON WELLS	/	
UNDRY NOTICES AND REPORTS ON WELLS	1	

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

NMSF-079065
6. If Indian, Allottee or Tribe Name

abandoneu we	an. Ose Form 3100-3 (A	rb) for such proposais.	7	N/A		
SUBMIT IN TR	IPLICATE - Other ins	tructions on reverse si	58 12 AM 10:	3. If Unit or	r CA/Agreement, Name and/or No) .
1. Type of Well Oil Well Gas Well 2. Name of Operator Richardson Operating Company 3a. Address	_	- A 75	armington, N	N/A 8. Well Na F-RPC 29 9. API We 30-045-3) #1 II No.	
3100 La Plata Highway Farming 4. Location of Well (Footage, Sec., 1080' FNL & 1585' FEL Sec. 29, T29N, R13W NMPM		505-564-3100 7 ion)		W. Kutz 1	nd Pool, or Exploratory Area PC & Basin Fruitland Coal or Parish, State	
12. CHECK AP	PROPRIATE BOX(ES)	TO INDICATE NATURE TYPE	OF NOTICE, RE		New Mexico R OTHER DATA	
 □ Notice of Intent ☑ Subsequent Report □ Final Abandonment Notice 	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Start/ Reclamation Recomplete Temporarily Aba Water Disposal	,	Water Shut-Off Well Integrify Other See below	_
following completion of the inv	he work will be performed or provided operations. If the operations are the operations.	provide the Bond No. on file with ion results in a multiple completi	h BLM/BIA. Require on or recompletion in	d subsequent a new interv	work and approximate duration the ths of all pertinent markers and zon t reports shall be filed within 30 days, a Form 3160-4 shall be filed or been completed, and the operator I	ays nce

9/3/03 Spud 8 3/4" surface hole. Drill to 154'. SDFN.

9/4/03 Ran 4 jts. 7" 23# casing; set at 149.63'. Cemented with 81 sx Class 'B' w/ 3 % CaCl, 1/4# celloflake. Circ. 4.5 Bbl cement to pit. WOC 12 hours.

9/5/03 Install and test BOP to 600 psi; test good. Test surface casing to 600 psi; test good. Drill 6 1/4" hole to 450'. SDFN

9/6/03 Drill 6 1/4" hole to 1000'. SDFN.

9/8/03 Drill 6 1/4" hole to 1580'. Rig needs repair.

9/9/03 Rig Repair.

9/10/03 Drill 6 1/4" hole to TD. Tally and run 38 joints 4.5" J-55 10.5# casing; set guide shoe at 1618'. Float at 1578'. Cemented with 114 sx (235 cuft) Class 'B' with 2% metasilicate, 1/4# celloflake and 85 sx (100 cuft) Class 'B' with 2 % CaCl. Bumped plug to 800#, float held. Circ. 6 bbl cmt to surface.

14. 1 hereby certify that the foregoing is true and correct Name (PrintedlTyped)	1			
Drew Carnes	Title Operations Manager			
Signature	Date 9-11-03			
THIS SPACE FOR FEDER	AL OR STATE OFF	ICE USE ACCEPTED FOR RECORD		
Approved by (Signature)	Name (Printed/Typed)	Title		
Conditions of approval, if any, are attached. Approval of this notice does not w	orrant or Office	SEP 13at 5 2003		
certify that the applicant holds legal or equitable title to those rights in the subj which would entitle the applicant to conduct operations thereon.	ect lease	FARMINGTUN FIELD OFFICE		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for States any false, fictitious or fraudulent statements or representations as to any matter	any person knowingly and within its jurisdiction.	d willfully to make to any department or agency of the United		