Submit 3 Copies to Appropriate District Office DISTRICT I	State of New Mexico Energy, Minerals and Natural Reso OIL CONSERVATION P.O. Box 2088	ures Department JUN 2003 DIVISION	Form C-103 Revised 1-1-89
P.O. Box 1980, Hobbs, NM 88240 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, New Mexico 87.	CIL CONS. DIV.	WELLIAPI NO.
(DO NOT USE THIS FORM FOR P DIFFERENT I	NOTICES AND REPORTS ON WELLS PROPOSALS TO DRILL OR TO DEEPEN OR PLUCRESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name SANTA FE PACIFIC RAILROAD
2. Name of Operator ROBERT L. BAY 3. Address of Operator	ZLESS		8. Well No. 24 9. Pool name or Wildcat
4. Well Location Unit Letter A	<u>330</u> Feet from the <u>NORTH</u>	Line and 990	
Section 29	• • • • • • • • • • • • • • • • • • • •	nge 6W whether DF, RKB, RT, GR, etc.,	NMPM McKINLEY County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT X PULL OR ALTER CASING OTHER: OTHER:			
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Robert L. Bayless plugged and abandoned this well 4/23/03. The procedure is attached.			
	Tom McCarthy	ENGINEER	DATE 6/25/03 TELEPHONE NO. S (505) 327-2659 TELEPHONE NO. S (505) 327-2659
APPROVED BY CONDITIONS OF APPROVAL, IF ANY		DEPUTY OIL & GAS INSPE	CTOR, DIST. ED DATE

PN

9-25-03

Robert L. Bayless Plug and Abandon Report SFPRR No. 24

330' FNL & 990' FEL, Section 29, T16N, R6W McKinley County, NM

4/22/2003: Rig up JC Well Service. Pressure test tubing with rods and pump in hole. Tested OK. Trip out rods and pump, and used rod count as tally. Tag PBD at 775'. Roll hole with water. Mix and spot 16 sack bottom plug at 775'. Trip out tubing and WOC.

4/23/2003: Tag plug at 629'. Pressure test of casing to 300 PSI was OK. Perforated squeeze holes at 100'. Mix and pump 46 sacks cement. Circulated cement up casing and up backside. Rigged down. Class B cement was used.

Top off cement in both casings. Installed abandonment marker and backfilled pit. Cleaned up location.