

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

707 JUN 22 PM 3:35

1. Type of Well
GAS

2. Name of Operator
ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit F (SENW) 1465' FNL & 2020' FWL, Sec. 23, T31N, R8W, NMPM

5. Lease Number
SF-079047
6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. San Juan 32-8 Unit
Well Name & Number

9. SJ 32-8 Unit #17C
API Well No.

30-045-33681

10. Field and Pool

Blanco MV

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

☒ Other - Casing Report

RCVD JUN 29 07
OIL CONS. DIV.
DIST. 3

13. Describe Proposed or Completed Operations

6/7/07 MIRU Aztec 711. NU BOP. PT casing to 600# 30/min - good test. RIH w/8 3/4" bit, tagged cement @ 46'. D/O cement & ahead to 3190' intermediate. Circ Hole. RIH w/74 jts 20# J-55 ST & C casing set @ 3179'. RU to cement. 6/11/07 pumped pre-flush of 10 bbls FW/10 bbls MC/10 bbls FW. Pumped Scavenger 20 sx(60cf-11bbls) Type G Cement w/8% Bentonite, 3% CaCl₂, .25 #/sx Cello-flakes, .4% FL-52, 5 #/sx LCM-1, .4% SMS. Lead-pumped 370 sx(788cf-140bbls) Premium Lite Cement w/8% Bentonite, 3% CaCl₂, .25 #/sx Cello-Flakes, .4% FL-52, 5 #/sx LCM-1, .4% SMS. Tail- pumped 80 sx(110cf-20bbls) Type III Cement w/1% CaCl₂, .25 #/sx Cello-Flakes, 2% FL-52A. Dropped plug & displaced w/127 bbls FW. Circ 55 bbls cement to pit. Bumped plug to 1400#. RD cement.

6/12/07 RIH w/6 1/4" bit. PT casing to 1500# 30/min - good test. D/O cement & ahead to 6080' (TD). TD reached o 6/14/07. Circ hole. RIH w/144 jts 4 1/2" 10.5# J-55 & 1 jts 4 1/2" 11 6# J-55 Casing set @ 6040'. RU to cement. 6/16/07. Pumped pre-flush of 10 bbls gel H₂O/2 bbls FW. Pumped Scavenger 10sx(30cf-5bbls) Premium Lite HS FM Cement w/ 25 #/sx Cello-Flakes, 6.25 #/sx CD-32, 1% FL-52, 1% LCM-1. Pumped 210 sx(416cf-74bbls) Premium Lite HS FM Cement w/ 6.25 #/sx CD-32, .25 #/sx Cello-Flake, 1% FL-52A, & 1% LCM-1. Dropped plug & displaced w/86 bbls FW. Bumped plug to 1190#. Plug down @ 08:100. ND RD RR @ 14.00

The casing PT will be conducted by the completion rig and results shown on next report.

Report to C A/S O.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 6/21/07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD

JUN 28 2007

FARMINGTON FIELD OFFICE