

UNITED STATES  
DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION TO DRILL" for permit for such proposals

5. Lease Designation and Serial No.  
NMSF-078764

Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

If Unit or CA, Agreement Designation

1. Type of Well  
Oil Well ☒ Gas Well ☐ Other ☐

8. Well Name and No.  
ROSA UNIT #183B

2. Name of Operator  
WILLIAMS PRODUCTION COMPANY

9. API Well No.  
30-039-30087

3. Address and Telephone No  
PO BOX 3102 MS 25-2, TULSA, OK 74101 (918) 573-6254

10. Field and Pool, or Exploratory Area  
BLANCO MESAVERDE

4. Location of Well (Footage, Sec., T, R., M, or Survey Description)  
590' FNL & 2180' FEL, NW/4 NE/4 SEC 19-T31N-R05W

11. County or Parish, State  
RIO ARRIBA, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

Notice of Intent  
☒ Subsequent Report  
Final Abandonment

Abandonment  
Recompletion  
Plugging Back  
Casing Repair  
Altering Casing  
Other Missing Information

Change of Plans  
New Construction  
Non-Routine Fracturing  
Water Shut-Off  
Conversion to Injection  
Dispose Water  
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The following pressure tests were conducted after the surface csg was landed & cmt'd on 5/1/07: test BOP pipe & blind rams, choke manifold valves, mud cross valves, floor valve, supper Kelly valve & standpipe valve to 250 psi low for 5 mins & 1500 psi high for 10 mins, no leak off. Tested 9-5/8" csg to 1500 psi, held for 30 mins, no leak off. All tested good.

7" intermediate csg information: 7", 23#, J-55, LT&C csg.

4 1/2" production csg information: 4 1/2", 10.5#, J-55, ST&C csg. TOC on production csg is @ surface.

RCVD JUL 2'07  
OIL CONS. DIV.  
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed Tracy Ross  
Tracy Ross

Title Sr. Production Analyst

Date June 25, 2007

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

Conditions of approval, if any:

Title 18 U.S.C Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

FARMINGTON FIELD OFFICE