

24-30-045-11098
252-30-045-27840
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Company Location: Unit A Sec. 5 Twp 31 Rng 9

Name of Well/Wells or Pipeline Serviced San Juan 32-9 #252 + 24
CPS #408:W

Elevation 6746 Completion Date 7-3-91 Total Depth 385' Land Type F

Casing Strings, Sizes, Types & Depths 100' 8" PUC Casing

If Casing Strings are cemented, show amounts & types used yes - 20 sacks

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Water at 110' - Fresh

Depths gas encountered: None

Ground bed depth with type & amount of coke breeze used: Gr. Bed Depth - 385'
Loresco SW - Coke From 385' up to 110'

Depths anodes placed: #1-371', #2-362', #3-352', #4-342', #5-325', #6-315', #7-306', #8-271'
#9-265', #10-190', #11-171', #12-110'

Depths vent pipes placed: 385' to Surface

Vent pipe perforations: From 385' to 85'

Remarks: No gas encountered on drilling of hole

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
FEB 24 1992
OIL CON. DIV. I
DIST 3

CPS GROUP BED CONSTRUCTION WORKSHEET

CPS# 408-U	P/L NAME(S), NUMBER(S) San Juan 32-9 #24 + #252					
NO # 1392	TOTAL	VOLTS 12.2	AMPS 13.8	OHMS .88	DATE 7-3-91	NAME David Ashworth

REMARKS (notes for construction log)

H₂O at 110'

300' Vent Pipe - Perf.

DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	
100	2.2		295	.9		490			685			
105	1.9		300	1.0		495			690			
110	2.1		305	1.3	7	500			695			
115	1.9		310	1.6		505			700			
120	1.9	12	315	1.7	6	510			ANODE	DEPTH	NO	FULL
125	3.1		320	1.4		515			*		COKE	COKE
130	3.4		325	1.2	5	520			1	371	2.5	4.0
135	2.3		330	1.1		525			2	362	2.6	4.7
140	2.1		335	1.0		530			3	352	2.4	4.7
145	1.9		340	1.0	4	535			4	342	2.0	4.3
150	1.1		345	1.4		540			5	325	1.3	2.3
155	.7		350	2.0	3	545			6	315	1.8	2.9
160	.6		355	2.3		550			7	306	1.7	2.8
165	1.1		360	2.4	2	555			8	274	1.5	2.6
170	1.6	11	365	2.8		560			9	265	1.7	2.7
175	2.2		370	2.7	1	565			10	180	2.3	3.3
180	1.6	10	375	2.3		570			11	171	2.0	3.2
185	.9		380	2.3		575			12	121	2.4	3.8
190	.7		385	TD 385		580			13			
195	.4		390			585			14			
200	.3		395			590			15			
205	.3		400			595			16			
210	.4		405			600			17			
215	.6		410			605			18			
220	1.0		415			610			19			
225	1.0		420			615			20			
230	.8		425			620			21			
235	.6		430			625			22			
240	.6		435			630			23			
245	.9		440			635			24			
250	.8		445			640			25			
255	.9		450			645			26			
260	1.4		455			650			27			
265	1.6	9	460			655			28			
270	1.4		465			660			29			
275	1.2	8	470			665			30			
280	1.0		475			670						
285	1.1		480			675						
290	1.0		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist