

49-30-039-07386
103-30-039-21866
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator MERIDIAN Location: Unit 4 Sec. 23 Twp 28 Rng 5

Name of Well/Wells or Pipeline Serviced S. J. 28-5 # 49, # 103

Elevation 7462 Completion Date 8-18-91 Total Depth 460 Land Type F

Casing Strings, Sizes, Types & Depths SURFACE CASING 100'

DEEP 8"

If Casing Strings are cemented, show amounts & types used Yes 20

BAGS NEAT CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used.

NO

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. _____

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 457' with

33 100 lb bags LORESCO Type SW + 60 bags Asbury Flocoke (50 lb) 4518

Depths anodes placed: 424, 415, 405, 390, 380, 370, 361, 350, 340, 324, 315, 290

Depths vent pipes placed: 457'

Vent pipe perforations: bottom 320

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV. I

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s)					
1127-u	S.J. 28-5 # 49, #103					
WO #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
		11.63	27.2	.43	8-18-91	MW
REMARKS (notes for construction log)						
100' 8" RASING 20 BAGS cement						
Drilled 460 LOGGED 457 Damp 130 & 270 NOT Enough for sample						
perforated 320' 33 horesco						
(60) Asbury						

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100			295	4.1		490			685			
105			300	3.9		495			690			
110			305	4.1		500			695			
115			310	4.8		505			700			
120			315	5.4-		510			ANODE	DEPTH	NO.	FULLY
125			320	5.0		515			#		COKE	COKE'D
130			325	4.0-		520			1	424	4.2	6.2
135			330	3.7		525			2	415	5.0	7.2
140			335	3.9		530			3	405	4.7	6.7
145			340	4.3-		535			4	390	3.9	6.3
150			345	4.2		540			5	380	5.4	7.4
155			350	4.2-		545			6	370	4.8	7.1
160			355	4.1		550			7	361	4.4	6.3
165			360	4.2-		555			8	350	4.3	6.5
170			365	4.8		560			9	340	4.3	6.6
175			370	4.8-		565			10	324	4.2	6.8
180			375	5.3		570			11	315	5.5	8.1
185			380	5.2-		575			12	290	4.3	6.9
190			385	4.1		580			13			
195			390	3.8-		585			14			
200			395	3.4		590			15			
205			400	4.0		595			16			
210			405	4.6-		600			17			
215			410	4.5		605			18			
220			415	5.0-		610			19			
225			420	4.7		615			20			
230			425	3.8-		620			21			
235			430	3.5		625			22			
240			435	3.6		630			23			
245			440	3.6		635			24			
250			445	3.5		640			25			
255			450	3.5		645			26			
260			455			650			27			
265			460	TO 457		655			28			
270	.8		465			660			29			
275	1.8		470			665			30			
280	3.3		475			670						
285	4.2		480			675						
290	4.4-		485			680						

DISTRIBUTION - original - permanent CPS FILE.

copy - Division Corrosion Supervisor.

copy - Region Corrosion Specialist.