

9-30-045-05824

12-30-045-05839

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

17-30-045-21406

Operator Meridian O. I. Inc. Location: Unit 0 Sec. 15 Twp 26 Rng 9Name of Well/Wells or Pipeline Serviced Ballard #17, #12, #9CPS# 1022Elevation 178 Completion Date 11-13-91 Total Depth 320 Land Type FCasing Strings, Sizes, Types & Depths Set 90' at 8" P.V.C.If Casing Strings are cemented, show amounts & types used Used 22
sacks of neat cement.If Cement or Bentonite Plugs have been placed, show depths & amounts used
No plugsDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Water was at 150' and clear.Depths gas encountered: No gasGround bed depth with type & amount of coke breeze used: 320' with
42 sacks of Asbury 45' 8Depths anodes placed: #1 is at 305' & #10 is at 175'Depths vent pipes placed: 320 to surfaceVent pipe perforations: vent pipe is perforated up to 150'

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED

FEB 24 1992

OIL CON. DIV.]

DIST. 3

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 1032-W	P/L NAME(S), NUMBER(S) Ballard #12, #12, #9
0 *	TOTAL VOLTS 11.69
	AMPS 15.7
	OHMS .74
	DATE 11-13-91
	NAME R. Smith

REMARKS (notes for construction log)

H₂O is at 150' vent pipe
is perforated up to 150'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100			295	2.2	(2)	490			685			
105			300	2.2		495			690			
110			305	2.4	(1)	500			695			
115			310	2.3		505			700			
120	2.3		315	2.3		510			ANODE	DEPTH	NO	FULLY
125	2.6		320	10.320		515			*		COKE	COKE'D
130	2.6		325			520			1	305	2.4	4.2
135	2.6		330			525			2	295	2.3	4.2
140	2.6		335			530			3	284	2.5	4.4
145	2.6		340			535			4	275	2.3	4.3
150	2.7		345			540			5	265	2.5	4.3
155	2.6		350			545			6	255	2.5	4.5
160	2.5		355			550			7	245	2.5	4.6
165	2.5		360			555			8	235	2.4	4.5
170	2.5		365			560			9	225	2.6	4.7
175	2.5	(2)	370			565			10	215	2.7	4.6
180	2.3		375			570			11	205	2.6	4.5
185	1.7		380			575			12	175	2.6	4.5
190	1.8		385			580			13			
195	1.7		390			585			14			
200	2.2		395			590			15			
205	2.6	(1)	400			595			16			
210	2.7		405			600			17			
215	2.7	(2)	410			605			18			
220	2.8		415			610			19			
225	2.5	(2)	420			615			20			
230	2.4		425			620			21			
235	2.5	(2)	430			625			22			
240	2.6		435			630			23			
245	2.3	(2)	440			635			24			
250	2.5		445			640			25			
255	2.4	(6)	450			645			26			
260	2.4		455			650			27			
265	2.4	(6)	460			655			28			
270	2.3		465			660			29			
275	2.3	(2)	470			665			30			
280	2.3		475			670						
285	2.5	(3)	480			675						
290	2.2		485			680						

DISTRIBUTION - original - permanent CPS FILE.

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist