

550

05-30-045-05900 92-30-045-05910

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc. Location: Unit 4 Sec. 12 Twp 26 Rng 9Name of Well/Wells or Pipeline Serviced Huerfano #92 and
Huerfano #65 1019WElevation 218 Completion Date 11-12-91 Total Depth 363 Land Type FCasing Strings, Sizes, Types & Depths Set 700' of 8" P.U.C.If Casing Strings are cemented, show amounts & types used Used 23
sacks of neat cementIf Cement or Bentonite Plugs have been placed, show depths & amounts used
no plugsDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. water is at 160' and is clear.Depths gas encountered: no gasGround bed depth with type & amount of coke breeze used: 363' with
50 sacks of loresco S.W.Depths anodes placed: #1 is at 350' & #12 is at 180'Depths vent pipes placed: 363' to surfaceVent pipe perforations: vent pipe is perforated up to 160'

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Prop.
If Federal or Indian, add Lease Number.

RECEIVED
FEB 24 1992OIL CON. DIV.
DIST. 3

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 1019-W	P/L NAME(s), NUMBER(s) Huerfano #92, #65					
J # m914	TOTAL	VOLTS 12.34	AMPS 30.3	- OHMS	DATE 11-12-91	NAME R. Smith

REMARKS (notes for construction log)

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100			295	1.3		490			685			
105			300	1.2		495			690			
110			305	2.3		500			695			
115			310	3.0	(5)	505			700			
120			315	3.0		510			ANODE	DEPTH	NO	FULLY
125			320	3.1	(4)	515			*		COKE	COKE D
130			325	3.1		520			1	350	3.1	6.8
135			330	3.0	(4)	525			2	340	3.0	7.1
140			335	2.9		530			3	330	3.1	7.0
145			340	3.2	(2)	535			4	320	3.2	6.9
150			345	3.1		540			5	310	3.0	6.5
155			350	3.1	(1)	545			6	240	2.9	7.1
160	1.0		355	3.1		550			7	230	3.0	7.9
165	.9		360	2.9		555			8	220	3.5	9.3
170	1.0		365	TD 36.3		560			9	210	3.1	8.6
175	2.0		370			565			10	200	3.0	9.5
180	3.0	(12)	375			570			11	190	2.9	9.6
185	2.9		380			575			12	180	3.0	6.7
190	2.9	(8)	385			580			13			
195	2.9		390			585			14			
200	3.0	(10)	395			590			15			
205	3.0		400			595			16			
210	2.8	(7)	405			600			17			
215	3.3		410			605			18			
220	3.9	(8)	415			610			19			
225	3.0		420			615			20			
230	3.2	(11)	425			620			21			
235	2.9		430			625			22			
240	2.2	(6)	435			630			23			
245	2.0		440			635			24			
250	1.9		445			640			25			
255	1.7		450			645			26			
260	1.3		455			650			27			
265	.9		460			655			28			
270	.9		465			660			29			
275	1.0		470			665			30			
280	1.1		475			670						
285	1.1		480			675						
90	1.0		485			680						

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist