

660
30-039-24982
E
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Mexican Oil Location: Unit H Sec. 21 Twp 31 Rng 5

Name of Well/Wells or Pipeline Serviced Kass # 262

CPS # 2289-P

Elevation 5560 Completion Date 4-22-91 Total Depth 495' Land Type F

Casing Strings, Sizes, Types & Depths 60' 40' 4" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO OIL CON. DIV.

Ground bed depth with type & amount of coke breeze used: DIST. 3

495' Ashbury 84 sacks

Depths anodes placed: 470 455 420 400 390 350 360 330 315 295 286 273

Depths vent pipes placed: 455

Vent pipe perforations: 1" apart Perforated bottom 360'

Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s)					
2289-u	Kara # 262					
WO #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
L483		12.43	24.4	.50	9-22-91	L.S.E
REMARKS (notes for construction log)						
Dry hole. Not bc' of 8' PWC saving.						
Separated bottom 360' from 2nd Anode.						

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100			295	2.7	-10	490	1.7		685			
105			300	2.4		495	TD	495	690			
110			305	2.3		500			695			
115			310	2.7		505			700			
120			315	2.5	-9	510			ANODE	DEPTH	NO	FULLY
125			320	2.4		515			#		COKE	COK'D
130			325	2.6		520			1	420	2.6	4.9
135			330	2.8	-9	525			2	455	2.6	5.3
140			335	2.7		530			3	420	2.7	5.0
145			340	3.1		535			4	400	2.8	5.2
150			345	2.7		540			5	390	2.9	5.3
155	3.2		350	3.4		545			6	380	2.8	5.1
160	2.7		355	2.9		550			7	360	2.8	5.0
165	2.4		360	2.8	-7	555			8	330	2.8	4.9
170	3.0		365	2.7		560			9	315	2.8	5.3
175	2.5		370	3.2		565			10	295	2.7	5.2
180	2.7		375	3.0		570			11	286	2.5	5.0
185	2.5		380	2.8	-6	575			12	273	2.8	5.6
190	2.5		385	2.9		580			13			
195	2.5		390	2.8		585			14			
200	3.2		395	2.9		590			15			
205	3.1		400	2.8	-4	595			16			
210	3.3		405	2.1		600			17			
215	3.1		410	3.1		605			18			
220	3.0		415	3.0		610			19			
225	3.0		420	2.6	-3	615			20			
230	3.2		425	2.1		620			21			
235	3.3		430	2.2		625			22			
240	3.1		435	2.3		630			23			
245	3.3		440	2.2		635			24			
250	3.4		445	2.3		640			25			
255	3.1		450	2.2		645			26			
260	2.9		455	2.7	-2	650			27			
265	3.1		460	2.3		655			28			
270	3.3		465	2.0		660			29			
275	2.5	-12	470	2.6	-1	665			30			
280	2.3		475	2.5		670						
285	2.4	-11	480	2.4		675						
290	2.6		485	1.9		680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist