

653

30-039-24493

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

2280w

Operator Mesa Verde Oil Location: Unit A Sec. 13 Twp 31 Rng 6

Name of Well/Wells or Pipeline Serviced Ross #220

Elevation 6470 Completion Date 10-11-91 Total Depth 367 Land Type F

Casing Strings, Sizes, Types & Depths 60" sch 40 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO OIL CON. DIV.

Ground bed depth with type & amount of coke breeze used. DIST. 3

367' Ashbury 58 sacks

Depths anodes placed: 345, 320, 280, 270, 255, 240, 225, 210, 195, 185, 150, 140

Depths vent pipes placed: 320

Vent pipe perforations: 1" apart, Perforated bottom 200'

Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2280-W	P/L NAME(s), NUMBER(s) Rosa # 220					
O # K719	TOTAL	VOLTS 12.50	AMPS 21.9	- OHMS .57	DATE 10-11-91	NAME L.S.E.

REMARKS (notes for construction log)

No water table, Dry hole. Set 60' of 8" PVC casing. Perforated bottom 200' from 2nd anode.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100			295	1.6		490			685			
105			300	1.6		495			690			
110	2.2		305	1.6		500			695			
115	2.0		310	1.8		505			700			
120	2.1		315	1.9		510			ANODE	DEPTH	NO.	FULLY
125	2.2		320	2.0	-2	515			#	COKE	COKE	D
130	2.1		325	1.9		520			1	345	2.1	3.7
135	2.1		330	1.9		525			2	320	2.0	4.2
140	3.2	-12	335	1.8		530			3	280	2.4	4.6
145	3.6		340	1.8		535			4	270	2.6	4.7
150	2.9	-11	345	2.0	-1	540			5	255	3.1	5.4
155	1.7		350	2.1		545			6	240	2.9	5.2
160	1.8		355	2.1		550			7	225	3.0	5.1
65	1.7		360	2.0		555			8	210	2.7	5.0
170	1.7		365	TD	367	560			9	195	3.0	5.0
175	1.9		370			565			10	185	2.6	4.4
180	1.7		375			570			11	150	2.9	6.0
185	2.4	-10	380			575			12	140	3.0	6.5
190	2.8		385			580			13			
195	2.8	-9	390			585			14			
200	2.7		395			590			15			
205	2.8		400			595			16			
210	2.5	-8	405			600			17			
215	2.2		410			605			18			
220	2.8		415			610			19			
225	2.8	-7	420			615			20			
230	2.9		425			620			21			
235	2.9		430			625			22			
240	2.8	-6	435			630			23			
245	3.0		440			635			24			
250	3.0		445			640			25			
255	2.6	-5	450			645			26			
260	2.0		455			650			27			
265	2.5		460			655			28			
270	2.5	-4	465			660			29			
275	2.3		470			665			30			
280	2.2	-3	475			670						
285	2.0		480			675						
10	1.9		485			680						

DISTRIBUTION -- original -- permanent CPS FILE

copy

-- Division Corrosion Supervisor

copy

-- Region Corrosion Specialist