

6:30
30-039-25020
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
22760

Operator MERIDIAN C.I. INC Location: Unit B Sec. 29 Twp 28 Rng 6

Name of Well/Wells or Pipeline Serviced SAN JUAN 28-6-#475

Elevation 6294 Completion Date 8-30-91 Total Depth 300' Land Type SF-07905

Casing Strings, Sizes, Types & Depths 90' 8" SURFACE CASING
100'

If Casing Strings are cemented, show amounts & types used 2A SACKS

CLEAN CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

No

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Approx. 100'; Fresh, Driller did NOT provide
SAMPLE

Depths gas encountered: No

Ground bed depth with type & amount of coke breeze used: 300'; 86 sacks
of Ashbury 4518 Flocok

Depths anodes placed: 285, 204, 199, 189, 179, 169, 159, 149, 139, 129, 119, 109

Depths vent pipes placed: 300'

Vent pipe perforations: bottom 200'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.)

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	2276					
P/L NAME(s), NUMBER(s)	SAN JUAN 28-6-#475					
Q #	TOTAL	VOLTS	AMPS	OHMS	DATE	NAME
M57		12.8	26.7	48	8-30-91	W.R. McGaha

REMARKS (notes for construction log)

90"
100" 8" SURFACE CASING. HIT H₂O RIGHT UNDER CASING. CEMENT CASING W/24 SACKS.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100	3.0	12	295	1.8		490			685			
105	2.9		300		300	495			690			
110	2.9		305			500			695			
115	2.5		310			505			700			
120	2.4	11✓	315			510			ANODE	DEPTH	NO	FULLY
125	3.1		320			515			*		COKE	COK'D
130	2.9	0✓	325			520			1	285	2.0	4.7
135	3.2		330			525			2	209	2.5	5.8
140	3.3	1✓	335			530			3	279	3.5	7.9
145	3.2		340			535			4	129	3.5	8.5
150	3.2	3✓	345			540			5	179	3.2	8.4
155	3.3		350			545			6	169	3.3	8.1
160	2.9	2✓	355			550			7	159	3.0	7.9
165	3.6		360			555			8	149	3.1	8.2
170	3.2	0✓	365			560			9	139	3.3	8.2
175	2.3		370			565			10	129	2.9	7.3
180	2.3	5✓	375			570			11	119	2.4	6.6
185	2.7		380			575			12	109	2.9	6.7
190	2.4	4✓	385			580			13			
195	2.6		390			585			14			
200	2.2	3✓	395			590			15			
205	2.2		400			595			16			
210	2.0	2✓	405			600			17			
215	1.3		410			605			18			
220	1.2		415			610			19			
225	1.0		420			615			20			
230	1.0		425			620			21			
235	1.0		430			625			22			
240	1.2		435			630			23			
245	3		440			635			24			
250	1.2		445			640			25			
255	1.0		450			645			26			
260	1.2		455			650			27			
265	2		460			655			28			
270	2		465			660			29			
275	2		470			665			30			
280	2.1		475			670						
285	2.1	1✓	480			675						
290	1.8		485			680						

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist