

4603

1-30045-08245

7-30-045-20908

201-30-045-26986

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 17 Twp 29 Rng 8Name of Well/Wells or Pipeline Serviced DAY #1, DAY #7, DAY #201cps 80wElevation 6400' Completion Date 9/25/68 Total Depth 420' Land Type* N/ACasing, Sizes, Types & Depths N/AIf Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 40'**RECEIVED**

MAY 31 1991

Depths gas encountered: N/A**OIL CON. Dⁿ
DIST. ?**Type & amount of coke breeze used: 4800 lbs.Depths anodes placed: 334', 328', 322', 316', 310', 304', 298', 292', 209', 203'Depths vent pipes placed: 334' OF 3/4" HOSEVent pipe perforations: 334'Remarks: vgb #2 MOVED RIG OVER OLD GB TO RECLAIM OLD ANODES.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

Date 9-25-68

Insert 506 = 140
- Insert 503 = 200
4 1/2" Rod 49603 = 280

Well Name <u>Day #1</u>				CPS No. <u>80 W</u>			
Location <u>SW 17-29-8</u>				Work Order No. <u>184-52041-50-20</u>			
Anode Hole Depth <u>420</u>	Total Drilling Rig Time <u>33 1/2</u> <u>sec</u>	Type & Size Bit Used <u>6 3/4, 285495-420'</u>		No. Sacks Mud Used <u>0</u>			
No. Sacks Lost Circulation Mat'l Used <u>0</u>	Anode Depth						
	# 1 <u>334</u>	# 2 <u>328</u>	# 3 <u>322</u>	# 4 <u>316</u>	# 5 <u>310</u>	# 6 <u>304</u>	
Total Lbs. Coke Used <u>4800</u>	Anode Output (Volts)						
	# 1 <u>2.7</u>	# 2 <u>3.5</u>	# 3 <u>3.5</u>	# 4 <u>3.2</u>	# 5 <u>3.4</u>	# 6 <u>3.5</u>	
Total Circuit Resistance	No. Ft. Surface Cable Conduit						
Volts <u>13.0</u>	Amps <u>9.8</u>	Ohms <u>1.32</u>	<u>31160 W Anodes 130 surface 3246</u>				
Drilling Log (Attach Hereto). ☐			7 <u>298</u>	8 <u>292</u>	9 <u>209</u>	10 <u>203</u>	
Remarks:			7 <u>3.0</u>	8 <u>2.6</u>	9 <u>3.2</u>	10 <u>2.8</u>	

3/4" Hose to No. 1 Anode - Perforated All

Note - Moved Rig over old GB To Reclaim old Anodes 8 1/2 Hrs
Insert #503 = 200 7 7/8 1631133 = 80'

All Construction Completed

Samuels
(Signature)

GROUND BED LAYOUT SKETCH



