

4808

Operator MERIDIAN OIL Location: Unit SW Sec. 28 Twp 29 Rng 7

Name of Well/Wells or Pipeline Serviced SAN JUAN 29-7 UNIT #41, #124

cps 120w

Elevation 6577' Completion Date 12/26/62 Total Depth 65' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 425 lbs.

Depths anodes placed: 52', 46', 40', 34', 25'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: qb #1

RECEIVED
MAY 31 1991
CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
MAY 31 1991
CON. DIV.
DIST. 3

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

DATE 12-26-62

WELL NAME 29-7 # 41

CPS NO. 1204

LOCATION 28-29N-7W

WORK ORDER NUMBER 184-40542-50-02

ANODE HOLE DEPTH 65'

TOTAL DRILLING RIG TIME 5 hrs

DRILLING TIME FOR RECTIFIER POLE HOLE 0

TYPE AND SIZE BIT USED _____

NUMBER SACKS MUD USED 0

NUMBER SACKS LOST CIRCULATION MAT'L USED 0

ANODE DEPTHS #1 52', #2 46', #3 40, #4 34' 5.25'

TOTAL LBS. COKE USED 425 lbs

ANODE OUTPUTS 12 VOLTS, #1 3.4, #2 3.3, #3 3.8, #4 3.4 5.3.7

TOTAL CIRCUIT RESISTANCE: VOLTS 11.6 AMPERES 8.1 OHMS 1.44

NUMBER FEET SURFACE CABLE CONDUIT 370'

DRILLING LOG (ATTACH HERETO).

FORMATION LOG (ATTACH HERETO).

REMARKS: Static c/s .68 600' w

Anodes = 1.92 R

ALL CONSTRUCTION COMPLETED

E. Paulk
SIGNATURE

GROUND BED LAYOUT SKETCH



ORIGINAL & 1 COPY
ALL REPORTS

567'

