District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico Energy Minerals and Natural Resources

ion Dr. For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505 Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ⊠ No ☐

Type of action: Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator: BP AMERICA PROD. CO.	Telephone: (505)-326-9200 e-mai	l address:
Address: 200 ENERGY COURT, FARMINGTON.		1 4441000.
	API#: 30-045- 25883 U/L or Qtr/Q	otr M Sec 28 T 32N R 10W
County: SAN JUAN Latitude 36.95129 Longitude 10		
<u>Pit</u>	Below-grade tank	
Type: Drilling Production Disposal M BLOW	Volume:bbl_Type-of-fluid: /	
Workover ☐ Emergency ☐	Construction materia:	RCVD APR5'07
Lined Unlined 🛛	Double-walled, with leak distection? Yes If it	explain why not
Liner type: Synthetic Thickness mil Clay		UIL COMS. DIV.
Pit Volumebbl		DIST. 3
	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points) 0
high water elevation of ground water.)	100 feet or more	(0 points)
	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)
water source, or less than 1000 feet from all other water sources.)		(o points)
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) attach a diagram of the facility showing the pit's	relationship to other equipment and tanks. (2) Indicate	te disposal location: (check the onsite box if
your are burying in place) onsite \(\square\) offsite \(\square\) If offsite, name of facility	. (3) Attach a general de	escription of remedial action taken including
remediation start date and end date. (4) Groundwater encountered: No 🔯 Y		
Attach soil sample results and a diagram of sample locations and excavation		
Additional Comments PIT LOCATED APPROXIMATELY		I.I. HEAD
PIT EXCAVATION: WIDTH N/Aft., LENGTH		GB TIB. NO.
PIT REMEDIATION: CLOSE AS IS: ⊠, LANDFARM: □, C		-1-:->
	OMPOST: [], STOCKPILE: [], OTHER [] (ex	piain)
Cubic yards: N/A	4.44.44.4	
I hereby certify that the information above is true and complete to the best	of my knowledge and helief. I further earlify that th	no above described nit or below grade tank
has been/will be constructed or closed according to NMOCD guideline		
Date: 02/15/06		
Date: 02/13/00		•
PrintedName/Title Jeff Blagg - P.E. # 11607	Signature The C	
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.		
Approval: Deputy Oil & Gas Inspector, Printed Name/Title District #3 Signal Sig	gnature Bund EM	Date: AUG 0 2 2007

TRAVEL NOTES.

CALLOUT: _



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	5-Point Composite @ 6'	Date Reported:	02-15-06
Laboratory Number:	36230	Date Sampled:	02-14-06
Chain of Custody No:	15551	Date Received:	02-14-06
Sample Matrix:	Soil	Date Extracted:	02-14-06
Preservative:	Cool	Date Analyzed:	02-15-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Schneider GC C 1 Blow Pit.

Analyst P. Organia

May Bull
Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	5-Point Composite @ 6'	Date Reported:	02-15-06
Laboratory Number:	36230	Date Sampled:	02-14-06
Chain of Custody:	15551	Date Received:	02-14-06
Sample Matrix:	Soil	Date Analyzed:	02-15-06
Preservative:	Cool	Date Extracted:	02-14-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	ND	1.8	
Toluene	ND	1.7	
Ethylbenzene	3.9	1.5	
p,m-Xylene	19.7	2.2	
o-Xylene	5.4	1.0	
Total BTEX	29.0		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99.0 %
	1,4-difluorobenzene	99.0 %
	Bromochlorobenzene	99.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Schneider GC C 1 Blow Pit.

Analyst

Review



Chloride

Project #: 94034-010 Client: Blagg / BP Sample ID: 5-Point Composite @ 6' Date Reported: 02-15-06 02-14-06 Lab ID#: 36230 Date Sampled: Date Received: 02-14-06 Sample Matrix: Soil Preservative: Cool Date Analyzed: 02-15-06 Condition: Cool and Intact Chain of Custody: 15551

Parameter Concentration (mg/Kg)

Total Chloride 2.9

Reference: Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Schneider GC C 1 Blow Pit.

Revie

CHAIN OF CUSTODY RECORD

Client / Project Name	Project Location	THE STATE OF THE S	- ALL P. 1977.			ANALV	CIC / DAD	AMETERS				7
BLAGG/BP	Schneider G	CCI				ANALI	oio / ran	AIVIETENS				
BLAGG/BP Sampler:	Client No.		ers	12	+_				Rei	marks		
	94034-01		No. of Containers	70	122	1						
Sample No./ Sample Sample Identification Date Time	Lab Number	Sample Matrix	2 5	TX	D C	8						
5-Pont Coupus & 2/14/00 1231	36230 5	SOIL	1	ン	بز	×		Be	000	Pi	7	
			1 -									
		-	<u> </u>									
				-								
					:		_					
									T		1 -	
Relinquished by: (Signature)	Date 2/14/0	Time Rece	eived by:	(Signatu	re)				2/14	ate		ime { <i>'{</i> -/
Relinquished by: (Signature)	7 (1/6)	Rece	eived by:	(Signatu	re)					. (• •		
Relinquished by: (Signature)		Rece	eived by:	(Signatu	re)							
			,		, 		···	1				
	En	VIROTE	CH		\hat{J} .			Sam	ple Re	eceipt	т	
			MPAZ S	62070						Υ	N	N/A
	Farı	5796 U.S. Hig nington, New I						Received Inta	act	*Accessory		
	7 411	(505) 632-		2. 10	•			Cool - Ice/Blue	Ice	*200.0		



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC		Project #:		N/A
Sample ID:	02-15-06 QA/0	QC	Date Reported:		02-15-06
Laboratory Number:	36224		Date Sampled:		N/A
Sample Matrix:	Methylene Chlor	ride	Date Received:		N/A
Preservative:	N/A		Date Analyzed:		02-15-06
Condition:	N/A		Analysis Reques	ted:	TPH
	I-Cal Date	- I-cal RF:	C-Cal RF:	% Difference	Accept Rang
Gasoline Range C5 - C10	02-04-05	1.0019E+003	1.0029E+003	0.10%	0 - 15%
Diesel Range C10 - C28	02-04-05	1.0075E+003	1.0095E+003	0.20%	0 - 15%
Blank Conc. (mg/L - mg/k		Concentration		Detection Lim	nit
					ņit
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10		Concentration		Detection Lim	nit
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10 Diesel Range C10 - C28	(g)] } & & & & & & & & & & & & & & & & & &	Concentration ND ND		Detection Lim 0.2 0.1	ņit
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10 Diesel Range C10 - C28	(g)] } & & & & & & & & & & & & & & & & & &	Concentration		Detection Lim	nit
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10 Diesel Range C10 - C28 Total Petroleum Hydrocarbons	(g)	Concentration ND ND		Detection Lim 0.2 0.1 0.2	
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10 Diesel Range C10 - C28 Total Petroleum Hydrocarbons Duplicate Conc. (mg/Kg)	(g)	Concentration ND ND ND ND	a single	Detection Lim 0.2 0.1 0.2	
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10 Diesel Range C10 - C28 Total Petroleum Hydrocarbons Duplicate Conc. (mg/Kg) Gasoline Range C5 - C10	s Sample	Concentration ND ND ND ND Duplicate	% Difference	Detection Lim 0.2 0.1 0.2 Accept Range	
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10 Diesel Range C10 - C28 Total Petroleum Hydrocarbons Duplicate Conc. (mg/Kg) Gasoline Range C5 - C10 Diesel Range C10 - C28	s Sample 13.0	Concentration ND ND ND Duplicate	% Difference 0.8%	Detection Lim 0.2 0.1 0.2 Accept Range 0 - 30%	
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10 Diesel Range C10 - C28 Total Petroleum Hydrocarbons Duplicate Conc. (mg/Kg) Gasoline Range C5 - C10 Diesel Range C10 - C28 Spike Conc. (mg/Kg)	(g) s Sample 13.0 20.8	Concentration ND ND ND Duplicate 13.1 20.6	% Difference 0.8% 1.0%	Detection Lim 0.2 0.1 0.2 Accept Range 0 - 30% 0 - 30%	

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments: QA/QC for Samples 36224 - 36225, 36228 - 36231.

May Buce

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	F	Project #:		N/A
Sample ID:	02-15-BTEX QA/Q		Date Reported:		02-15-06
Laboratory Number	36224		Date Sampled:		N/A
Sample Matrix:	Soil		Date Received:		N/A
Preservative:	N/A		Date Analyzed:		02-15-06
Condition:	N/A	Δ	Analysis:		BTEX
Calibration and Detection Limits (ug/L)	I-Cal RE	C-Cal RF: Accept. Rang	%Diff. e 0 - 15%	Blank Conc	Detect.
Benzene	2 4473E+007	2 4522E+007	0.2%	ND	0.2
Toluene	8.4649E+006	8.4818E+006	0.2%	ND	0.2
Ethylbenzene	1.1093E+007	1.1115E+007	0.2%	ND	0.2
p,m-Xylene	2.8891E+007	2.8949E+007	0.2%	ND	0.2
o-Xylene	1.1900E+007	1.1924E+007	0.2%	ND	0.1
Duplicate Conc. (ug/Kg)	Sample	Duplicate		Accept Range	alone 3 1986 St. 1 at 1
Duplicate Conc. (ug/Kg) Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene	Sample ND 157 177 1,300 678	Duplicate ND 156 176 1,290 677	%Diff	Accept Range 0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Toluene Ethylbenzene p,m-Xylene	ND 157 177 1,300	ND 156 176 1,290 677	0.0% 0.1% 0.5% 0.8%	0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene	ND 157 177 1,300 678	ND 156 176 1,290 677	0.0% 0.1% 0.5% 0.8% 0.1%	0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene	ND 157 177 1,300 678	ND 156 176 1,290 677	0.0% 0.1% 0.5% 0.8% 0.1%	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg)	ND 157 177 1,300 678	ND 156 176 1,290 677	0.0% 0.1% 0.5% 0.8% 0.1% Spiked Sample	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg)	ND 157 177 1,300 678 Sample	ND 156 176 1,290 677 Amount Spiked	0.0% 0.1% 0.5% 0.8% 0.1% Spiked Sample 49.9 206	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% %Recovery 99.8%	1.8 1.7 1.5 2.2 1.0 Accept Range 39 - 150 46 - 148

ND - Parameter not detected at the stated detection limit.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 36224 - 36225, 36228 - 36231.

Analyst

Review