Submit 3 Copies To Appropriate District	State of New Mexico			Form C-103
Office District I	Energy, Minerals and Natural Resources			vised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240			WELL API NO. 30-039-27273	
District II 811 South First, Artesia, NM 87210	OIL CONSERVATION DIVISION		5. Indicate Type of Lease	
District III	2040 South Pacheco		I	EE 🗆
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505762720			
2040 South Pacheco, Santa Fe, NM 87505		Des A Com	6. State Oil & Gas Lease LG 898	No.
SUNDRY NOTICES AND REPORTS ON WELLS 2002 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) State Bancos				
1. Type of Well: Oil Well Gas Well X	Other			
2. Name of Operator	Other	10. 30.	8. Well No.	
Energen Resources Corporation	n n	"KG//IIII Jahr	100\$	
3. Address of Operator			9. Pool name or Wildcat	
2198 Bloomfield Highway, Far 4. Well Location	mington. NM 87401		Basin Fruitland Coal	
Unit Letter	720 feet from the N	lorth line and	1180 feet from the_	West line
Section 32	Township 32N	Range 05W	NMPM Cou	nty Rio Arriba
	10. Elevation (Show whether		tc.)	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data				
	** *	· ·	-	
NOTICE OF INT			SEQUENT REPORT	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	L. ALI	ERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILL	ABA	G AND
PULL OR ALTER CASING L.	MULTIPLE L. COMPLETION	CASING TEST AND CEMENT JOB		
OTHER:		OTHER: set casi	ng	X
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
09/22/03 Ran 76 jts. 7" 23# J-55 ST&C casing, set @ 3391'. RU BJ Services. Cement with 415 sks 65/35 Class C poz, 3% CaCl2, 1/4#/sk flocele, 10#/sk gilsonite, 8% bentonite, 0.4% sodium metasilicate followed by 100 sks Class C, 1% CaCl2, 1/4#/sk flocele, 10#/sk gilsonite (1006 cu.ft.). Plug down @ 3:15 pm on 09/22/03. Circulate 12 bbls cement to surface. RD BJ Services. WOC. NU BOP. Test casing & BOP to 1200 psi-ok.				
			•	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE VICK DO	making TI	TLE Production Assi	istant DATE	09/25/03
Type or print name Vicki Donaghey	, U O		Talanhana Na	505-325-6800
	,	DEPUTY AN .	Telephone No.	303-323-0000
(This space for State use)	//	ML & GAS INS	PECTOR nier OF-) () () () () ()
APPROVED BY Conditions of approval, if any:	Т	TTLE	PECTOR, DIST. (** DATE!	* × 5 2003