District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico **Energy Minerals and Natural Resources**

For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe

Date: AUG 0 9 2007

Form C-144

June 1, 2004

<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

Jeff Blagg - P.E. # 11607

Deputy Oil & Gas Inspector, District #3

PrintedName/Title

Printed Name/Title

regulations.

Approval

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

	de Tank Registration or Closur	
Is pit or below-grade tan	k covered by a "general plan"? Yes 🛛 No	
Type of action: Registration of a pit of	r below-grade tank 📋 Closure of a pit or below-grad	te tank 🔀
Operator: BP AMERICA PROD. CO.	Telephone: (505)-326-9200 e-mai	l address:
Address 200 ENERGY COURT, FARMINGTON.	-	
Facility or well name: ELLIOTT GC C #1		tr G Sec 9 T 30N R 9W
County: SAN JUAN Latitude 36.82848 Longitude 10		vner Federal ⊠ State ☐ Private ☐ Indian ☐
<u>Pit</u>	Below-grade tank	RCVD APR5'07
Type: Drilling ☐ Production ☒ Disposal ☐ SEPARATOR	Volume:bbl_Type-of-fluid:	OIL CONS. DIV.
Workover ☐ Emergency ☐	Construction material:	DIST. 3
Lined Unlined STEEL TANK	Double-walled, with leak of tection? Yes I If nt.	explain why not.
Liner type: Synthetic Thicknessmil Clay		
Pit Volumebbl		
Double to a second district of the second	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or more	(0 points)
	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)
water source, or less than 1000 feet from all other water sources.)		(v positio)
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) attach a diagram of the facility showing the pit's	relationship to other equipment and tanks. (2) Indicate	e disposal location: (check the onsite box if
your are burying in place) onsite 🛛 offsite 🔲 If offsite, name of facility	(3) Attach a general de	escription of remedial action taken including
remediation start date and end date. (4) Groundwater encountered: No 🛛 Y		
Attach soil sample results and a diagram of sample locations and excavations		1
Additional Comments: PIT LOCATED APPROXIMATELY		I. HFAD
PIT EXCAVATION: WIDTH N/Aft., LENGTH		
PIT REMEDIATION: CLOSE AS IS: ⊠, LANDFARM: □, CO	***************************************	olain)
Cubic vards: N/A	(,
STEEL TANK TO BE REPLACED.		
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guidelines.		
Date:08/7/06		

Signature

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or

		30042	77/10	<u> </u>	000101101	
0 D		GG ENGI		•	LOCATION NO	B1788
CLIENT. BP		87, BLO (505) 632), NM 8741	COCR NO	14640
FIELD REPO	RT: PIT CL	OSURE	VERIF	ICATION	PAGE No:	/_ of/_
LOCATION: NAME. EL					DATE STARTED	8
	9 TWP: 302 RN			*	DATE FINISHED ENVIRONMENTAL	
QTR/FOOTAGE: 1650 EXCAVATION APP	BOX NO ET			, , , , , , , , , , , , , , , , , , ,		
DISPOSAL FACILITY:	02-5					i i
_	6E-BLM				-	
FIELD NOTES & RE					83E FROM	
DEPTH TO GROUNDWATER						
NMOCD RANKING SCORE.			-			
SOIL AND EXCAV			,	OVM CALIB. RE	AD = 51.7 ppn	
				TIME: 11:05	S= <u>/ 00</u> ppm and/pm DATE	8/1/06
SOIL TYPE. SAND / SILT						
COHESION (ALL OTHERS)	YELL 320WN TO	COHESIVE / COI	<u>7</u> HESIVE / HIGHLY	COHESIVE		
CONSISTENCY (NON COHES PLASTICITY (CLAYS) NON F				/ LIICHI V DI ACTIC		
DENSITY (COHESIVE CLAYS				HIGHLY PLASTIC		CLOSED
MOISTURE: DRY/SLIGHTLY DISCOLORATION/STAINING	MOIST MOIST / WET / SA	TURATED / SUPER	R SATURATED	a= / a	, \ (200	
HC ODOR DETECTED: YES	NO EXPLANATION - EN	TIRE TEST A	19LE + pl	n JAMPLE.	BELOW GWD	<u> </u>
SAMPLE TYPE: GRAB COM ADDITIONAL COMMENTS _	IPOSITE - # OF PTS.		-		STEEL TRNY	#5 8E
_	REPLACED + WITH	pled in s	FAME LOCA	TION. INSTRU	CTED OPERATE	r ro
<u></u>	DILUTE LATERATE TOIL		このに をメアラヘブ LD 418.1 CALC		ETLEAVE W	PLACE.
SCALE SAM	IP. TIME SAMP. ID	LAB NO.	WEIGHT (g)		ILUTION READING	G CALC (ppm)
i de la companya de l			(8)			(
0 FT						
PIT PERI	METER ♠N	1 0			PIT PROFI	
[5]	P. Di		VM DING		ENCOUNTERED	
Eompr	8.6.	SAMPLE	FIELD HEADSPACE (ppm)	7/13	20 DN CO	En/1021
)	1@ 9	3,050			•
	15	2 @ 3 @				
		4 @ 5 @				
5	1. 6 15					
70	AR			701	APPLICAR	こしモ
70 (
MENT MENT	/	IARCA	AMPLES			
T. H.	tokmell	SAMPLE AN	ALYSIS TIME			
В.Т.	, between tralific	Deg TAH	(80158) 1058 (80213) 11			
j	T. B .~5' B. C .		-0'51 DE "	_		
P.D. = PIT DEPRESSION; B.G. = T.H. = TEST HOLE; ~ = APPROX	BELOW GRADE; B = BELOW	ÇUA	535-0)			
TRAVEL NOTES:	- 1 1 5/	~~?\\		21.1	<u> </u>	



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 9'	Date Reported:	08-03-06
Laboratory Number:	38031	Date Sampled:	08-01-06
Chain of Custody No:	14640	Date Received:	08-02-06
Sample Matrix:	Soil	Date Extracted:	08-02-06
Preservative:	Cool	Date Analyzed:	08-03-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	726	0.2
Diesel Range (C10 - C28)	515	0.1
Total Petroleum Hydrocarbons	1,240	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Elliott GC C #1

Separator Pit

Grab Sample

Analyst

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 9'	Date Reported:	08-03-06
Laboratory Number:	38031	Date Sampled:	08-01-06
Chain of Custody:	14640	Date Received:	08-02-06
Sample Matrix:	Soil	Date Analyzed:	08-03-06
Preservative:	Cool	Date Extracted:	08-02-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

		Det.	
	Concentration	Limit	
Parameter	(ug/Kg)	(ug/Kg)	
Benzene	38.6	1.8	
Toluene	316	1.7	
Ethylbenzene	2,710	1.5	
p,m-Xylene	8,230	2.2	
o-Xylene	2,610	1.0	
Total BTEX	13,900		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99.0 %
	1,4-difluorobenzene	99.0 %
	Bromochlorobenzene	99.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Elliott GC C #1 Separator Pit Grab Sample

Reme Warll



Chloride

Blagg / BP Project #: 94034-010 Client: Sample ID: 1@9' Date Reported: 08-03-06 38031 Date Sampled: 08-01-06 Lab ID#: Date Received: 08-02-06 Sample Matrix: Soil Cool Date Analyzed: 08-03-06 Preservative: Condition: Cool and Intact Chain of Custody: 14640

Parameter Concentration (mg/Kg)

Total Chloride 20.0

Reference: Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Elliott GC C #1 Separator Pit Grab Sample

Slend Warll Bariew

CHAIN OF CUSTODY RECORD

Client / Project Name/	P.3	and the second s	Project Location						ANCESSA MANTENIA WAS COST. MA	AN	ALYSIS / PAR	AMETERS	Burrens managadilina (O) (D) (D) (M) (M)	and a show on an	DOV. Over Like Street let	** ***********************************
02966 /BI	· ·		ELLIOT 6	ic c	HI					· · · · · · · · · · · · · · · · · · ·						
Sampler:			Client No.				S	.600		MEX	L.		Remar	ks		
·······		1	74034-01	10			No. of ontainer	JIM.		BOLK)	E.	Par	524FD	Co	0/	مو مو
Sample No./ Identification	Sample Date	Sample Time	Lab Number		Sample Matrix		ž 5(7PH (3015B)		(30214)	CHERICE	GRAI	584ED 5741	n fr	J.	,
0 29	3/1/04	1058	38031	50	7/		1	√		1	/	SEPA	CATOR	والكم	7	
						, 										
																
Relinquished by: (Signatur The Lorent Relinquished by: (Signatur		· 		Date	Time で705	d	المعالمة	(Signatu	<u>C. (</u>	Lylin			Date		Tim <u>デる・</u>	
Relinquished by: (Signatu	(A)					Receiv	ed by:	(Signatu	re)	V						
Fielinguished by: (Signatui	re)					Receiv	ed by:	(Signatu	re)							
				=nv	IRO	TEC		n				Sam	ple Recei	ot		
													Υ	N	J	N/A
					796 U.S ngton, N							Received Inta	act -			
	apa a mandapakka laka SV (ka laka pana maka ana mama			r Castill	(505)			J, 101				Cool - Ice/Blue	Ice			



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC		Project #:		N/A
Sample ID:	08-03-06 QA/	QC	Date Reported:		08-03-06
Laboratory Number:	38031		Date Sampled:		N/A
Sample Matrix:	Methylene Chlo	ride	Date Received:		N/A
Preservative:	N/A		Date Analyzed:		08-03-06
Condition:	N/A		Analysis Request	ted:	TPH
	- I-Cal Date	J-Cal RF:	C-Cal RF:	% Difference	Accept Range
Gasoline Range C5 - C10	07-11-05	9.9873E+002	9.9973E+002	0.10%	0 - 15%
Diesel Range C10 - C28	07-11-05	1.0009E+003	1.0029E+003	0.20%	0 - 15%
Brando - Tanan Tanan	Dari etalo dari.	77 - 28 6 7 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1		Detection Lim	6.e.(
Blank Conc. (mg/L - mg/Kg)		Concentration	. Gradie Stad Stad Stad	TABLES - SAT .	III.
Gasoline Range C5 - C10		ND ND		0.2	
Diesel Range C10 - C28		ND ND		0.1 0.2	
Total Petroleum Hydrocarbons		MD		0.2	
Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Difference	Accept. Rang	**************************************
Gasoline Range C5 - C10	726	722	0.6%	0 - 30%	
Diesel Range C10 - C28	515	512	0.6%	0 - 30%	
Spike Conc. (mg/Kg)	Sample	Spike Added	Spike Result	% Recovery	Accept Range
Gasoline Range C5 - C10	726	250	975	99.9%	75 - 125%
Diesel Range C10 - C28	515	250	763	99.8%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 38031 - 38033, 38036 - 38037

Analyst

Review

luh Warth



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	F	Project #:	I	N/A
Sample ID:	08-03-BTEX QA/Q	C D	Date Reported:	!	08-03-06
Laboratory Number:	38031		Date Sampled:		N/A
Sample Matrix:	Soil		Date Received:		N/A
Preservative:	N/A		Date Analyzed:	+	08-03-06
Condition:	N/A	P	Analysis:		BTEX
Calibration and Detection Limits (ug/L)	I-Cal RF:	C-Cal RF: Accept. Rang	%Diff. e 0 - 15%	Blank Conc	Detect Limit
Benzene	7,2380E+007	7.2525E+007	0.2%	ND	0.2
Toluene	1.0207E+008	1.0227E+008	0.2%	ND	0.2
Ethylbenzene	4.2243E+007	4.2328E+007	0.2%	ND	0.2
p,m-Xylene	4.2243E+007 1.7946E+008	1.7982E+008	0.2%	ND	0.2
p,m-xylene p-Xylene	1.7946E+008	1.0345E+008	0.2%	ND	0.1
Benzene Toluene Ethylbenzene	38.6 316 2,710	Duplicate 38.6 315 2,700	0.0% 0.3% 0.4%	0 - 30% 0 - 30% 0 - 30%	Detect Limit 1.8 1.7 1.5
Duplicate Conc. (ug/Kg) Benzene Toluene Ethylbenzene p,m-Xylene	38.6 316 2,710 8,230	38.6 315 2,700 8,220	0.0% 0.3% 0.4% 0.1%	0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2
Benzene Toluene Ethylbenzene	38.6 316 2,710	38.6 315 2,700 8,220 2,600	0.0% 0.3% 0.4% 0.1% 0.4%	0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene	38.6 316 2,710 8,230 2,610	38.6 315 2,700 8,220 2,600	0.0% 0.3% 0.4% 0.1% 0.4%	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg)	38.6 316 2,710 8,230 2,610	38.6 315 2,700 8,220 2,600	0.0% 0.3% 0.4% 0.1% 0.4%	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Foluene Ethylbenzene o,m-Xylene o-Xylene Spike Conc. (ug/Kg)	38.6 316 2,710 8,230 2,610 Sample 38.6 316	38.6 315 2,700 8,220 2,600 Amount Spiked 50.0 50.0	0.0% 0.3% 0.4% 0.1% 0.4% Spiked Sample 88.5 365	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery 99.9% 99.8%	1.8 1.7 1.5 2.2 1.0 Accept Range
Benzene Foluene Ethylbenzene o,m-Xylene o-Xylene Benzene Foluene Ethylbenzene	38.6 316 2,710 8,230 2,610 38.6 316 2,710	38.6 315 2,700 8,220 2,600 Amount Spiked 50.0 50.0 50.0	0.0% 0.3% 0.4% 0.1% 0.4% Spiked Sample 88.5 365 2,750	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery 99.9% 99.8% 99.6%	1.8 1.7 1.5 2.2 1.0 Accept Range 39 - 150 46 - 148 32 - 160
Benzene Toluene Ethylbenzene p,m-Xylene p-Xylene Spike Conc. (ug/Kg)	38.6 316 2,710 8,230 2,610 Sample 38.6 316	38.6 315 2,700 8,220 2,600 Amount Spiked 50.0 50.0	0.0% 0.3% 0.4% 0.1% 0.4% Spiked Sample 88.5 365	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery 99.9% 99.8%	1.8 1.7 1.5 2.2 1.0 Accept Range

ND - Parameter not detected at the stated detection limit.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 38031, 38035

Analyst

Review