1 : 1 District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S St Francis Dr , Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe

Form C-144 June 1, 2004

Pit or Bel	<u>low-Grade</u>	Tank R	egistration	or Closure
Is pit or below	v-grade tank co	vered by a	"general plan"	'? Yes 🔀 No 🗌

Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀			
Occupies DB America Production Company Telephon	e (505)226 0200 e mail addres	c.	
Operator BP America Production Company Telephon Address 200 Energy Ct, Farmington, NM 87401	c-man addres		
Facility or well name CALLOW #\2E API #: 30	0045 24796 W/ or Otr	Otr A Sec 33 T 79 NR 13 W	
		NAD 1927 ☐ 1983 🔀	
Surface Owner Federal State Private Indian			
Pit	Below-grade tank		
Type Drilling Production Disposal	Volumebbl Type of fluid. A	/	
Workover ☐ Emergency ☐	Construction material:		
Lined Unlined	Double-walled, with leak detection? Ye	If no, explain why not	
Liner type Synthetic [Thicknessmil Clay [V / \	
Pit Volumebbl	/	'	
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)	
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)	
Then water elevation of ground water.	100 feet or more	(0 points)	
Wellhead protection area. (Less than 200 feet from a private domestic	Yes	(20 points)	
water source, or less than 1000 feet from all other water sources.)	No	(0 points)	
water source, or ress than 1000 feet from an other water sources.	Less than 200 feet	(20 points)	
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10)	
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(10 points)	
	Ranking Score (Total Points)	8	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	relationship to other equipment and tanks	i. (2) Indicate disposal location. (check the onsite box if	
your are burying in place) onsite 🛛 offsite 🗌 If offsite, name of facility_	(3) Attach	a general description of remedial action taken including	
remediation start date and end date (4) Groundwater encountered. No 🔀 Y	es 🗌 If yes, show depth below ground s	urfaceft and attach sample results	
(5) Attach soil sample results and a diagram of sample locations and excavat	ions.		
Additional Comments			
See Attached Documentation			
		RCVD JUNS'07	
	OIL CONS. DIV.		
		DIST. 3	
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. I further ce s 🔀, a general permit 🔲, or an (attach	rtily that the above-described pit or below-grade lank ed) alternative OCD-approved plan.	
Date	111.00	36	
Printed Name/Title Jeffrey C Blagg, Agent Signature July C - Slegy			
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations			
D		/	
Approval Deputy Oil & Gas Inspecior, Printed Name/Title District #3 Signature Date AUG 1 0 2007			
Printed Name/Title	Signature Deflection	Date: AUG 1 0 2007	

BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 FIELD REPORT: CLOSURE VERIFICATION PAGE NO			
FIELD REPORT: CLOSURE VERIFICATION PAGE NO. 1 of 1 LOCATION: NAME CALOW WELL #. 12E PIT ABAM. DATE STARTED 1/11/02 QUAD/UNIT: A SEC: 33 TWP: 29N RNG: 13W PM: NM CNTY. SJ ST: NM QTR/FOOTAGE: 790 N / 1120 E NEW CONTRACTOR FUNT SPECIALIST DISPOSAL FACILITY: NN SPECIALIST LAND USE: RAME - BAM LEASE: NM 0/68126 FORMATION: OK FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 144 FT 550W FROM WELL #E-D DEPTH TO GROUNDVATER: NOO NEAREST WATER SOURCE: NOO NEAREST SURFACE WATER: NOO NEAREST WATER SOURCE: NEAREST SURFACE WATER: NOO NEAREST SURFACE WATE			
FIELD REPORT: CLOSURE VERIFICATION PAGE NO. 1 of 1 LOCATION: NAME CALLOW WELL #. 12E PIT ABAN. QUAD/UNIT: A SEC: 33 TWP: 29N RNG: 13W PM: NM CNTY. SJ ST: NM QTR/FOOTAGE: 790W 1120E NAME CONTRACTOR FUNT SPECIALIST ENVIRONMENTAL SPECIALIST WEXCAVATION APPROX. 15 FT. x 13 FT. x 1 FT DEEP. CUBIC YARDAGE 5-10 DISPOSAL FACILITY: 2N-SITE REMEDIATION METHOD: DILLITED PRESENTED LAND USE: NAME - BAN LEASE: NM 0468136 FORMATION: OK FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 144 FT \$50W FROM WELL-E-D DEPTH TO GROUNDWATER: 7100 NEAREST WATER SOURCE: 71000 NEAREST SURFACE VATER: 71000 NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPM CHECK ONE SOIL AND EXCAVATION DESCRIPTION: TIME: 8:20 @D/PM DATE: 11102 FIBERGLASS TANK INSTALLED TIME: 8:20 @D/PM DATE: 11102 FIBERGLASS TANK INSTALLED SOIL TYPE: SAND/ SILTY SAND / SILTY SAND / SILTY SILTY CLAY / CLAY / GRAVEL / OTHER BEDROX (SANDSTONE) COHESION (ALL OTHERS): (NDN COHESIVE) SLIGHTLY COHESIVE / HIGHLY COHESIVE			
QUAD/UNIT: A SEC: 33 TWP: 29N RNG: 13W PM: NM CNTY. SJ ST: NM QTR/FOOTAGE: 790 N/1120 E NEW CONTRACTOR FLINT EXCAVATION APPROX. JS FT. x J3 FT. x L FT DEEP. CUBIC YARDAGE 5-10 DISPOSAL FACILITY: 0N-SITE REMEDIATION METHOD: DIGNITED PRESENTED LAND USE: NM O 168136 FORMATION: OK FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 144 FT \$50W FROM WELL-12-15 DEPTH TO GROUNDWATER: 7100 NEAREST WATER SOURCE: 71000 NEAREST SURFACE WATER: 71000 NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPM CHECK DNE SOIL AND EXCAVATION DESCRIPTION: TIME: 8:20 CP/pm DATE: 1/11/02 FIBERGLASS TANK INSTALLED SOIL TYPE: SAND/ SILTY SAND / SILTY SAND / SILTY CLAY / CLAY / GRAVEL / OTHER BEDRAIR (SANDSTONE) SOIL COLOR: DIK, YELL-18-1000			
QUAD/UNIT: A SEC: 33 TWP: 29~ RNG: 13~ PM: ~M CNTY. 5] ST. ~M QTR/FOOTAGE: 790 / 1120 E			
QUAD/UNIT: A SEC: 33 TWP: 29N RNG: 13W PM: 29M CNTY. 5] ST-20M DTR/FOOTAGE: 790N/1120 E New Contractor F-INT SPECIALIST NV EXCAVATION APPROX 15			
EXCAVATION APPROX. IS FT. x 13 FT. x 1 FT DEEP. CUBIC YARDAGE 5-10 DISPOSAL FACILITY:			
DISPOSAL FACILITY: DISPOSAL FACILITY: LEASE: NM 0 468136 FORMATION: OK FIELD NOTES & REMARKS: DEPTH 10 GROUNDWATER: NMOCD RANKING SCORE: NMOCD THE CLOSURE STD: DVM CALIB. READ. DVM CALIB. GAS = 100 ppm DVM CALIB. G			
LEASE: NM 0 46 81 36 FORMATION OK FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 144 FT \$50W FROM WELL-EAD DEPTH TO GROUNDWATER: 7100 NEAREST WATER SOURCE: 7000 NEAREST SURFACE WATER: 7000 NEARE			
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 144 FT \$50W FROM WELL-EAD DEPTH TO GROUNDWATER: 7100 NEAREST WATER SOURCE: 7000 NEAREST SURFACE WATER: 71000 NEAREST WATER SOURCE: 7000 PPM CHECK ONE SOIL AND EXCAVATION DVM CALIB. GAS = 100 PPM RF = 0.52 STEEL TANK INSTALLED TIME: 8:20 CP/Pm DATE: 1/11/02 FIBERGLASS TANK INSTALLED SOIL TYPE: SAND/ SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER BEDROK (SADOSTONE) SOIL COLOR: DIK YELL GROWN SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE			
DESCRIPTION: SOIL TYPE: SAND/ SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER BEDROIR (SANDSTONE) SOIL COLOR: DESCRIPTION: NEAREST WATER SOURCE: NEAREST SURFACE WATER: NEAREST SURFACE W			
NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPM SOIL AND EXCAVATION DESCRIPTION: SOIL TYPE: SAND/ SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER BEDROCK (SADOSTONE) SOIL COLOR: DIK, YELL BROWN SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE			
DESCRIPTION: DVM CALIB. GAS = 100 ppm RF = 0.52 TIME: 8:20 @P/pm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TIME: 8:20 @P/pm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm			
DESCRIPTION: DVM CALIB. GAS = 100 ppm RF = 0.52 TIME: 8:20 @P/pm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TIME: 8:20 @P/pm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm RF = 0.52 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm DATE: 1/11/02 FIBERGLASS TANK INSTALLED TOWN CALIB. GAS = 1000 ppm			
DESCRIPTION: TIME: 8:20 @P/pm DATE: //11/02 FIBERGLASS TANK INSTALLED SOIL TYPE: SAND / SILTY SAND / SILTY / SILTY CLAY / CLAY / GRAVEL / OTHER BEDROCK (SADOSTONE) SOIL COLOR: DIK. YELL: BROWN LT. GRAY - BEDROCK COHESION (ALL OTHERS): (NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE			
SOIL TYPE: SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER BEDROCK (SANDSTONE) SOIL COLOR: DIK. YELL BROWN LT. GRAY - BEDROCK COHESION (ALL OTHERS): (NON COHESIVE) / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE			
CONSISTENCY (NON COHESIVE SOILS): COOSD / CIRM / DENSE / VERY DENSE			
PLASTICITY (CLAYS) NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS) SOFT / FIRM / STIFF / VERY STIFF / HARD (LOSED)			
MOISTURE DRY / SLIGHTLY MOISD / MOISD / WET / SATURATED / SUPER SATURATED			
DISCOLORATION/STAINING OBSERVED: (YES) NO EXPLANATION - ENTIRE TEST HOLE INTERVAL (APPROX I') HC ODOR DETECTED (YES) NO EXPLANATION - ENTIRE TEST HOLE INTERVAL OF OWN SAMPLE.			
SAMPLE TYPE: GRAD/ COMPOSITE - # OF PTS			
ADDITIONAL COMMENTS: BEORDCK - 5 UGHTLY FRIABLE, UERY HARD. INSTRUCTED OPERATOR TO DILITE & AEROTE			
BEDROCK SOIL ABOVE BEDROCK & CONTAIN WITHIN PIT AREA.			
FIELD 418.1 CALCULATIONS			
SCALE SAMP. TIME SAMPLE I.D. LAB No: WEIGHT (g) ML. FREON DILUTION READING CALC ppm			
O FT			
OVM			
LP RESULTS SLOPE			
ORECT. SAMPLE FIELD HEADSPACE ID PID (opm)			
1 @ 3' 215 2 @			
BERM 3 @			
5 @			

PIT PERIMETER *A	<u></u>	PIT PROFILE	
LIP TO WELL HEAD	OVM RESULTS		
SLOPE ORECT.	SAMPLE FIELD HEADSPACE PID (ppm)		
€	1 @ 3' Z\S	-	
	2 @		
BERM	3 @		
Belm	4 @		
	5 @		
[] / PROD.			
7 Q 13 (TACIK)		NOT APPLICABLE	
		-{	
		-	
15'			
	LAB SAMPLES	_	
	SAMPLE ANALYSIS TIME		
PD. , TH.	De 3' TPH (80158) 1310	<u>}</u>	
APPROX. Z' T.H.	" BTEX(80718) "	-	
B.G. BELLOW P.D.	(BOTH PRISED)	-	
P.D = PIT DEPRESSION; BG = BELOW GRADE	750		
TH = TEST HOLE		1	
TRAVEL NOTES: CALLOUT. [1002 - AFTER. ONSITE: 1/11/02 - MORN.			

revised: 08/17/01



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 3'	Date Reported:	01-14-02
Laboratory Number:	21788	Date Sampled:	01-11-02
Chain of Custody No:	8890	Date Received:	01-11-02
Sample Matrix:	Soil	Date Extracted:	01-14-02
Preservative:	Cool	Date Analyzed:	01-14-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	20.1	0.2
Diesel Range (C10 - C28)	128	0.1
Total Petroleum Hydrocarbons	148	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments: Callow #12E Abandoned Pit Grab Sample.

Analyst C. Copiner

Mistry Warters



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Place / PD	Decis et #	04004 040
Client.	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 3'	Date Reported:	01-14-02
Laboratory Number:	21788	Date Sampled:	01-11-02
Chain of Custody:	8890	Date Received:	01-11-02
Sample Matrix:	Soil	Date Analyzed:	01-14-02
Preservative:	Cool	Date Extracted:	01-14-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	5.8	1.8
Toluene	ND	1.7
Ethylbenzene	60.6	1.5
p,m-Xylene	144	2.2
o-Xylene	22.4	1.0
Total BTEX	233	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	96 %
	1,4-difluorobenzene	96 %
	Bromochlorobenzene	96 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Callow #12E Abandoned Pit Grab Sample.

Alexan C. aferen

(Mistin M Waeters