

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other In-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐		2007 AUG 27 PM 2:35	
b TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESVR ☐ Other ☐		RECEIVED 070 FARMINGTON NM	
2 NAME OF OPERATOR ConocoPhillips		7 UNIT AGREEMENT NAME San Juan 28-7 Unit	
3 ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700		8 FARM OR LEASE NAME, WELL NO San Juan 28-7 Unit #223F	
4 LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface Unit B (NWNE) 15' FNL, 2435' FEL At top prod. interval reported below Same as above At total depth Same as above		9 API WELL NO 30-039-27257	
14. PERMIT NO.		DATE ISSUED	
12 COUNTY OR PARISH Rio Arriba		13 STATE New Mexico	
15 DATE SPUDDED 3/7/07	16 DATE T.D. REACHED 3/27/07	17 DATE COMPL. (Ready to prod.) 8/22/07	18 ELEVATIONS (DF, RKB, RT, BR, ETC.) GL 6658' KB 6674'
19 ELEV CASINGHEAD			
20 TOTAL DEPTH, MD & TVD 7824'	21 PLUG, BACK T.D., MD & TVD 7818'	22 IF MULTIPLE COMPL., HOW MANY* 2	23 INTERVALS DRILLED BY yes
24 PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Blanco Mesa Verde 4976' - 5634'			25 WAS DIRECTIONAL SURVEY MADE No
26 TYPE ELECTRIC AND OTHER LOGS RUN Cement Bond Log/Gamma Ray Casing Collar			27. WAS WELL CORED No
28 CASING RECORD (Report all strings set in well)			
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE
9 5/8" H-40	32.3#	232'	12 1/4"
7" J-55	20#	3640'	8 3/4" 1125
4 1/2" J-55	11.6#	7821'	6 1/4"
29 LINER RECORD		30. TUBING RECORD	
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*
			SCREEN (MD)
			SIZE
			DEPTH SET (MD)
			PACKER SET (MD)
31 PERFORATION RECORD (Interval, size and number) @1SPF LMF 5510' - 5402' = 10 holes PLO 5634' - 5534' = 20 holes CH 5114' - 4976' = 18 holes UMF 5302' - 5160' = 11 holes		32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. 5402' - 5634' 60Q Slickfoam w/101686# 20/40 Brady Sand 4976' - 5302' pumped 15 bbls 15% HCL Acid, 60Q Slickfoam w/101641# 20/40 Brady Sand. Total N2=1145000SCF	
33. PRODUCTION DATE FIRST PRODUCTION SI W/O Facilities SI PRODUCTION METHOD (Flowing, gas lift, pumping-size and type of pump) Flowing WELL STATUS (Producing or shut-in) SI DATE OF TEST 8/20/07 HOURS TESTED 1 CHOKE SIZE 1/2" PROD'N FOR TEST PERIOD OIL-BBL 63.25 mcf GAS-MCF .25 bw WATER-BBL FLOW TUBING PRESS 575# CASING PRESSURE SI - 515# CALCULATED 24-HOUR RATE OIL-BBL 1518 mcf/d GAS-MCF 6 bwpd WATER-BBL 34 DISPOSITION OF GAS (Sold, used for fuel, vented, etc) To be sold TEST WITNESSED BY			
35. LIST OF ATTACHMENTS This will be a Basin Dakota/Mesa Verde well being DHC per order # 2513AZ			
36 I hereby certify that the foregoing and attached information is complete and correct as determined from all available records			

SIGNED Duane W. Monnet TITLE Regulatory Technician DATE 8/25/07

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD
8/25/07

AUG 28 2007

FARMINGTON FIELD OFFICE

NMOCD

Ojo Alamo	2513'	2636'	White, cr-gr ss.	Ojo Alamo	2513'
Kirtland	2636'	3070'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2636'
Fruitland	3070'	3348'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3070'
Pictured Cliffs	3348'	3516'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3348'
Lewis	3516'	3902'	Shale w/siltstone stringers	Lewis	3516'
Huerfanito Bentonite	3902'	4287'	White, waxy chalky bentonite	Huerfanito Bent.	3902'
Chacra	4287'	4883'	Gry fn grn silty, glauconitic sd stone w/drck gry shale	Chacra	4287'
Mesa Verde	4883'	5129'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	4883'
Menefee	5129'	5533'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5129'
Point Lookout	5533'	5880'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5533'
Mancos	5880'	6743'	Dark gry carb sh.	Mancos	5880'
Gallup	6743'	7501'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh	Gallup	6743'
La Ventana	XXXX	XXXX	Wt to lt buff to med grn sl carb bent	Greenhorn	7501'
Greenhorn	7501'	7573'	Highly calc gry sh w/thin lmst.	Graneros	7573'
Graneros	7573'	7608'	Dk gry shale, fossil & carb w/pyrite incl.	Dakota	7608'
Dakota	7608'		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks		