

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2007 AUG 13 PM 4:15

1. Type of Well  
GAS

RECEIVED  
BLM  
210 FARMINGTON NM

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit E (SWNW), 1700' FNL & 1155' FWL, Section 5, T30N, R9W, NMPM

5. Lease Number  
SF-078316D  
6. If Indian, All. or  
Tribe Name  
7. Unit Agreement Name

8. Well Name & Number

Woodriver 1B  
9. API Well No.

30-045-34092

10. Field and Pool

Basin DK/Blanco MC

11. County and State  
San Juan Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission

Type of Action

☐ Notice of Intent ☐ Abandonment ☐ Change of Plans  
☒ Subsequent Report ☐ Recompletion ☐ New Construction  
☐ Final Abandonment ☐ Plugging ☐ Non-Routine Fracturing  
☐ ☐ Casing Repair ☐ Water Shut off  
☐ ☐ Altering Casing ☐ Conversion to Injection

☒ Other - casing report

RCVD AUG 23 '07  
OIL CONS. DIV.

DIST. 3

**13. Describe Proposed or Completed Operations**

7/31/07 NU BOP. RIH w/8/34" bit. D/O cement & ahead to 3925' intermediate. Circ hole. RIH w/95jts 7" 23# L-80 LT & C casing Set @ 3919'. RU to cement. 8/5/07 Pumped pre-flush of 25 bbls gel H2O. Lead- pumped 419 sx(1094cf-194bbls) Class G Cement w/ 2 #/bbl Cemnet, .2% D46, 3% D79. Tail- pumped 236sx(300cf-53bbls) Type III Cement w/2 #/bbl Cemnet, 2% D20, 5 #/sx D24, 1% D46, .15% D65, 1% S-1. Dropped plug & displaced w/152 bbls FW. Bumped plug to 2115#. Circ 64 bbls to pit.

8/5/07 PT casing to 1500# 30/min - good test. RIH w/6 1/4" bit. D/O cement & ahead to 7870'(TD). TD reached on 8/10/07. Circ hole. RIH w/184 jts 4 1/2" 11.6# L-80 LT & C casing set @ 7866'. RU to cement. 8/10/07 pumped pre-flush of 10 bbls gel H2O/2 bbls FW. Pumped Scavenger 10 sx(30cf-5bbls) Premium Lite HS FM Cement w/6.25#/sx CD-32, .25 #/sx Cello-Flake, 1% FL-52, 1% LCM-1. Pumped 290 sx(574cf-102bbls) Premium Lite HS FM Cement w/6.25 #/sx CD-32, .25 #/sx Cello-Flakes, 1% FL-52, & 1% LCM-1. Dropped plug & displaced w/112 bbls FW. Bumped plug to 1500#. Plug down @ 03:15. WOC. ND. RR @ 09:15/

PT will be conducted by the completion rig. PT results & TOC will be shown on next report.

**14. I hereby certify that the foregoing is true and correct.**

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 8/13/07

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOCD

ACCEPTED FOR RECORD

AUG 20 2007

FARMINGTON FIELD OFFICE  
BY T. Salyers