submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells		y	
	2007 AUS 30 PM 2: 20	5.	Lease Number
	PEOUNED		NMSF-079029
1. Type of Well GAS	RECEIVED BLM	6.	If Indian, All. or Tribe Name
	210 FARMINGTON NM	-	
2. Name of Operator		7.	Unit Agreement Name San Juan 32-8 Unit
CONOCOPHILLIPS			
3. Address & Phone No. of Operator		 8.	Well Name & Number
PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	San Juan 32-8 Unit #39A API Well No.
4. Location of Well, Footage, Sec., T, R, M			30-045-34281
		10.	Field and Pool
Unit J (NWSE), 1415' FSL & 1894' FEL, Sec	e. 3, T31N, R8W, NMPM		
			Blanco Mesaverde
		11.	County and State San Juan Co., NM
12. CHECK APPROPRIATE BOX TO INDIC	ATE NATURE OF NOTICE, REPORT,	OTHER !	DATA
Type of Submission Type of Action Notice of Intent Abandonmer	the Change of Plans	<u>X</u>	Other - casing
X Subsequent Report Plugging	ion New Construction Non-Routine Fracturing		RCVD SEP 6 '07
Casing Rep	pair Water Shut off Casing Conversion to Injection	٠,	OIL CONS. DIV.
13. Describe Proposed or Completed Operation	ns		DIST_3
8/21/07 RIH w/8-3/4" bit & D/O cement & then formation 8/17/07. Anticipate loss circulation — reason for change Pumped 20 bbls mud clean II ahead of 385 sx (820 cf-14.4% SMS, .4% FL-52A. Tailed with 90 sx (124 cf - 22 bbls FW. Circ. 50 bbls cement to surface. Plug down @ Good test. 8/25/07 RIH w/6-1/4" bit & tagged cement @ 3136'. D & ran openhole logs from 3162' — 3900'. Circ. Hole. Regel & 2 bbls water, ahead of 226 sx (447 cf – 80 bbls) P plug and displaced w/97 bbls water w/25# sugar in first Will show casing PT and TOC on the next report. Com	e). Circ. Hole. RIH w/78 jts of 7", 20#, J-55 S' 46 bbls) Premium Lite FM cement w/3% CaCl, bbls) Type III w/1% CaCl, .25#/sx Celloflake,2 1500 hrs 8/24/07. RD BJ. WOC. 8/25/07 PT J-55? b/O cement and then formation to 6156' (TD). TRIH w/155 jts 4-1/2", 10.5#, £-80 LT&C and set remium Lite HS w/.25#/sx Celloflake, .3% CD-10 bbls. Bumped plug @ 859 hrs 8/28/07. RD	F&C casing 25#/sx Cell 2% FL-52A Casing to 2 Casing to 2 D was reac @ 6155* 32, 6.25#/sx	and set @ 3193'. RU to cement. loflake, 5#/sx LCM-1, 8% Bentonits. Dropped plug and displaced w/1250 psi/3 min. and 1800psi/30 min. hed 8/27/07. RU Schlumberger RU To cement. Pumped 10 bbls a LCM-1, 1% FL-52A. Dropped
14. I hereby certify that the foregoing is true as	nd correct.		
Signed Tamososimo 1	Title Regulatory T	<u>[echnician</u>	Date 8/30/07
(This space for Federal or State Office use)	Title	-	Data
APPROVED BY CONDITION OF APPROVAL, if any:	Title		Date
Little 18 U S C. Section 1001, makes it a crime for any person knowingly and willful the United States any false, fictitious or fraudulent statements or representations as t			ACCEPTED FOR RECORD