

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a TYPE OF WELL OIL WELL ☐ GAS WELL ☒ OTHER ☐ 210 FARMINGTON NM 2:19

b TYPE OF COMPLETION.

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESVR ☐

RECEIVED
SLM

2 NAME OF OPERATOR

ConocoPhillips

3 ADDRESS AND TELEPHONE NO

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4 LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface Unit K (NESW) 1900' FSL, 1930' FWL

At top prod. interval reported below Same as above

At total depth Same as above

14 PERMIT NO. DATE ISSUED

12. COUNTY OR PARISH

13. STATE

Rio Arriba

New Mexico

15 DATE SPUDDED 9/30/07

16. DATE T.D. REACHED 10/25/07

17 DATE COMPL. (Ready to prod) 8/27/07

18 ELEVATIONS (DF, RKB, RT, BR, ETC) GL 6491' KB 6507'

19 ELEV CASINGHEAD

20 TOTAL DEPTH, MD & TVD

8097'

21 PLUG, BACK T.D., MD & TVD

8029'

22. IF MULTIPLE COMPL. HOW MANY* 2

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

yes

24 PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesa Verde 5123' - 6042'

25. WAS DIRECTIONAL SURVEY MADE

No

26 TYPE ELECTRIC AND OTHER LOGS RUN

Cement Bond Log/Gamma Ray Casing Collar

27 WAS WELL CORED

No

28 CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB/FT	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8" H-40	32.3#	231'	12 1/4"	surface; 198sx (265 cf)	20 bbls
7" J-55	20#	3677'	8 3/4"	surface; 841sx (1697 cf)	20 bbls includes squeeze
4 1/2" N-80	11.6#	8032'	6 1/4"	TOC 2800'; 323sx (645 cf)	DV tool @ 2815'

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	7940'	

31 PERFORATION RECORD (Interval, size and number)

@2SPF
@1SPF
LMF 5620' - 5706'
PLO 5720' - 6042'
CH 5123' - 5453'
UMF 5476' - 5506'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

5620' - 6042'	60Q Slickfoam w/99260# 20/40 Brady Sand, tailed w/ 2340# 20/40 TLC. Total N2= 1112500 SCF.
5123' - 5506'	60Q Slickfoam w/101140# 20/40 Brady Sand, tailed in w/ 2340# 20/40 TLC. Total N2 = 1121700 SCF.

33 PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump)					WELL STATUS (Producing or shut-in)	
SI W/O Facilities		Flowing					SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO	
8/23/07	1	1/2"						
FLOW TUBING PRESS	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR)		
692#	500#		To be reported w/ First Delivery					

34 DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This will be a Basin Dakota/Blanco Mesa Verde well being DHC per order #2306AZ.

36 I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Mary J. Monahan

TITLE

Regulatory Technician

DATE

9/4/07

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD

SEP 10 2007

FARMINGTON FIELD OFFICE
BY *T. Salyers*

Ojo Alamo	2500'	2643'
Kirtland	2643'	3146'
Fruitland	3146'	3453'
Pictured Cliffs	3453'	3617'
Lewis	3617'	4195'
Huerfanito Bentonite	4195'	4594'
Chacra	4594'	5113'
Mesa Verde	5113'	5461'
Menefee	5461'	5716'
Point Lookout	5716'	6113'
Mancos	6113'	7013'
Gallup	7013'	7722'
Greenhorn	7722'	7778'
Graneros	7778'	7893'
Dakota	7893'	

White, cr-gr ss.
 Gry sh interbedded w/tight, gry, fine-gr ss.
 Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.
 Bn-Gry, fine grn, tight ss.
 Shale w/siltstone stringers
 White, waxy chalky bentonite
 Gry fn grn silty, glauconitic sd stone w/drak gry shale
 Light gry, med-fine gr ss, carb sh & coal
 Med-dark gry, fine gr ss, carb sh & coal
 Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation
 Dark gry carb sh.
 Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh
 Highly calc gry sh w/thin lmst.
 Dk gry shale, fossil & carb w/pyrite incl.
 Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks

Ojo Alamo	2500'
Kirtland	2643'
Fruitland	3146'
Pic.Cliffs	3453'
Lewis	3617'
Huerfanito Bent.	4195'
Chacra	4594'
Mesa Verde	5113'
Menefee	5461'
Point Lookout	5716'
Mancos	6113'
Gallup	7013'
Greenhorn	7722'
Graneros	7778'
Dakota	7893'

W-112336-111111
 111111

W-112336-111111

W-112336-111111