

30-045-20467

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SE Sec. 27 Twp 26 Rng 10

Name of Well/Wells or Pipeline Serviced HUERFANO UNIT #198

cps 988w

Elevation 6698' Completion Date 12/20/82 Total Depth 440' Land Type\* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used  
N/A

Depths & thickness of water zones with description of water when possible:  
Fresh, Clear, Salty, Sulphur, Etc. DRILLED OUT OF WATER ZONE AT 200'

Depths gas encountered: N/A

Type & amount of coke breeze used: 3000 lbs.

Depths anodes placed: 365', 355', 340', 330', 315', 305', 290', 280', 240', 220'

Depths vent pipes placed: 400'

Vent pipe perforations: 220'

Remarks: gb #2 FIRST HOLE CAVED AT 440' RECOVERED ANODES.

**RECEIVED**

**MAY 31 1991**

**OIL CON. D**

**DIST. 3**

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.

30-045-20467

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SE Sec. 27 Twp 26 Rng 10

Name of Well/Wells or Pipeline Serviced HUERFANO UNIT #198

cps 988w

Elevation 44 (\*) Completion Date 9/29/75 Total Depth 400' Land Type\* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 140'

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

Type & amount of coke breeze used: 3500 lbs. OIL CON. DIV

Depths anodes placed: 320', 310', 300', 290', 280', 270', 260', 250', 240', 230' DIST

Depths vent pipes placed: N/A

Vent pipe perforations: 210'

Remarks: qb #1

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.