Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR CEIVED BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Evoires March 31, 1993

	SUNDRY NOTICES AND	DEPORTS ON WELLS	5 Lease Designation and Serial No
Do not us		to deepen or reentry to realife rank exhaning	emeg: NMNM-99738
	Use "APPLICATION FOR P	ERMIT -" for such proposal mington Field Of	fire 6. If Indian, Allottee or Tribe Name
			
1 Type	SUBMIT IN T	TRIPLICATE	7 If Unit or CA, Agreement Designation
туре	e or vveii		/ If Onit of CA, Agreement Designation
	Oil Well X Gas Well	Other	
			8 Well Name and No
. 2. Name	e of Operator	OCDID (1634E9)	Symprony 24 7 20 # 450
ç	Synergy Operating, LLC	OGRID (163458)	Synergy 21-7-20 # 159 9. API Well No
	ress and Telephone No.		3.74.14461140
	•		30-043-21045
	P.O. Box 5513, Farmington, NM		10 Field and Pool, or Exploratory
4 Locat	ition of Well (Footage, Sec, T R , M, or Sun	vey Description)	D 1 m 24 10 1
	11-14 F 47001 FNII 0451 FN	W. O. O. TOAN DOTING	Basin Fruitland Coal
	Unit E, 1780' FNL, 845' FV	VL, Sec 20, 121N - R0/VV	11 County or Parish, State
	320 acres (N/2)		Sandoval County, NM
12. CF		INDICATE NATURE OF NOTICE, REPORT,	
	TYPE OF SUBMISSION	TYPE OF ACTION	
	National States		Channel of Di
	Notice of Intent	Abandoment	Change of Plans New Construction
X	Subsequent Report	Recompletion Plugging Back	Non-Routine Fracturing
123	Subsequent report	Casing Repair	Water Shut-Off
	Final Abandonment Notice	Altering Casing	Converion to Injection
		X Other: Deferral of Termination	Dispose Water
			Olds Daniel III 6 Wards III 1 184-18
			(Note Report results of multiple completion on Well
12 Decemb	on Brancood or Completed Operations /Class	du data all postinget datale, and also portinent datas, incl	Completion or recompletion Report and Log Form)
		rrly state all pertinent details, and give pertinent dates, inclusions and measured and true vertical depths for all markers a	Completion or recompletion Report and Log Form)
		irly state all pertinent details, and give pertinent dates, includes and measured and true vertical depths for all markers a	Completion or recompletion Report and Log Form)
If well is	directionally drilled give subsurface location		Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work
If well is -27-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi	ns and measured and true vertical depths for all markers a ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs	Completion or recompletion Report and Log Form) duding, estimated date of starting work and zones of pertinent to this work s w/ water. Drill to 33 feet. SDFN.
If well is -27-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro	ns and measured and true vertical depths for all markers a ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work sw/ water. Drill to 33 feet. SDFN. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing.
If well is -27-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7' KB, runni	ns and measured and true vertical depths for all markers a ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work sw/ water. Drill to 33 feet. SDFN. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing.
If well is	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro	ns and measured and true vertical depths for all markers a ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work sw/ water. Drill to 33 feet. SDFN. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing.
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line	ns and measured and true vertical depths for all markers and Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work s w/ water. Drill to 33 feet. SDFN. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. sing Setter & Move Rig to sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7' KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3)	ns and measured and true vertical depths for all markers and setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. es. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go	Completion or recompletion Report and Log Form) studing, estimated date of starting work and zones of pertinent to this work s w/ water. Drill to 33 feet. SDFN. s. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. sing Setter & Move Rig to sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line	ns and measured and true vertical depths for all markers and setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. es. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go	Completion or recompletion Report and Log Form) studing, estimated date of starting work and zones of pertinent to this work s w/ water. Drill to 33 feet. SDFN. s. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. sing Setter & Move Rig to sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7' KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca	ns and measured and true vertical depths for all markers and measured and true vertical depths for all markers and Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs and two (2) centralizers. Rig down Surface Cas in to Cement on 30th. Pers. Pump 15 bbls H2O ahead. Cement w/ 90 massing. Plug down at 9:34 hrs.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work Starting work
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7' KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca	ns and measured and true vertical depths for all markers and measured and true vertical depths for all markers and Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ing two (2) centralizers. Rig down Surface Cas in to Cement on 30th. Pers. Pump 15 bbls H2O ahead. Cement w/ 90 may 19.1 bbls cement slurry. Circulate 7.0 bbls going asing. Plug down at 9:34 hrs. In deferral of termination status. Active operations.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work s w/ water. Drill to 33 feet. SDFN. s. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. sing Setter & Move Rig to sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello od cement to surface. Displace 6.75 bbls to
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca Lease NMNM-99738 should be i	ns and measured and true vertical depths for all markers and measured and true vertical depths for all markers and Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ing two (2) centralizers. Rig down Surface Cas in to Cement on 30th. Pers. Pump 15 bbls H2O ahead. Cement w/ 90 may 19.1 bbls cement slurry. Circulate 7.0 bbls going asing. Plug down at 9:34 hrs. In deferral of termination status. Active operations.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work Sew/ water. Drill to 33 feet. SDFN. Sew. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. Sing Setter & Move Rig to Seacks Type 5 Cement w/ 2% CaCl & 1/4# Cello and cement to surface. Displace 6.75 bbls to ROUD OCT 2 'OT'
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca Lease NMNM-99738 should be i	ns and measured and true vertical depths for all markers and measured and true vertical depths for all markers and Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ing two (2) centralizers. Rig down Surface Cas in to Cement on 30th. Pers. Pump 15 bbls H2O ahead. Cement w/ 90 may 19.1 bbls cement slurry. Circulate 7.0 bbls going asing. Plug down at 9:34 hrs. In deferral of termination status. Active operations.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work s w/ water. Drill to 33 feet. SDFN. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. sing Setter & Move Rig to Sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello od cement to surface. Displace 6.75 bbls to
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca Lease NMNM-99738 should be i	ns and measured and true vertical depths for all markers and measured and true vertical depths for all markers and Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ing two (2) centralizers. Rig down Surface Cas in to Cement on 30th. Pers. Pump 15 bbls H2O ahead. Cement w/ 90 may 19.1 bbls cement slurry. Circulate 7.0 bbls going asing. Plug down at 9:34 hrs. In deferral of termination status. Active operations.	Completion or recompletion Report and Log Form) Iduding, estimated date of starting work and zones of pertinent to this work Starting work
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca Lease NMNM-99738 should be i	ns and measured and true vertical depths for all markers and measured and true vertical depths for all markers and Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ing two (2) centralizers. Rig down Surface Cas in to Cement on 30th. Pers. Pump 15 bbls H2O ahead. Cement w/ 90 may 19.1 bbls cement slurry. Circulate 7.0 bbls going asing. Plug down at 9:34 hrs. In deferral of termination status. Active operations.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work Sew/ water. Drill to 33 feet. SDFN. Sew. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. Sesing Setter & Move Rig to Seacks Type 5 Cement w/ 2% CaCl & 1/4# Cello and cement to surface. Displace 6.75 bbls to RCUD OCT 2 'O'T
If well is -27-2007 -28-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca Lease NMNM-99738 should be i	ns and measured and true vertical depths for all markers and measured and true vertical depths for all markers and Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ing two (2) centralizers. Rig down Surface Cas in to Cement on 30th. Pers. Pump 15 bbls H2O ahead. Cement w/ 90 may 19.1 bbls cement slurry. Circulate 7.0 bbls going asing. Plug down at 9:34 hrs. In deferral of termination status. Active operations.	Completion or recompletion Report and Log Form) Iduding, estimated date of starting work and zones of pertinent to this work Starting work
If well is 1-27-2007 1-28-2007 1-30-2007	directionally drilled give subsurface location MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca Lease NMNM-99738 should be i	ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. es. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go asing. Plug down at 9:34 hrs. n deferral of termination status. Active operatin 120 days per 43 CFR 3107.	Completion or recompletion Report and Log Form) Iduding, estimated date of starting work and zones of pertinent to this work Starting work
If well is -27-2007 -28-2007 -30-2007	MIRU Steve & Son Surface Casion Continue Drilling 12-1/4" hole fro Land Casing @ 126.7' KB, running Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" can Lease NMNM-99738 should be inplans forecasted to proceed with	ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. es. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls gor asing. Plug down at 9:34 hrs. In deferral of termination status. Active operating 120 days per 43 CFR 3107.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work S w/ water. Drill to 33 feet. SDFN. S. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. Sing Setter & Move Rig to P sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello and cement to surface. Displace 6.75 bbls to RCVD DCT 2 'O'T OIL CONS. DIV. DIST. 3
If well is -27-2007 -28-2007 -30-2007	MIRU Steve & Son Surface Casion Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, running Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" can be case NMNM-99738 should be included by plans forecasted to proceed with	ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. Ses. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go asing. Plug down at 9:34 hrs. In deferral of termination status. Active operation 120 days per 43 CFR 3107.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work S w/ water. Drill to 33 feet. SDFN. S. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. Sing Setter & Move Rig to P sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello and cement to surface. Displace 6.75 bbls to EXECUTED TOTAL CONS. DIV. DIST. 3 Manager Date: 09-30-2007
If well is -27-2007 -28-2007 -30-2007 14. I he Signed:	MIRU Steve & Son Surface Casion Continue Drilling 12-1/4" hole fro Land Casing @ 126.7' KB, running Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" call Lease NMNM-99738 should be inplans forecasted to proceed with the step of	ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. Ses. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go asing. Plug down at 9:34 hrs. In deferral of termination status. Active operation 120 days per 43 CFR 3107.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work S w/ water. Drill to 33 feet. SDFN. S. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. Sing Setter & Move Rig to P sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello and cement to surface. Displace 6.75 bbls to RCVD DCT 2 'OT' OIL CONS. DIV. DIST. 3
If well is -27-2007 -28-2007 -30-2007 14. I he Signed:	MIRU Steve & Son Surface Casion Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, running Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" can be case NMNM-99738 should be included by plans forecasted to proceed with	ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. Ses. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go asing. Plug down at 9:34 hrs. In deferral of termination status. Active operation 120 days per 43 CFR 3107.	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work S w/ water. Drill to 33 feet. SDFN. S. Run 3 Jts of 8-5/8" 24# K-55 Surface Casing. Sing Setter & Move Rig to P sacks Type 5 Cement w/ 2% CaCl & 1/4# Cello and cement to surface. Displace 6.75 bbls to EXECUTED TOTAL CONS. DIV. DIST. 3 Manager Date: 09-30-2007
If well is 1-27-2007 1-28-2007 1-30-2007 14. I he Signed:	MIRU Steve & Son Surface Casion Continue Drilling 12-1/4" hole fro Land Casing @ 126.7' KB, running Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" cast Lease NMNM-99738 should be inplans forecasted to proceed with the plans forecasted to proceed with the step of the plans forecasted to proceed with the step of the plans forecasted to proceed with the step of the plans forecasted to proceed with the plans fore	ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. Ses. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go asing. Plug down at 9:34 hrs. In deferral of termination status. Active operation 120 days per 43 CFR 3107.	Report and Log Form) Relating, estimated date of starting work and zones of pertinent to this work Sew/ water. Drill to 33 feet. SDFN. Sew/ water. Drill to 34 feet. SDFN. Sew/ water. Drill to
### 14. he Signed: This space	MIRU Steve & Son Surface Casion Continue Drilling 12-1/4" hole fro Land Casing @ 126.7' KB, running Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" cast Lease NMNM-99738 should be inplans forecasted to proceed with the plans forecasted to proceed with the step of the plans forecasted to proceed with the step of the plans forecasted to proceed with the step of the plans forecasted to proceed with the plans fore	ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. Ses. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go asing. Plug down at 9:34 hrs. In deferral of termination status. Active operation 120 days per 43 CFR 3107. Title: Engineering tom.mullins	Completion or recompletion Report and Log Form) Ruding, estimated date of starting work and zones of pertinent to this work Starting work and zones of pertinent to this work Starting work and zones of pertinent to this work Starting Water. Drill to 33 feet. SDFN. Starting Setter & Move Rig to Starting S
14. I he Signed: Approve	MIRU Steve & Son Surface Casi Continue Drilling 12-1/4" hole fro Land Casing @ 126.7" KB, runni Synergy 22-7-31 # 144 well. Pla MIRU Key Cementers. Test Line 15.5 ppg (1.19 yield - 107.1 ft3) leave 20' cement inside 8-5/8" ca Lease NMNM-99738 should be i plans forecasted to proceed with	ng Setter Rig. Spud 12-1/4" hole at 17:15 hrs m 33 feet to 126.7' KB. COOH w/ 6-1/4" DCs ng two (2) centralizers. Rig down Surface Cas n to Cement on 30th. Ses. Pump 15 bbls H2O ahead. Cement w/ 90 19.1 bbls cement slurry. Circulate 7.0 bbls go asing. Plug down at 9:34 hrs. In deferral of termination status. Active operation 120 days per 43 CFR 3107. Title: Engineering tom.mullins	Report and Log Form) Relating, estimated date of starting work and zones of pertinent to this work Sew/ water. Drill to 33 feet. SDFN. Sew/ water. Drill to 34 feet. SDFN. Sew/ water. Drill to