

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0137
Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1 Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2 Name of Operator

XTO ENERGY INC.

3a Address

382 CR 3100

3b. Phone No (include area code)

505-333-3100

4 Location of Well (Footage, Sec, T., R., M., or Survey Description)

1630' ENL & 885' FWL SEC 36E-T32N-R14W

5 Lease Serial No.

BIA 14-20-604-62

6. If Indian, Allottee or Tribe Name

UTE MOUNTAIN UTE

7. If Unit or CA/Agreement, Name and/or No
N/A

8. Well Name and No.

UTE INDIANS A #65

9. API Well No.

30-045-34295

10. Field and Pool, or Exploratory Area

UTE DOME PARADOX

11. County or Parish, State

SAN JUAN NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☒ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☐ Other _____

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

Please see attachment for changes to the surface casing & cement.

RCVD OCT 25 '07

OIL CONS. DIV.

DIST. 3

RECEIVED

OCT 16 2007

Bureau of Land Management
Durango, Colorado

14 I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

MORRI D. BINGHAM

Title

REGULATORY COMPLIANCE TECH

Date 10/15/07

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



Lorri Bingham/FAR/CTOC

10/12/2007 09:02 AM

To

cc

bcc

Subject

Lorri,

Would you mind filing this sundry on this well?

Surface Casing: 9.625" casing to be set at 850' in a 12-1/4" hole filled with 9.20 ppg mud

| Interval | Length | Wt | Gr | Cplg | Coll Rating (psi) | Burst Rating (psi) | Jt Str (M-lbs) | ID (in) | Drift (in) | SF Coll | SF Burst | SF Ter |
|----------|--------|-------|------|------|-------------------|--------------------|----------------|---------|------------|---------|----------|--------|
| 0'-850' | 850' | 36.0# | J-55 | ST&C | 2020 | 3520 | 394 | 8.921 | 8.765 | 4.97 | 8.656 | 12.88 |

Cement:

LEAD:

±196 sx of Premium Lite FM (Type III/Poz/Gel) or equivalent, with dispersant, fluid loss, accelerator, & LCM mixed at 12.1 ppg, 2.13 ft³/sk, 11.29 gal wtr/sx.

TAIL:

100 sx of Type III cement (or equivalent) typically containing accelerator and LCM, mixed at 15.2 ppg, 1.28 ft³/sk, & 5.77 gal wtr/sk.