This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator ConocoPhillips Inc.					Lease Name JICARILLA A						Well No. 13
Location of We	ll: Unit	Letter	E 5	Sec 13	Twp	026N	l Rg	ge .	004W	API #	[‡] 30-039-20395
!	Name of Reservoir or Pool			ol (Type of Prod			Method of Prod			Prod Medium
Upper Completion	PC			(Gas			Flow			Tubing
Lower Completion	DK			C	Gas						Tubing
				Pre-Flo	w Shut-In	Pressi	ıre Data				
Upper	Hour, D	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG			Stabilized?(Yes or No)
Completion	9/10/2007			ar are sultaneous	13 hours				Flow		Yes
Lower Completion		Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG			Stabilized?(Yes or No)
9/10/2007				733 hours				N		Yes	
					Flow Tes	t No. 1					
Commenced a		Ž	Zone Pro	oducing	(Upper or Lower): Upper						
Time Lapsed (date/time) Sin		ed Time	PF	RESSURE		Prod 2					
		Si	nce*	Upper zo	ne Lowe	er zone	Tempe	rature	F		Remarks
9/10/2007 1:47:58 PM			0	168		186		Da			
9/10/2007 1:52:19 PM		0		168		186			Day 1.		
9/11/2007 1:52:46 PM		24		234		278			Day 2.		
9/12/2007 1:53:16 PM		48		241		283			Day 3, turned on lower zone.		
9/13/2007 1:54:06 PM			72	244		136	<u> </u>		Day 4, test completed.		
10/10/2007 1:48:31 PM 720			234	!		1					
Production rate	during	test					,				
Oil: BPOD Based on: B				Bbls. In	Bbls. In Hrs.			Grav. GOR			
Gas		MCF	PD; Test th	nru (Orifice c	or Meter)						
				Mid-Tes	st Shut-In	Process	ıre Data		•		, •
Upper Completion				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)
Lower Completion	1 '			Len	Length of Time Shut-In			SI Press. PSIG Stabilized?(Yes or No)			Stabilized?(Yes or No)
				(Cor	itinue on r	everse s	side)		2031	RE	6789707723

Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)						
Time	Lapsed Time	PRES	SURE	Prod Zone		Remarks				
(date/time)	Since*	Upper zone	Lower zone	Temperature						
	1			(
		;	1			!				
	i 	1	· · · · · · · · · · · · · · · · · · ·							
·		1 0 1		<u> </u>						
	1	,	1	1	1 1 SAME					
			 	<u> </u>						
		i 				i				
Production rate during	test t									
Oil: BPO	D Based on:	Bbls. In	Hrs.	(Grav.	GOR				
Gas MCFPD; Test thru (Orifice or Meter)										
Remarks:										
Remarks.										
				(
I hereby certify that the information herein contained is true and complete to the best of my knowledge.										
Approved: NOV	12 2007	20	Operat	Operator: ConocoPhillips Inc.						
	enservation Division		By:	By: Augustine Gomez						
	nueva			A PER SECURITION OF THE RESIDENCE OF THE SECURITION OF THE SECURITIES OF THE SECURIT						
1 -			ı itle:	Title: Multi-Skilled Operator						
Title: Deput	ty Oil & Gas Insp District #3	ector,	Date: _	Date: Friday, October 26, 2007						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- 6 Flow Test No 2 shall be conducted even though no leak was indicated during Flow Test No 1 Procedure for Flow Test No 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above