This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## **Oil Conservation Division**

## **Northwest New Mexico Packer-Leakage Test**

Page 1 Revised June 10, 2003

Operator ConocoPhillips Inc.				Lease Name JICARILLA K						Well No. 18
Location of We	ell: Unit L	etter M	Sec	02	Twp	025N	Rge	005W	API#	30-039-20567
	Name of Reservoir or Pool			Type of Prod				Method of Prod		Prod Medium
Upper Completion	PC		Gas			Flow	Flow		Casing	
Lower Completion	СН		Gas			Flow			Tubing	
			Р	re-Flow S	Shut-In	Pressu	re Data			
Upper	Hour, Dat	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)
Completion	9/10	0/2007	80 hours			Flo	Flow		Yes	
Lower	Hour, Date, Shut-In			Length of Time Shut-In			SI Pre	SI Press. PSIG		Stabilized?(Yes or No)
Completion	9/10	0/2007	9 hours			Flo	ow		Yes	
Commenced	at: 9/10/	/2007 9:30:00	) AM	Flo	ow Test		ducing (Uppe	r or Lowe	r): Low	er
Time Lapsed Time (date/time) Since*		me	PRESSURE			Prod Zone				
				Upper zone Lower		r zone	Temperature	•	Remarks	
9/11/2007 8:48:53 AM		23		106	3(	65		both zones shut in		
9/12/2007 8:49:44 AM 47				109 368			turn on ch zone			
9/13/2007 8:55:04 AM 71				112 90			flowed ch zone			
Production rate	e during te	est	·							
Oil:	_BPOD E	Based on:	B	bls. In		Hrs.		Grav.		GOR
Gas		MCFPD;	Test thru (C	rifice or N	/leter) _					·
			N	/lid-Test S	Shut-In	Praesii	re Data		•	•
Upper Completion	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG			Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		,	Stabilized?(Yes or No)

(Continue on reverse side)



## Flow Test No. 2

Commenced at:		Zone Producing (Upper or Lower)								
Time	Lapsed Time			Prod Zone						
(date/time)	Since*	Upper zone	Lower zone	Temperature	9	Remarks				
						/				
Production rate du	ring test									
Oil:BF	POD Based on:	Bbls. In	Hrs.		Grav.	GOR				
Gas MCFPD; Test thru (Orifice or Meter)										
Remarks:			•							
Nemarks.	•			, .						
I hereby certify that the information herein contained is true and complete to the best of my knowledge.										
Approved: NOV	1 2 2007	20	Operat	tor: Conoco	Dhilling Inc					
<del></del>	-	20	_	tor: Conocol						
New Mexico Oil	Conservation Division		By:	Damian Cas	ssador					
By: H. Vill	anueva Deputy Oil & Gas Ins	enactor	Title:	Multi-Skilled	Operator					
Title:	District #3	эрсого,	Date:	Date: Friday, October 05, 2007						

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed Tests shall also be taken at any time that communication is suspected or when
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4 For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the
- atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3