

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr , Hobbs, NM 87240
District II
1301 W. Grand Ave , Artesia, NM 88210
District III
1000 Rio Brazos Rd , Aztec, NM 87410
District IV
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-045-22814
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: HAMPTON
8. Well Number #3A
9. OGRID Number 5380
10. Pool name or Wildcat BLANCO MESAVERDE

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other	7. Lease Name or Unit Agreement Name: HAMPTON
2. Name of Operator XTO Energy Inc.	8. Well Number #3A
3. Address of Operator 382 CR 3100 AZTEC, NM 87410	9. OGRID Number 5380
4. Well Location Unit Letter <u>D</u> : <u>700</u> feet from the <u>NORTH</u> line and <u>655</u> feet from the <u>WEST</u> line Section <u>10</u> Township <u>30N</u> Range <u>11W</u> NMPM County <u>SAN JUAN</u>	10. Pool name or Wildcat BLANCO MESAVERDE
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 5658' GR	
Pit or Below-grade Tank Application ☐ or Closure ☐ Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐	REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐	CASING TEST AND CEMENT JOB ☐
OTHER: REPAIR CASING ☒	OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

XTO Energy, Inc. repaired the casing in this well per the attached morning report. RCVD NOV 15 '07
OIL CONS. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Lorri D. Bingham TITLE REGULATORY COMPLIANCE TECH DATE 11/14/07
E-mail address: Lorri_bingham@xtoenergy.com
Type or print name LORRI D. BINGHAM Telephone No. 505-333-3100

For State Use Only

APPROVED BY H. Villanueva TITLE Deputy Oil & Gas Inspector DATE NOV 15 2007
Conditions of Approval, if any: District #3

Hampton #3A Casing Repair MR

10/4/07 Anchors tstd 9/07. MIRU Triple P Rig #6. Cycled PM plngr to surf. RIH & ret ball & trvlg sprg. Bd well. Ppd dwn tbg w/20 bbls 2% KCl wtr & KW. ND WH. NU BOP. PU & TIH w/4 jts 2-3/8" tbg w/no tg (EOT @ 4,803'). TOH & LD 4 jts tbg. TOH w/147 jts 2-3/8" tbg, SN & NC. TIH w/Weatherford 7" RBP & 55 jts tbg. Set RBP @ 1,750' FS. TOH & LD 1 jt tbg. SWI. SDFN. Called for night watchman.

10/5/07 Bd well. Attd ld 7" csg w/84 bbls 2% KCl wtr. Could not ld 7" csg. TOH w/54 jts 2-3/8" tbg & setting tl. PU & TIH w/7" pkr & 1 jt tbg. PT 7" csg to 200 psig for 5' w/1 bbl 2% KCl wtr. Tstd OK. Rlsd press. TIH w/53 jts tbg. Set pkr @ 1,725'. PT RBP @ 1,750' to 925 psig for 30" w/4 bbls 2% KCl wtr. Tstd OK. PT 7" csg to 500 psig for 15" w/1 bbl 2% KCl wtr. Tstd OK. TOH w/54 jts tbg & pkr. MIRU BWWC WLU. Run CCL/CBL log fr/1,750' - surf. Gd cmt fr/1,750' (RBP) - 1,380'. Erratic cmt bond fr/1,380' - surf. RDMO BWWC WL trk. SWI. SDFN. Called for night watchman.

10/6/07 TIH w/NC, SN (SV) & 54 jts 2-3/8" tbg. RU swb tls. BFL surf. S. 0 BO, 71 BLW, 33 Runs, 6 hrs, FFL 1,550' FS. Cln fld smpl w/no solids. FTP 0 psig. SICP (7") 0 psig. SICP (9-5/8") 0 psig. SWIFPBU. SDFWE. Called for night watchman.

10/9/07 Bd tbg. RU swb tls. BFL 1,300' FS. S. 0 BO, 3 BLW, 1 run, 15", FFL 1,300' FS. Cln fld smpl w/no solids. FTP 0 psig. SICP 200 psig. RD swb tls. Bd 7" csg & 9-5/8" csg. Ld 7" csg w/65 bbls 2% KCl wtr. PT tst csg w/foolwing results; 7" csg fr/533' - 1,750' to 1,010 psig for 5" w/1/4 bbl 2% KCl wtr. 7" csg fr/512' - surf to 1,010 psig for 5" w/1/4 bbl 2% KCl wtr. Tstd OK. Rlsd press. Found csg lk fr/512' - 533'. TOH w/16 jts tbg & pkr. TIH w/setting tl & 55 jts tbg. Unset RBP @ 1,750'. TOH w/33 jts tbg. Set RBP @ 695'. TOH w/22 jts tbg & setting tl. TIH w/pkr & 17 jts tbg. Ld 7" csg w/21 bbls 2% KCl wtr. Set pkr @ 553'. PT RBP @ 695' to 1,500 psig for 5". Tstd OK. Rlsd press. Unset pkr. TOH w/2 jts tbg. Set pkr @ 491'. Attd to EIR. Could not EIR. Press dropd fr/1,500 - 900 psig in 1". SWI. SDFN. Called for night watchman.

10/10/07 Unset pkr @ 491'. TOH w/15 jts 2-3/8" tbg & pkr. TIH w/NC, 16 jts tbg & 2-3/8" x 10 tbg sub. EOT @ 516'. MIRU H&M pmp trk. Ppd 100 gals 15% HCl ac dwn tbg. EIR @ 1 BPM @ 1,200 psig. Flshd w/7 bbls 2% KCl. TOH w/2-3/8 x 10' tbg sub, 16 jts tbg & NC. TIH w/setting tl & 22 jts tbg. Caught & rlsd RBP @ 695'. TOH w/22 jts tbg, setting tl & RBP. TIH w/CIBP, setting tl & 22 jts tbg. Set CIBP @ 695'. TOH w/22 jts tbg & setting tl. TIH w/pkr & 17 jts tbg. Ld 7" csg w/30 bbls 2% KCl wtr. Set pkr @ 553'. PT RBP @ 695' to 1,500 psig w/1 bbl 2% KCl wtr. Tstd OK. Rlsd press. Unset pkr @ 553'. TOH w/17 jts tbg & pkr. TIH w/cmt ret, 12 jts tbg & 2 - 2-3/8" tbg subs (4' & 10'). Set cmt ret @ 402'. PT tbg to 1,500 psig for 5" w/1/4 bbl 2% KCl wtr. Tstd OK. Rlsd press. PT 7" csg fr/402' - surf to 1,500 psig for 5" w/1/4 bbl 2% KCl wtr. Tstd OK. Rlsd press. MIRU Schulmberger cmt pmp trk. PT Ins to 1,931 psig. Ppd dwn tbg w/4 BFW @ 1/2 BPM & 938 psig. Ppd dwn tbg w/75 sxs Class G cmt, 0.1% D046, 5.0% D154, 0.5% D202, 0.5% 400, 0.2% D176, 1.0% S001 & 2.0% CaCl (mixed @ 15.6, 1.21 cu ft/sx, 90.75 cu/ft). Ppd dwn tbg w/17 bbls cmt @ 1/2 BPM & avg 1,150 psig. Flshd w/1.5 BFW @ 1/2 BPM & 1,698 psig. Final sqz press @ 1,705 psig. Ppd 12 bbls cmt outside csg. Sting out fr/cmt ret. TOH w/2 - 2-3/8" tbg subs (10' & 4'), 12 jts tbg & setting tl. Ld 7" csg w/2 BFW. SWI. SDFN. 200 BLWTR. Recd approval fr/Herman Lujan w/BLM & Henry Villanueva 8:15 a.m. 10/9/07 prior to cmt operations.

Hampton #3A Casing Repair MR

10/11/07 PU & TIH w/6-1/4" bit, XO, 6 - 4" DCs, 2 - XOs, SN & 6 jts 2-3/8" tbg. Tgd cmt @ 388' (14' of cmt). RU pwr swivel. DO cmt fr/388' - 402'. DO cmt ret @ 402'. SWI. SDFN. Called for nightwatch man.

10/12/07 RU pwr swivel. Estb circ w/FW. DO CICR @ 402'. DO cmt fr/402' - 452'. Circ cln. RD pwr swivel. TOH w/1 jt tbg. SWI. SDFN. 200 BLWTR. Called for night watchman.

10/13/07 TIH w/1 jt 2-3/8" tbg. RU pwr swivel. Estb circ w/FW. DO cmt fr/452' - 510' (BOC). Circ cln. RD pwr swivel. PT sqz to 590 psig for 30" w/chart. Press dropd fr/590 - 570 psig. Tstd OK. Rlsd press. TIH w/7 jts tbg. Tgd @ 685' (10' of fill). RU pwr swivel. Estb circ w/FW. CO fill fr/685' - 695' (CIBP). Circ cln w/30 bbls 2% KCl wtr. RD pwr swivel. TOH w/14 jts, XO, 6 - 4-1/8" DC's, XO & 6-1/4" bit. SWI. SDFWE. 200 BLWTR. Called for night watchman.

10/16/07 MIRU Hurricane AFU. TIH w/6-1/4" rotary shoe, MJ tl, jars, 6 - 4-1/8" DC's, XO & 17 jts 2-3/8" tbg. Tgd @ 695' (CIBP). RU pwr swivel. Estb circ w/2% KCl wtr. Att'd to set MJ tl w/o success. MI over 6" of CIBP. Lost circ. Estb circ w/AFU. Fin MI over CIBP. Ppd dwn csg w/20 bbls 2% KCl wtr & KW. TOH w/17 jts tbg & BHA. Recd packing element & upr cone assy in shoe. TIH w/5-3/4" OS w/3-3/4" grapple, bmr sub, jars, 6 - 4-1/8" DC's & 65 jts tbg. Tgd @ 2,299' (TOL). Att'd to catch CIBP mandrel. TOH w/65 jts tbg & BHA w/o fish. SWI. SDFN. Used 10 bbls 2% KCl wtr w/AFU. Recd 0 BO, 10 BLW w/AFU.

10/17/07 Bd well. TIH w/NC, SN & 73 jts 2-3/8" tbg. Tgd @ 2,099' (TOF). TOH w/tbg, SN & NC. TIH w/5-3/4" OS w/3-3/4" grapple, bmr sub, jars, 6 - 4-1/8" DC's, XO & 65 jts tbg. Tgd @ 2,099' (TOF). Caught fish. Wrkd tbg to 50K. Fish pulled free. Ppd dwn csg w/10 bbls 2% KCl wtr & KW. TOH w/65 jts tbg & BHA. Recd fish (missing pc of lwr cone assy). SWI 1 hr. SICP 150 psig. SIBHP 70 psig. Bd BH. Press to 40 psig in 10". Bd well. TIH w/3-7/8" bit, XO & 147 jts tbg. PU & TIH w/1 jt tbg. Tgd @ 4,672'. RU pwr swivel. Estb circ w/AFU. Wrkd pc of lwr cone assy to 4,822' (PBSD). Circ cln. RD pwr swivel. TOH & LD w/4 jts tbg. TOH w/147 jts tbg, XO & 3-7/8" bit. SWI. SDFN. Used 16 bbls 2% KCl wtr w/AFU. Recd 0 BO, 26 BLW w/AFU. 220 BLWTR. Called for night watchman.

10/18/07 Bd well. TIH w/Weatherford 7" RBP & 12 jts 2-3/8" tbg. Set @ 394'. SWI 30". SICP 0 psig. SIBHP 0 psig. Rlsd RBP. SWI 30". SICP 140 psig. SIBHP 17 psig. Bd well. Set RBP @ 394'. Ld csg w/4 bbls 2% KCl wtr. Circ cln. TOH w/12 jts tbg & setting tl. PT RBP to 840 psig for 15". Press dropd fr/840-830 psig. Rlsd press RBP lkg. TIH w/setting tl & 12 jts tbg. Caught & rlsd RBP @ 394'. TOH w/12 jts tbg & RBP. Rplcd RBP. TIH w/RBP & 12 jts tbg. Set RBP @ 394'. Ld csg w/4 bbls 2% KCl wtr. Circ cln. TOH w/12 jts tbg & setting tl. PT RBP to 500 psig for 5". Tsd OK. Rlsd press. ND BOP. ND tbg hngr. Found tbg hngr w/o secondary seal. NU used 11" x 7-1/16" 2K flg tbg hngr. NU BOP. SWI. SDFN. Called for night watchman.

10/19/07 TIH w/setting tl & 12 jts 2-3/8" tbg. Caught & rlsd RBP @ 390'. SWI 30". SICP 230 psig. SIBHP 0 psig. Bd well. TOH & LD RBP & 12 jts tbg. TIH w/NC, SN & 147 jts 2-3/8" tbg. RIH w/XTO's 1.910" tbg broach to SN. POH w/tbg broach. LD w/tbg broach. Ld tbg w/donut & 2-3/8" seal assy as follows: SN @ 4,671. EOT @ 4,672'. MV perfs fr/4,113' - 4,758'. PBSD @ 4,822'. ND BOP. NU WH. RU Swb tls. BFL 3,700' FS. S. 0 BO, 37 BLW, 12 runs 4 hrs, FFL 2,800'. Tbg flwg 10" after each swb run. Cln fld smpl w/o solids. SICP 220 psig. FTP 120 psig. SWI.

10/20/07 Bd tbg. RU Swb tls. BFL 3,900' FS. S. 0 BO, 4 BLW, 1 run, 30". Tbg KO flwg. F. 0 BO, 1 BLW 2" ck, 2 hrs. FTP 15 psig. SICP 240-180 psig. SWIFPBU.

RDMO Triple P #6.

Hampton #3A Casing Repair MR

10/23/07PL. 24 hrs O&W prod.